

Supermicro - AS -2125HS-TNR, HS219-R16H13, HS219-16 : AS -2125HS-TNR, HS219-R16H13, HS219-16

| Specifications | |
|--|--|
| ENERGY STAR Unique ID: | 3629843 |
| ENERGY STAR Partner: | Super Micro Computer, Inc. |
| Brand Name: | Supermicro |
| Model Name: | AS -2125HS-TNR, HS219-R16H13, HS219-16 |
| Model Number: | AS -2125HS-TNR, HS219-R16H13, HS219-16 |
| Form Factor: | Rack-mount |
| Resilient System: | No |
| Available Expansion Slots: | 2 |
| Operating Systems Supported: | Windows |
| Power Saving Features Available: | Other |
| Product Processor Socket Count: | 2 |
| Available DIMM Slots: | 24 |
| Maximum Memory Capacity (GB): | 6000.0 |
| Installed Processors for Typical or Single Configuration: | 2 |
| Cores Per Processor Typical or Single Configuration: | 192 |
| Number of Threads for Typical or Single Configuration: | 384 |
| Processor Brand Typical or Single Configuration: | AMD |
| Processor Model Name Typical or Single Configuration: | AMD EPYC 9654 |
| Processor Speed for Typical or Single Configuration (GHz): | 2.4 |
| Num. of DDR Channels for Typical or Single Configuration: | 14 |
| Memory Speed Typical or Single Configuration (GHz): | 4.1 |
| Typical or Single Configuration Size Per DIMM (GB): | 96 |
| Installed Num. DIMMs for Typical or Single Configuration: | 24 |
| Installed Memory for Typical or Single Configuration (GB): | 2304.0 |

| Typical or Single Configuration Redundant Power Supply: | Yes |
|---|------------------------------|
| SERT Active State Efficiency Score Typical or Single Configuration: | 74.50 |
| SERT Version : | Other |
| SERT Version Other: | 2.0.7 |
| 64-bit Architecture: | 64-bit supported |
| Date Available On Market: | 2024-03-01 |
| Date Certified: | 2024-10-03 |
| Markets: | United States, Japan, Canada |
| ENERGY STAR Certified: | Yes |

Captured On: 06/17/2025