

## AUTEL - Maxi UF19L101 : Maxi UF19L101

SpecificationsBrand Name:AUTELModel Name:Maxi UF19L101Model Number:Maxi UF19L101ENERGY STAR Unique ID:2500043ENERGY STAR Partner:Autel Digital Power Co., Ltd.Product Type:Level 2Input Voltage (V):240.0Maxinum Output Power (kW):19.2Number of Outputs:1Maxinum Output Cord Length (ft.):25Output Cord Gauge (AWG):6	
Model Name:Maxi UF19L101Model Number:Maxi UF19L101ENERGY STAR Unique ID:2500043ENERGY STAR Partner:Autel Digital Power Co., Ltd.Product Type:Level 2Input Voltage (V):240.0Maximum Output Current (A):80Number of Outputs:1Number of Outputs:25	
Model Number:Maxi UF19L101ENERGY STAR Unique ID:2500043ENERGY STAR Partner:Autel Digital Power Co., Ltd.Product Type:Level 2Input Voltage (V):240.0Maximum Output Current (A):80Number of Outputs:19.2Number of Outputs:1Maximum Output Current (ft.):25	
ENERGY STAR Unique ID:2500043ENERGY STAR Partner:Autel Digital Power Co., Ltd.Product Type:Level 2Input Voltage (V):240.0Max Nameplate Output Current (A):80Maximum Output Power (kW):19.2Number of Outputs:1Maximum Output Cord Length (ft.):25	
ENERGY STAR Partner:Autel Digital Power Co., Ltd.Product Type:Level 2Input Voltage (V):240.0Max Nameplate Output Current (A):80Maximum Output Power (kW):19.2Number of Outputs:1Maximum Output Cord Length (ft.):25	
Product Type:Level 2Input Voltage (V):240.0Max Nameplate Output Current (A):80Maximum Output Power (kW):19.2Number of Outputs:1Maximum Output Cord Length (ft.):25	
Input Voltage (V):240.0Max Nameplate Output Current (A):80Maximum Output Power (kW):19.2Number of Outputs:1Maximum Output Cord Length (ft.):25	
Max Nameplate Output Current (A):80Maximum Output Power (kW):19.2Number of Outputs:1Maximum Output Cord Length (ft.):25	
Maximum Output Power (kW):19.2Number of Outputs:1Maximum Output Cord Length (ft.):25	
Number of Outputs: 1   Maximum Output Cord Length (ft.): 25	
Maximum Output Cord Length (ft.): 25	
Output Cord Gauge (AWG): 6	
Maximum (100%) Measured Luminance of the 905.0 High Res Display (candelas per m2):	
Automatic Brightness Control (ABC) Capable?: No	
Network Connection Types Available: Wi-Fi or Gigabit Ethernet	
Screen Area, if EVSE has high res display (in2): 27.2	
Auxiliary Product Features:     High Resolution Display,PLC Board (ISO 15118),Credit Card       Reader,Radio Frequency Identification (RFID)	
15 A Operation Mode Test: Total Loss (watts): 30.0	
<b>30 A Operation Mode Test: Total Loss (watts):</b> 30.0	
4 A Operation Mode Test: Total Loss (watts): 10.0	
Full Current Operation Mode Test: Total Loss220.0(watts):	
Idle Mode Input Power (watts):20.1	
Idle Mode Power Factor: 0.42	
Idle Mode Total Allowance (watts): 48.52	
No Vehicle Mode Input Power (watts): 5.9	
No Vehicle Mode Power Factor: 0.27	
No Vehicle Mode Total Allowance (watts): 16.52	
Partial On Mode Input Power (watts): 6.84	
Partial On Mode Power Factor: 0.28	
Partial On Mode Total Allowance (watts): 16.52	
<b>Date Certified:</b> 2023-05-25	

,Maxi UF19C101,

Captured On: 04/28/2025