Auxus - UCS-DP-48S-40FT : UCS-DP-48S-40FT

Specifications Brand Name: Auxus Model Name: UCS-DP-48S-40FT Model Number: UCS-DP-48S-40FT ENERGY STAR Unique ID: 3462868 ENERGY STAR Partner: ZHONGSHAN AUXUS ELECTRONIC TECHNOLOGY CO.#LTD Product Type: Level 2 Input Voltage (V): 240.0 Max Nameplate Output Current (A): 48 Maximum Output Power (kW): 11.52 Number of Outputs: 1 Maximum Output Cord Length (ft.): 40 Output Cord Gauge (AWG): 8 Automatic Brightness Control (ABC) Capable?: No Network Connection Types Available: Wi-Fi or Gigabit Ethernet Auxilliary Product Features: Radio Frequency Identification (RFID) 15 A Operation Mode Test: Total Loss (watts): 18.0 4 A Operation Mode Test: Total Loss (watts): 18.0 Full Current Operation Mode Test: Total Loss (watts): 18.0 Idle Mode Input Power (watts): 6.63 Idle Mode Power Factor: 0.33 Idle Mode Total Allowance (watts): 2.5.7 No Vehicle Mode Total Allowance (watts): 0.12 No Vehicle Mode Total Allowance (watts): 0.5 Partial On Mode Input Power (watts): 2.13	_	
Model Name: Model Number: UCS-DP-48S-40FT ENERGY STAR Unique ID: 3462868 ENERGY STAR Partner: Product Type: Level 2 Input Voltage (V): Max Nameplate Output Current (A): Maximum Output Power (kW): 11.52 Number of Outputs: Maximum Output Cord Length (ft.): Maximum Output Cord Length (ft.): Motwork Connection Types Available: Mutiliary Product Features: Auxiliary Product Features: Badio Frequency Identification (RFID) 15 A Operation Mode Test: Total Loss (watts): 18.0 4 A Operation Mode Test: Total Loss (watts): Illo Urrent Operation Mode Test: Total Loss (watts): Illo Mode Input Power (watts): 6.63 Idle Mode Input Power (watts): 25.7 No Vehicle Mode Input Power (watts): 0.12 No Vehicle Mode Power Factor: 0.12 No Vehicle Mode Input Power (watts): 6.5 Partial On Mode Input Power (watts): 2.13	Specifications	
Model Number: UCS-DP-48S-40FT ENERGY STAR Unique ID: 3462868 ENERGY STAR Partner: ZHONGSHAN AUXUS ELECTRONIC TECHNOLOGY CO.#LTD Product Type: Level 2 Input Voltage (V): 240.0 Max Nameplate Output Current (A): 48 Maximum Output Power (kW): 11.52 Number of Outputs: 1 Maximum Output Cord Length (ft.): 40 Output Cord Gauge (AWG): 8 Automatic Brightness Control (ABC) Capable?: No Network Connection Types Available: Wi-Fi or Gigabit Ethernet Auxilliary Product Features: Radio Frequency Identification (RFID) 15 A Operation Mode Test: Total Loss (watts): 18.0 30 A Operation Mode Test: Total Loss (watts): 18.0 4 A Operation Mode Test: Total Loss (watts): 18.0 Full Current Operation Mode Test: Total Loss (watts): 101.0 (watts): Idle Mode Input Power (watts): 25.7 No Vehicle Mode Input Power (watts): 2.07 No Vehicle Mode Power Factor: 0.12 No Vehicle Mode Input Power (watts): 6.5 Partial On Mode Input Power (watts): 2.13	Brand Name:	Auxus
ENERGY STAR Unique ID: 3462868 ENERGY STAR Partner: ZHONGSHAN AUXUS ELECTRONIC TECHNOLOGY CO.#LTD Product Type: Level 2 Input Voltage (V): 240.0 Max Nameplate Output Current (A): 48 Maximum Output Power (kW): 11.52 Number of Outputs: 1 Maximum Output Cord Length (ft.): 40 Output Cord Gauge (AWG): 8 Automatic Brightness Control (ABC) Capable?: No Network Connection Types Available: Wi-Fi or Gigabit Ethernet Auxiliary Product Features: Radio Frequency Identification (RFID) 15 A Operation Mode Test: Total Loss (watts): 18.0 30 A Operation Mode Test: Total Loss (watts): 46.0 4 A Operation Mode Test: Total Loss (watts): 18.0 Full Current Operation Mode Test: Total Loss (watts): 101.0 (watts): Idle Mode Input Power (watts): 25.7 No Vehicle Mode Input Power (watts): 2.07 No Vehicle Mode Power Factor: 0.12 No Vehicle Mode Input Power (watts): 6.5 Partial On Mode Input Power (watts): 2.13	Model Name:	UCS-DP-48S-40FT
ENERGY STAR Partner: Product Type: Level 2 Input Voltage (V): Ax Nameplate Output Current (A): Max Nameplate Output Current (A): Maximum Output Power (kW): Number of Outputs: 1 Maximum Output Cord Length (ft.): Output Cord Gauge (AWG): Automatic Brightness Control (ABC) Capable?: No Network Connection Types Available: Maxiliary Product Features: Radio Frequency Identification (RFID) 15 A Operation Mode Test: Total Loss (watts): 30 A Operation Mode Test: Total Loss (watts): 4 A Operation Mode Test: Total Loss (watts): Ille Urrent Operation Mode Test: Total Loss (watts): Idle Mode Input Power (watts): 10 0.33 Idle Mode Total Allowance (watts): 20.7 No Vehicle Mode Input Power (watts): 0.12 No Vehicle Mode Input Power (watts): 0.5 Partial On Mode Input Power (watts): 2.13	Model Number:	UCS-DP-48S-40FT
Product Type: Level 2 Input Voltage (V): 240.0 Max Nameplate Output Current (A): 48 Maximum Output Power (kW): 11.52 Number of Outputs: 1 Maximum Output Cord Length (ft.): 40 Output Cord Gauge (AWG): 8 Automatic Brightness Control (ABC) Capable?: No Network Connection Types Available: Wi-Fi or Gigabit Ethernet Auxiliary Product Features: Radio Frequency Identification (RFID) 15 A Operation Mode Test: Total Loss (watts): 18.0 30 A Operation Mode Test: Total Loss (watts): 18.0 4 A Operation Mode Test: Total Loss (watts): 18.0 Full Current Operation Mode Test: Total Loss (watts): 101.0 (watts): dide Mode Input Power (watts): 25.7 No Vehicle Mode Input Power (watts): 2.07 No Vehicle Mode Power Factor: 0.12 No Vehicle Mode Total Allowance (watts): 6.5 Partial On Mode Input Power (watts): 2.13	ENERGY STAR Unique ID:	3462868
Input Voltage (V): Max Nameplate Output Current (A): Maximum Output Power (kW): Number of Outputs: I Maximum Output Cord Length (ft.): Output Cord Gauge (AWG): Automatic Brightness Control (ABC) Capable?: No Network Connection Types Available: Auxiliary Product Features: Radio Frequency Identification (RFID) 15 A Operation Mode Test: Total Loss (watts): 30 A Operation Mode Test: Total Loss (watts): 4 A Operation Mode Test: Total Loss (watts): Idle Mode Input Power (watts): Idle Mode Power Factor: No Vehicle Mode Input Power (watts): No Vehicle Mode Power Factor: No Vehicle Mode Total Allowance (watts): Partial On Mode Input Power (watts): 240.0 2	ENERGY STAR Partner:	ZHONGSHAN AUXUS ELECTRONIC TECHNOLOGY CO.#LTD
Max Nameplate Output Current (A): Maximum Output Power (kW): Number of Outputs: Maximum Output Cord Length (ft.): Output Cord Gauge (AWG): Automatic Brightness Control (ABC) Capable?: No Network Connection Types Available: Mi-Fi or Gigabit Ethernet Auxiliary Product Features: Radio Frequency Identification (RFID) 15 A Operation Mode Test: Total Loss (watts): 30 A Operation Mode Test: Total Loss (watts): 4 A Operation Mode Test: Total Loss (watts): Full Current Operation Mode Test: Total Loss (watts): Idle Mode Input Power (watts): Idle Mode Power Factor: 0.33 Idle Mode Total Allowance (watts): 25.7 No Vehicle Mode Input Power (watts): 0.12 No Vehicle Mode Total Allowance (watts): 2.13	Product Type:	Level 2
Maximum Output Power (kW): Number of Outputs: Maximum Output Cord Length (ft.): Output Cord Gauge (AWG): Automatic Brightness Control (ABC) Capable?: No Network Connection Types Available: Wi-Fi or Gigabit Ethernet Auxiliary Product Features: Radio Frequency Identification (RFID) 15 A Operation Mode Test: Total Loss (watts): 30 A Operation Mode Test: Total Loss (watts): 4 A Operation Mode Test: Total Loss (watts): 18.0 Full Current Operation Mode Test: Total Loss (watts): Idle Mode Input Power (watts): 6.63 Idle Mode Power Factor: 0.33 Idle Mode Total Allowance (watts): 25.7 No Vehicle Mode Input Power (watts): 0.12 No Vehicle Mode Input Power (watts): 2.13	Input Voltage (V):	240.0
Number of Outputs: Maximum Output Cord Length (ft.): Output Cord Gauge (AWG): Automatic Brightness Control (ABC) Capable?: No Network Connection Types Available: Mi-Fi or Gigabit Ethernet Auxiliary Product Features: Radio Frequency Identification (RFID) 15 A Operation Mode Test: Total Loss (watts): 18.0 30 A Operation Mode Test: Total Loss (watts): 4 A Operation Mode Test: Total Loss (watts): Full Current Operation Mode Test: Total Loss (watts): Idle Mode Input Power (watts): 6.63 Idle Mode Power Factor: No Vehicle Mode Input Power (watts): No Vehicle Mode Power Factor: No Vehicle Mode Total Allowance (watts): Partial On Mode Input Power (watts): 2.13	Max Nameplate Output Current (A):	48
Maximum Output Cord Length (ft.): Output Cord Gauge (AWG): Automatic Brightness Control (ABC) Capable?: No Network Connection Types Available: Auxiliary Product Features: Radio Frequency Identification (RFID) 15 A Operation Mode Test: Total Loss (watts): 30 A Operation Mode Test: Total Loss (watts): 4 A Operation Mode Test: Total Loss (watts): Full Current Operation Mode Test: Total Loss (watts): Idle Mode Input Power (watts): 6.63 Idle Mode Power Factor: 0.33 Idle Mode Total Allowance (watts): 25.7 No Vehicle Mode Input Power (watts): 0.12 No Vehicle Mode Input Power (watts): 2.13	Maximum Output Power (kW):	11.52
Output Cord Gauge (AWG): Automatic Brightness Control (ABC) Capable?: No Network Connection Types Available: Auxiliary Product Features: Radio Frequency Identification (RFID) 15 A Operation Mode Test: Total Loss (watts): 18.0 30 A Operation Mode Test: Total Loss (watts): 46.0 4 A Operation Mode Test: Total Loss (watts): 18.0 Full Current Operation Mode Test: Total Loss (watts): Idle Mode Input Power (watts): 6.63 Idle Mode Power Factor: 0.33 Idle Mode Total Allowance (watts): 25.7 No Vehicle Mode Input Power (watts): 0.12 No Vehicle Mode Total Allowance (watts): 6.5 Partial On Mode Input Power (watts): 2.13	Number of Outputs:	1
Automatic Brightness Control (ABC) Capable?: No Network Connection Types Available: Wi-Fi or Gigabit Ethernet Auxiliary Product Features: Radio Frequency Identification (RFID) 15 A Operation Mode Test: Total Loss (watts): 18.0 30 A Operation Mode Test: Total Loss (watts): 18.0 4 A Operation Mode Test: Total Loss (watts): 18.0 Full Current Operation Mode Test: Total Loss (watts): 101.0 Idle Mode Input Power (watts): 6.63 Idle Mode Power Factor: 0.33 Idle Mode Total Allowance (watts): 25.7 No Vehicle Mode Input Power (watts): 2.07 No Vehicle Mode Power Factor: 0.12 No Vehicle Mode Total Allowance (watts): 6.5 Partial On Mode Input Power (watts): 2.13	Maximum Output Cord Length (ft.):	40
Network Connection Types Available: Wi-Fi or Gigabit Ethernet Auxiliary Product Features: Radio Frequency Identification (RFID) 15 A Operation Mode Test: Total Loss (watts): 18.0 30 A Operation Mode Test: Total Loss (watts): 18.0 4 A Operation Mode Test: Total Loss (watts): 18.0 Full Current Operation Mode Test: Total Loss (watts): 101.0 (watts): Idle Mode Input Power (watts): 6.63 Idle Mode Power Factor: 0.33 Idle Mode Total Allowance (watts): 25.7 No Vehicle Mode Input Power (watts): 2.07 No Vehicle Mode Power Factor: 0.12 No Vehicle Mode Total Allowance (watts): 6.5 Partial On Mode Input Power (watts): 2.13	Output Cord Gauge (AWG):	8
Auxiliary Product Features: Radio Frequency Identification (RFID) 15 A Operation Mode Test: Total Loss (watts): 46.0 4 A Operation Mode Test: Total Loss (watts): 18.0 Full Current Operation Mode Test: Total Loss (watts): Idle Mode Input Power (watts): 6.63 Idle Mode Power Factor: 9.33 Idle Mode Total Allowance (watts): 25.7 No Vehicle Mode Input Power (watts): 9.07 No Vehicle Mode Power Factor: 9.12 No Vehicle Mode Input Power (watts): 6.5 Partial On Mode Input Power (watts): 2.13	Automatic Brightness Control (ABC) Capable?:	No
15 A Operation Mode Test: Total Loss (watts): 30 A Operation Mode Test: Total Loss (watts): 4 A Operation Mode Test: Total Loss (watts): 5 Full Current Operation Mode Test: Total Loss (watts): 6 6.63 6 Idle Mode Input Power (watts): 7 Idle Mode Power Factor: 8 O.33 7 Idle Mode Total Allowance (watts): 8 O.33 8 Idle Mode Total Allowance (watts): 9 O.12 8 No Vehicle Mode Power Factor: 9 O.12 8 No Vehicle Mode Total Allowance (watts): 9 O.12 8 No Vehicle Mode Total Allowance (watts): 9 O.12 8 No Vehicle Mode Total Allowance (watts): 9 O.12 9 O.12 1 On Mode Input Power (watts): 9 O.13	Network Connection Types Available:	Wi-Fi or Gigabit Ethernet
30 A Operation Mode Test: Total Loss (watts): 46.0 4 A Operation Mode Test: Total Loss (watts): 18.0 Full Current Operation Mode Test: Total Loss (watts): 101.0 Idle Mode Input Power (watts): 6.63 Idle Mode Power Factor: 0.33 Idle Mode Total Allowance (watts): 25.7 No Vehicle Mode Input Power (watts): 2.07 No Vehicle Mode Power Factor: 0.12 No Vehicle Mode Total Allowance (watts): 6.5 Partial On Mode Input Power (watts): 2.13	Auxiliary Product Features:	Radio Frequency Identification (RFID)
4 A Operation Mode Test: Total Loss (watts): Full Current Operation Mode Test: Total Loss (watts): Idle Mode Input Power (watts): Idle Mode Power Factor: Idle Mode Total Allowance (watts): No Vehicle Mode Input Power (watts): No Vehicle Mode Power Factor: No Vehicle Mode Power Factor: No Vehicle Mode Total Allowance (watts): O.12 No Vehicle Mode Total Allowance (watts): Partial On Mode Input Power (watts): 2.13	15 A Operation Mode Test: Total Loss (watts):	18.0
Full Current Operation Mode Test: Total Loss (watts): Idle Mode Input Power (watts): Idle Mode Power Factor: 0.33 Idle Mode Total Allowance (watts): 25.7 No Vehicle Mode Input Power (watts): 2.07 No Vehicle Mode Power Factor: 0.12 No Vehicle Mode Total Allowance (watts): 6.5 Partial On Mode Input Power (watts): 2.13	30 A Operation Mode Test: Total Loss (watts):	46.0
(watts):6.63Idle Mode Input Power (watts):6.63Idle Mode Power Factor:0.33Idle Mode Total Allowance (watts):25.7No Vehicle Mode Input Power (watts):2.07No Vehicle Mode Power Factor:0.12No Vehicle Mode Total Allowance (watts):6.5Partial On Mode Input Power (watts):2.13	4 A Operation Mode Test: Total Loss (watts):	18.0
Idle Mode Power Factor: Idle Mode Total Allowance (watts): No Vehicle Mode Input Power (watts): No Vehicle Mode Power Factor: No Vehicle Mode Total Allowance (watts): Partial On Mode Input Power (watts): 2.07 6.5 Partial On Mode Input Power (watts): 2.13		101.0
Idle Mode Total Allowance (watts): 25.7 No Vehicle Mode Input Power (watts): 2.07 No Vehicle Mode Power Factor: 0.12 No Vehicle Mode Total Allowance (watts): 6.5 Partial On Mode Input Power (watts): 2.13	Idle Mode Input Power (watts):	6.63
No Vehicle Mode Input Power (watts): No Vehicle Mode Power Factor: No Vehicle Mode Total Allowance (watts): Partial On Mode Input Power (watts): 2.07 0.12 0.5 Partial On Mode Input Power (watts): 2.13	Idle Mode Power Factor:	0.33
No Vehicle Mode Power Factor: No Vehicle Mode Total Allowance (watts): Partial On Mode Input Power (watts): 2.13	Idle Mode Total Allowance (watts):	25.7
No Vehicle Mode Total Allowance (watts): 6.5 Partial On Mode Input Power (watts): 2.13	No Vehicle Mode Input Power (watts):	2.07
Partial On Mode Input Power (watts): 2.13	No Vehicle Mode Power Factor:	0.12
, , ,	No Vehicle Mode Total Allowance (watts):	6.5
	Partial On Mode Input Power (watts):	2.13
Partial On Mode Power Factor: 0.14	Partial On Mode Power Factor:	0.14
Partial On Mode Total Allowance (watts): 6.5	Partial On Mode Total Allowance (watts):	6.5
Date Certified: 2024-04-24	Date Certified:	2024-04-24
Date Available on Market: 2024-04-24	Date Available on Market:	2024-04-24
Markets: United States, Canada	Markets:	United States, Canada
ENERGY STAR Certified: Yes	ENERGY STAR Certified:	Yes

Additional Model Information

,TCS-DP-48S-40FT,

Captured On: 04/28/2025