



ENERGY STAR CERTIFIED

# Electric Vehicle Chargers (AC-Output)

## CHARGETROINX - EV Charger : CTX-C40-240-2

### Specifications

Brand Name:	CHARGETROINX
Model Name:	EV Charger
Model Number:	CTX-C40-240-2
ENERGY STAR Unique ID:	3798642
ENERGY STAR Partner:	Chargetronix
Product Type:	Level 2
Input Voltage (V):	240.0
Max Nameplate Output Current (A):	40
Maximum Output Power (kW):	9.6
Number of Outputs:	2
Maximum Output Cord Length (ft.):	25
Output Cord Gauge (AWG):	9
Maximum (100%) Measured Luminance of the High Res Display (candelas per m2):	826.47
Automatic Brightness Control (ABC) Capable?:	No
Connected Capable:	Yes
Connects Using:	Wi-Fi
Network Connection Types Available:	Wi-Fi or Gigabit Ethernet,Other LAN (Local Area Network),Cellular
DR Protocol:	Open Charge Point Protocol (OCPP)
Protocols Used to Support Smart Charging:	SAE J1772
Network Security Standards:	NIST Cybersecurity Framework
Screen Area, if EVSE has high res display (in2):	8.14
Product Features:	None
Auxiliary Product Features:	High Resolution Display,PLC Board (ISO 15118),Radio Frequency Identification (RFID),Revenue Grade Meter
15 A Operation Mode Test: Total Loss (watts):	16.0
30 A Operation Mode Test: Total Loss (watts):	12.0
4 A Operation Mode Test: Total Loss (watts):	13.5
Full Current Operation Mode Test: Total Loss (watts):	14.0
Idle Mode Input Power (watts):	5.94
Idle Mode Power Factor:	0.29
Idle Mode Total Allowance (watts):	24.55
No Vehicle Mode Input Power (watts):	5.56

No Vehicle Mode Power Factor:	0.28
No Vehicle Mode Total Allowance (watts):	8.55
Partial On Mode Input Power (watts):	5.64
Partial On Mode Power Factor:	0.28
Partial On Mode Total Allowance (watts):	8.55
Date Certified:	2024-11-11
Date Available on Market:	2024-11-11
Markets:	United States, Canada
ENERGY STAR Certified:	Yes

## Additional Model Information

„CTX-C40-240-2

Captured On:  
04/28/2025