Zerova - DSWU182J0TD: DSWU182J0TD

| Specifications Zerova Model Name: DSWU182J0TD Model Number: DSWU182J0TD ENERGY STAR Unique ID: 2454359 Type: DC-output (AC-input) Rated Input Voltage (V) AC-Input: 480 DC-input or AC-input: AC-input ENERGY STAR Partner: Zerova Technologies Taiwan Limited Maximum Masured Luminance of the High Res Display (candelas per m2): 865.0 Maximum Measured Luminance of the High Res Display (candelas per m2): 16 Number of Outputs: 2 Output Cord Length (ft.): 16 Number of Outputs: 2 Output Cord Gauge (AWG): 2 Single Phase or Three Phase: Three Phase Product Configuration: All-in-One Product Configuration Maximum Available Output Power: 180000.0 Maximum Output Power: 180000.0 Maximum Output Power: 18000.0 Automatic Brightness Control Capable?: Ve Connected Capable: Yes Connect Using: Wi-Fi,Wired Ethernet Network Connection Types Available: Gig | | |
|--|--|------------------------------------|
| Model Name: DSWU182JOTD Model Number: DSWU182JOTD ENERGY STAR Unique ID: 2454359 Type: DC-output (AC-input) Rated Input Voltage (V) AC-Input: 480 DC-input or AC-input: Zerova Technologies Taiwan Limited Maximum Nameplate Output Current (A) AC-Input: 300.0 Maximum Measured Luminance of the High Res Display (candelas per m2): 865.0 Output Cord Length (ft.): 16 Number of Outputs: 2 Output Cord Gauge (AWG): 2 Single Phase or Three Phase: Three Phase Product Configuration: All-in-One Product Configuration Maximum Available Output Power: 180.0 Maximum Output Power: 180.0 Automatic Brightness Control Capable?: No Connected Capable: Yes Connects Using: Wi-Fi,Wired Ethernet Network Connection Types Available: Gigabit Ethernet,Wi-Fi,Cellular Screen Area, if EVSE has high res display (in2): 20.52 Connector Type: Combined Charging System (CCS) DR Protocol: Open Charge Point Protocol (OCPP) <th>Specifications</th> <th></th> | Specifications | |
| Model Number: DSWU182JOTD ENERGY STAR Unique ID: 2454359 Type: DC-output (AC-input) Rated Input Voltage (V) AC-Input: 480 DC-input or AC-input: AC-input: AC-input ENERGY STAR Partner: Zerova Technologies Taiwan Limited Maximum Nameplate Output Current (A) AC-input Maximum Measured Luminance of the High Res Display (candelas per m2): 0140 Output Cord Length (ft.): 16 Number of Outputs: 2 Output Cord Gauge (AWG): 2 Single Phase or Three Phase: Three Phase Product Configuration: All-in-One Product Configuration Maximum Output Power: 180000.0 Maximum Output Power: 180000.0 Maximum Output Power: 180000.0 Maximum Output Power: Single Pitcheriet Automatic Brightness Control Capable?: No Connected Capable: Yes Connected Capable: Gigabit Ethernet, Wi-Fi, Cellular Screen Area, if EVSE has high res display (in2): 20.52 Connector Type: Ocmbined Charging System (CCS) DR Protocol: Open Charge Point Protocol (OCPP) Is Broadband Internet Connection Needed for Demand Response?: None Protocols Used to Support Smart Charging: AE J1772 Integral Battery Bank: No | Brand Name: | Zerova |
| ENRRGY STAR Unique ID: 2454359 Type: DC-output (AC-input) Rated Input Voltage (V) AC-Input: 480 DC-input or AC-input: AC-input ENERGY STAR Partner: Zerova Technologies Taiwan Limited Maximum Nameplate Output Current (A) AC-Input: 865.0 Maximum Measured Luminance of the High Res Display (candelas per m2): 16 Number of Outputs: 2 Output Cord Length (ft.): 16 Number of Outputs: 2 Output Cord Gauge (AWG): 2 Single Phase or Three Phase: Three Phase Product Configuration: All-in-One Product Configuration Maximum Available Output Power: 18000.0 Maximum Output Power: 180.0 Automatic Brightness Control Capable?: No Connected Capable: Yes Connects Using: Wi-Fi,Wired Ethernet Network Connection Types Available: Gigabit Ethernet,Wi-Fi,Cellular Screen Area, if EVSE has high res display (in:): 20.52 Connector Type: Open Charge Point Protocol (OCPP) Is Broadband Internet Connection Needed for Demand Response?: None Protocols Used to Support Smart Charging: SAE J1772 Integral Battery Bank: No | Model Name: | DSWU182J0TD |
| Type: DC-output (AC-input) Rated Input Voltage (V) AC-Input: 480 DC-input or AC-input: AC-input ENERGY STAR Partner: Zerova Technologies Taiwan Limited Maximum Nameplate Output Current (A) AC-Input: 865.0 Maximum Measured Luminance of the High Res Display (candelas per m2): 16 Output Cord Length (ft.): 16 Number of Outputs: 2 Output Cord Gauge (AWG): 2 Single Phase or Three Phase: Three Phase Product Configuration: All-in-One Product Configuration Maximum Available Output Power: 180.00 Maximum Output Power: 180.00 Automatic Brightness Control Capable?: No Connected Capable: Yes Connects Using: Wi-Fi,Wired Ethernet Network Connection Types Available: Gigabit Ethernet,Wi-Fi,Cellular Screen Area, if EVSE has high res display (in2): 20.52 Connector Type: Open Charge Point Protocol (OCPP) Be Broadband Internet Connection Needed for Demand Response?: None Protocols Used to Support Smart Charging: SAE J1772 Integral Battery Bank: No | Model Number: | DSWU182J0TD |
| Rated Input Voltage (V) AC-Input: DC-input or AC-input: ENERGY STAR Partner: Zerova Technologies Taiwan Limited Maximum Nameplate Output Current (A) AC-input: Maximum Measured Luminance of the High Res Display (candelas per m2): Output Cord Length (ft.): Number of Outputs: 2 Output Cord Gauge (AWG): Single Phase or Three Phase: Product Configuration: Maximum Available Output Power: Maximum Available Output Power: All-in-One Product Configuration Maximum Output Power: No Connected Capable: Yes Connected Capable: Ves Connected Using: Wi-Fi,Wired Ethernet Network Connection Types Available: Gigabit Ethernet,Wi-Fi,Cellular Screen Area, if EVSE has high res display (in2): Combined Charging System (CCS) DR Protocol: DR Protocol: DR Protocol: Broadband Internet Connection Needed for Demand Response?: None Protocols Used to Support Smart Charging: SAE J1772 Integral Battery Bank: No | ENERGY STAR Unique ID: | 2454359 |
| DC-input or AC-input: ENERGY STAR Partner: Zerova Technologies Taiwan Limited Maximum Nameplate Output Current (A) AC-input: Maximum Measured Luminance of the High Res Display (candelas per m2): Output Cord Length (ft.): 16 Number of Outputs: 2 Output Cord Gauge (AWG): 2 Single Phase or Three Phase: Product Configuration: Maximum Available Output Power: Maximum Output Power: 180000.0 Maximum Output Power: 180000.0 Maximum Output Power: No Connected Capable: Ves Connected Capable: Gigabit Ethernet,Wi-Fi,Cellular Screen Area, if EVSE has high res display (in2): Connector Type: Open Charge Point Protocol (OCPP) Is Broadband Internet Connection Needed for Demand Response?: None Protocols Used to Support Smart Charging: SAE J1772 Integral Battery Bank: Noo | Туре: | DC-output (AC-input) |
| ENERGY STAR Partner: Zerova Technologies Taiwan Limited Maximum Nameplate Output Current (A) AC- Input: Maximum Measured Luminance of the High Res Display (candelas per m2): Output Cord Length (ft.): 16 Number of Outputs: 2 Output Cord Gauge (AWG): 2 Single Phase or Three Phase: Three Phase Product Configuration: All-in-One Product Configuration Maximum Available Output Power: 180000.0 Maximum Output Power: 180.0 Automatic Brightness Control Capable?: No Connected Capable: Yes Connects Using: Wi-Fi, Wired Ethernet Network Connection Types Available: Gigabit Ethernet, Wi-Fi, Cellular Screen Area, if EVSE has high res display (in2): 20.52 Connector Type: Combined Charging System (CCS) DR Protocol: Open Charge Point Protocol (OCPP) Is Broadband Internet Connection Needed for Demand Response?: Network Security Standards: None Protocols Used to Support Smart Charging: SAE J1772 Integral Battery Bank: No | Rated Input Voltage (V) AC-Input: | 480 |
| Maximum Nameplate Output Current (A) AC- Input: Maximum Measured Luminance of the High Res Display (candelas per m2): Output Cord Length (ft.): Number of Outputs: 2 Output Cord Gauge (AWG): 2 Single Phase or Three Phase: Product Configuration: Maximum Available Output Power: 180000.0 Maximum Available Output Power: 180.0 Automatic Brightness Control Capable?: No Connected Capable: Yes Connects Using: Wi-Fi,Wired Ethernet Network Connection Types Available: Gigabit Ethernet,Wi-Fi,Cellular Screen Area, if EVSE has high res display (in2): Combined Charging System (CCS) DR Protocol: DR Protocol: Broadband Internet Connection Needed for Demand Response?: None Protocols Used to Support Smart Charging: No Solution: All-in-One Product Configuration All-in-One Product Configuration Maximum Output Power: 180000.0 Maximum Ou | DC-input or AC-input: | AC-input |
| Input: Maximum Measured Luminance of the High Res Display (candelas per m2): Output Cord Length (ft.): Number of Outputs: Output Cord Gauge (AWG): Single Phase or Three Phase: Product Configuration: Maximum Available Output Power: 180000.0 Maximum Output Power: 180.0 Automatic Brightness Control Capable?: No Connected Capable: Ves Connects Using: Network Connection Types Available: Screen Area, if EVSE has high res display (in2): Connector Type: Ocher Connector Open Charge Point Protocol (OCPP) Is Broadband Internet Connection Needed for Demand Response?: Network Security Standards: No No No No No No No No No N | ENERGY STAR Partner: | Zerova Technologies Taiwan Limited |
| Res Display (candelas per m2): Output Cord Length (ft.): Number of Outputs: 2 Output Cord Gauge (AWG): 2 Single Phase or Three Phase: Three Phase Product Configuration: Maximum Available Output Power: 180000.0 Maximum Output Power: 180.0 Automatic Brightness Control Capable?: No Connected Capable: Yes Connects Using: Wi-Fi,Wired Ethernet Network Connection Types Available: Gigabit Ethernet,Wi-Fi,Cellular Screen Area, if EVSE has high res display (in2): Connector Type: Combined Charging System (CCS) DR Protocol: Open Charge Point Protocol (OCPP) Is Broadband Internet Connection Needed for Demand Response?: Network Security Standards: None Protocols Used to Support Smart Charging: SAE J1772 Integral Battery Bank: | | 300.0 |
| Number of Outputs: Output Cord Gauge (AWG): Single Phase or Three Phase: Three Phase Product Configuration: All-in-One Product Configuration Maximum Available Output Power: 180.00 Maximum Output Power: 180.0 Automatic Brightness Control Capable?: No Connected Capable: Yes Connects Using: Network Connection Types Available: Gigabit Ethernet, Wi-Fi, Cellular Screen Area, if EVSE has high res display (in2): Connector Type: Combined Charging System (CCS) DR Protocol: No Serven Area Connection Needed for Demand Response?: No No No No No No No No No N | _ | 865.0 |
| Output Cord Gauge (AWG): Single Phase or Three Phase: Product Configuration: All-in-One Product Configuration Maximum Available Output Power: 180000.0 Maximum Output Power: 180.0 Automatic Brightness Control Capable?: No Connected Capable: Yes Connects Using: Wi-Fi,Wired Ethernet Network Connection Types Available: Gigabit Ethernet,Wi-Fi,Cellular Screen Area, if EVSE has high res display (in2): Combined Charging System (CCS) DR Protocol: Open Charge Point Protocol (OCPP) Is Broadband Internet Connection Needed for Demand Response?: No No Protocols Used to Support Smart Charging: No No | Output Cord Length (ft.): | 16 |
| Single Phase or Three Phase: Product Configuration: All-in-One Product Configuration Maximum Available Output Power: 180000.0 Maximum Output Power: 180.0 Automatic Brightness Control Capable?: No Connected Capable: Yes Connects Using: Wi-Fi,Wired Ethernet Network Connection Types Available: Gigabit Ethernet,Wi-Fi,Cellular Screen Area, if EVSE has high res display (in2): Connector Type: Combined Charging System (CCS) DR Protocol: Open Charge Point Protocol (OCPP) Is Broadband Internet Connection Needed for Demand Response?: Network Security Standards: None Protocols Used to Support Smart Charging: SAE J1772 Integral Battery Bank: No | Number of Outputs: | 2 |
| Product Configuration: Maximum Available Output Power: 180000.0 Maximum Output Power: 180.0 Automatic Brightness Control Capable?: No Connected Capable: Connects Using: Network Connection Types Available: Gigabit Ethernet, Wi-Fi, Cellular Screen Area, if EVSE has high res display (in2): Connector Type: Combined Charging System (CCS) DR Protocol: Deen Charge Point Protocol (OCPP) Is Broadband Internet Connection Needed for Demand Response?: No No No Protocols Used to Support Smart Charging: SAE J1772 Integral Battery Bank: No | Output Cord Gauge (AWG): | 2 |
| Maximum Available Output Power: 180000.0 Maximum Output Power: 180.0 Automatic Brightness Control Capable?: No Connected Capable: Yes Connects Using: Wi-Fi,Wired Ethernet Network Connection Types Available: Gigabit Ethernet,Wi-Fi,Cellular Screen Area, if EVSE has high res display (in2): 20.52 Connector Type: Combined Charging System (CCS) DR Protocol: Open Charge Point Protocol (OCPP) Is Broadband Internet Connection Needed for Demand Response?: Network Security Standards: None Protocols Used to Support Smart Charging: SAE J1772 Integral Battery Bank: No | Single Phase or Three Phase: | Three Phase |
| Maximum Output Power: 180.0 Automatic Brightness Control Capable?: No Connected Capable: Yes Connects Using: Wi-Fi,Wired Ethernet Network Connection Types Available: Gigabit Ethernet,Wi-Fi,Cellular Screen Area, if EVSE has high res display (in2): 20.52 Connector Type: Combined Charging System (CCS) DR Protocol: Open Charge Point Protocol (OCPP) Is Broadband Internet Connection Needed for Demand Response?: Network Security Standards: None Protocols Used to Support Smart Charging: SAE J1772 Integral Battery Bank: No | Product Configuration: | All-in-One Product Configuration |
| Automatic Brightness Control Capable?: Connected Capable: Yes Connects Using: Network Connection Types Available: Gigabit Ethernet,Wi-Fi,Cellular Screen Area, if EVSE has high res display (in2): Connector Type: Combined Charging System (CCS) DR Protocol: Open Charge Point Protocol (OCPP) Is Broadband Internet Connection Needed for Demand Response?: Network Security Standards: None Protocols Used to Support Smart Charging: SAE J1772 Integral Battery Bank: No | Maximum Available Output Power: | 180000.0 |
| Connected Capable: Connects Using: Network Connection Types Available: Screen Area, if EVSE has high res display (in2): Connector Type: Combined Charging System (CCS) DR Protocol: S Broadband Internet Connection Needed for Demand Response?: Network Security Standards: None Protocols Used to Support Smart Charging: No No | Maximum Output Power: | 180.0 |
| Connects Using: Wi-Fi,Wired Ethernet Network Connection Types Available: Gigabit Ethernet,Wi-Fi,Cellular Screen Area, if EVSE has high res display (in2): 20.52 Connector Type: Combined Charging System (CCS) DR Protocol: Open Charge Point Protocol (OCPP) Is Broadband Internet Connection Needed for Demand Response?: No No No No Protocols Used to Support Smart Charging: SAE J1772 Integral Battery Bank: No | Automatic Brightness Control Capable?: | No |
| Network Connection Types Available: Gigabit Ethernet,Wi-Fi,Cellular Screen Area, if EVSE has high res display (in2): 20.52 Connector Type: Combined Charging System (CCS) DR Protocol: Open Charge Point Protocol (OCPP) Is Broadband Internet Connection Needed for Demand Response?: Network Security Standards: None Protocols Used to Support Smart Charging: SAE J1772 Integral Battery Bank: No | Connected Capable: | Yes |
| Screen Area, if EVSE has high res display (in2): Connector Type: Combined Charging System (CCS) DR Protocol: Open Charge Point Protocol (OCPP) Is Broadband Internet Connection Needed for Demand Response?: Network Security Standards: None Protocols Used to Support Smart Charging: SAE J1772 Integral Battery Bank: No | Connects Using: | Wi-Fi,Wired Ethernet |
| Connector Type: Combined Charging System (CCS) DR Protocol: Open Charge Point Protocol (OCPP) Is Broadband Internet Connection Needed for Demand Response?: Network Security Standards: None Protocols Used to Support Smart Charging: SAE J1772 Integral Battery Bank: No | Network Connection Types Available: | Gigabit Ethernet,Wi-Fi,Cellular |
| DR Protocol: Is Broadband Internet Connection Needed for Demand Response?: Network Security Standards: Protocols Used to Support Smart Charging: No No | Screen Area, if EVSE has high res display (in2): | 20.52 |
| Is Broadband Internet Connection Needed for Demand Response?: Network Security Standards: Protocols Used to Support Smart Charging: Integral Battery Bank: No | Connector Type: | Combined Charging System (CCS) |
| Demand Response?: None Network Security Standards: None Protocols Used to Support Smart Charging: SAE J1772 Integral Battery Bank: No | DR Protocol: | Open Charge Point Protocol (OCPP) |
| Protocols Used to Support Smart Charging: SAE J1772 Integral Battery Bank: No | | No |
| Integral Battery Bank: No | Network Security Standards: | None |
| | Protocols Used to Support Smart Charging: | SAE J1772 |
| Product Features: Vehicle to grid capability | Integral Battery Bank: | No |
| | Product Features: | Vehicle to grid capability |
| Idle Mode Input Power (watts) AC- Input: 268.42 | Idle Mode Input Power (watts) AC- Input: | 268.42 |
| No Vehicle Mode Input Power (watts) AC- Input: 55.2 | _ · · · · · · · · · · · · · · · · · · · | 55.2 |

| No Vehicle Mode Power Factor AC-Input: | 0.04 |
|---|-----------------------|
| No Vehicle Mode Total Allowance (watts): | 133.28 |
| Partial On Mode Input Power (watts) AC-Input: | 125.23 |
| Partial On Mode Power Factor AC-Input: | 0.02 |
| Partial On Mode Total Allowance (watts): | 133.28 |
| Average Loading-Adjusted Efficiency (%) AC-Input: | 0.95 |
| Date Certified: | 2023-04-18 |
| Date Available On Market: | 2023-02-06 |
| Markets: | United States, Canada |
| ENERGY STAR Certified: | Yes |

Additional Model Information

,DSWU182T0JD,

Captured On: 04/30/2025