

## Star Charge - Electric Vehicle Supply Equipment : DC2400AN147###

Specifications	
Brand Name:	Star Charge
Model Name:	Electric Vehicle Supply Equipment
Model Number:	DC2400AN147###
<b>ENERGY STAR Unique ID:</b>	3626987
Туре:	DC-output (AC-input)
Rated Input Voltage (V) AC-Input:	480
DC-input or AC-input:	AC-input
ENERGY STAR Partner:	Star Charge Americas Corp
Maximum Nameplate Output Current (A) AC-Input:	500.0
Maximum Measured Luminance of the High Res Display (candelas per m2):	514.9
Output Cord Length (ft.):	23
Number of Outputs:	2
Output Cord Gauge (AWG):	1
Single Phase or Three Phase:	Three Phase
Product Configuration:	Distributed Product Configuration
Maximum Available Output Power:	240000.0
Maximum Output Power:	240.0
Automatic Brightness Control Capable?:	No
Connected Capable:	No
<b>Network Connection Types Available:</b>	Gigabit Ethernet,Wi-Fi,Cellular
Screen Area, if EVSE has high res display (in2):	51.41
Connector Type:	Combined Charging System (CCS)
Integral Battery Bank:	No
Product Features:	None
Auxiliary Product Features:	High Resolution Display,Credit Card Reader,Radio Frequency Identification (RFID)
Idle Mode Input Power (watts) AC- Input:	156.3
No Vehicle Mode Input Power (watts) AC-Input:	53.8
No Vehicle Mode Power Factor AC-Input:	0.01
No Vehicle Mode Total Allowance (watts):	146.82

Partial On Mode Input Power (watts) AC-Input:	53.9
Partial On Mode Power Factor AC-Input:	0.01
Partial On Mode Total Allowance (watts):	146.82
Average Loading-Adjusted Efficiency (%) AC-Input:	0.96
Date Certified:	2024-09-03
Date Available On Market:	2024-07-08
Markets:	United States, Canada
<b>ENERGY STAR Certified:</b>	Yes

## **Additional Model Information**

"#=0-2 represents the different rated output current,0=400A,1=380A,2=400A+380A,#=1-3 represents the different DC connector deploy,1=With two Connectors,2=Only Left,3=Only Right,#=1-2 represents with or without POS terminal,1=with p os terminal

**Captured On:** 06/17/2025