

Rinnai - Heat pump water heater : REHP65C

ENREGY STAR Unique UD3722799ENREGY STAR Partner:Rinnai America CorporationBrand Name:Heat pump water heaterModel Name:Heat pump water heaterModel Number:REHP65CConnected Capable:YesConnected Capable:YesConnected Using:WiFL/CTA-2045-BCommunication Hardware Architecture:A -Bullt-inTime of Use Schedule:YesTax Credit Eligible:YesENERGY STAR Certified:YesType:Hybrid/Electric Heat PumpFuel:ElectricMax. Amps:24.0Iput Voltage for HPWH (V):240Darw Pattern (Intended Usage):High-UsageFirst Hour Rating (gallons):80Refreger Straft (Gallons):3.7Refreger Straft (UFF):3.9Upper Compressor Cut Off Temperature for HPWH (V):3.0Uniform Energy Factor (UFF):3.9Refreger (Kinhyr):1.01.6Stoage (Wihryr):1.02.0Stoage (Wihryr):3.9Electric Input (Wit):5.5Electric Input (Wit):5.5Electric Input (Wit):1.02.0Stoage (Vulnre(gallons):6.0.0Tank Height (Inches):2.18.2Tank Height (Inches):1.8.2Stoage Schulle:1.8.2Bettrie Input (Wit):1.8.2Stoage Schulle:1.8.2Stoage Schulle:1.8.2Bettrie Input (Wit):1.8.2Stoage Schulle:1.8.2Stoage Schulle:1.8.2 <th>Specifications</th> <th></th>	Specifications	
ENERGY STAR Partner:Rinnai America CorporationBrand Name:RinnaiModel Name:Heat pump water heaterModel Number:REHP65CConnected Capable:YesConnected Capable:VieF.CTA-2045DR Protocol:A-Built-inCommunication Hardware Architecture:A-Built-inTaw Credit Eligible:YesTax Credit Eligible:YesENERGY STAR Certified:YesType:Hybrid/Electric Heat PumpFuel:ElectricMax Amps:24.0Daw Pattern (Intended Usage):High-UsageFirst Hour Rating (gallons):80Upper Compressor Cut Off Temperature for UPWH ('f):3.14.3(GWP:1430)Upper Compressor Cut Off Temperature for UPWH ('ff):3.9Refigerant with GWP:5.5Electric Juput (kW):5.5Electric Juput (kW):1.24.0Storage VGM/ryf):1.24.0Inform Energy Factor (UEF):3.9Retorey Efficiency(s):6.0Electric Usage (kWhyr):1.24.0Storage VGM/ryf):1.24.0Storage VGM/ryf):1.24.0Storage VGM/ryf):1.24.0Storage VGM/ryf):1.24.0Storage VGM/ryf):1.24.0Retorey Efficiency (s):6.0Retorey Efficiency (s):6.0Storage VGM/ryf):1.24.0Storage VGM/ryf):1.24.0Storage VGM/ryf):6.0Storage VGM/ryf):1.24.0Storage VGM/ryf):1.24.0Storage VGM	- ENEDGY STAP Unique ID:	2722700
Brand Name:RinnaiModel Name:Heat pump water heaterModel Number:REHP65CConnected Capable:YesConnected Using:UN-FLCTA-2045-DR Protocol:CTA-2045-BCommunication Hardware Architecture:A -Built-inTime of Use Schedule:YesTax Credit Eligible:YesENERGY STAR Certified:YesType:Hybrid/Electric Heat PumpFuel:ElectricMax Amps:40.0Input Voltage for HPWH (V):24.0Parter (Intended Usage):High-UsageFirst Hour Rating (gallons):80Heat Pump Type:20.0 Volt Integrated HPWHLyper Compressor Cut Off Temperature for HPWH (F):3.1Reforementschröft Temperature for HPWH (F):9.1Longer Schedule:5.5Electric Lectric Lectri		
Model Name:Heat pump water heaterModel Number:REHP65CConnected Capable:YesConnects Using:Wi-Fi,CTA-2045DR Protocol:CTA-2045-BCommunication Hardware Architecture:A -Built-inTime of Use Schedule:YesTax Credit Eligible:YesType:Hybrid/Electric Heat PumpFuel:ElectricMax. Amps:240Input Voltage for HPWH (V):240Draw Pattern (Intended Usage):High-UsageFirst Hour Rating (gallons):80Lever Compressor Cut Off Temperature for HPWH (*F):3.4Uniform Energy Factor (UEF):3.9Reforey Efficiency (%):45.0Electric Input (Mt):9.0Compressor Cut Off Temperature for HPWH (*F):3.4Choine Energy Factor (UEF):3.9Reforey Efficiency (%):5.5Electric Input (KW):5.0Electric Usage (kMhyr):124.0Storage Volume (gallons):6.0Atta Height (inches):1.8Atta Electric Input (kM):5.5Electric Input (kM):5.5Electric Input (kM):1.24.0Storage Volume (gallons):6.0.0Atta Electric Input (kM):5.5Electric Input (km):1.8Atta Electric Input (km):6.0.0Atta Electric Input (km):1.8Atta Electric Input (km):1.8Atta Electric Input (km):1.8Atta Electric Input (km):1.8Atta Electric Input (km): <td< th=""><td></td><td></td></td<>		
Model Number:REHP65CConnected Capable:YesConnects Using:Wi-Fi,CTA-2045-BDR Protocol:CTA-2045-BCommunication Hardware Architecture:A -Built-inTime of Use Schedule:YesTax Credit Eligible:YesENERGY STAR Certified:YesType:Hybrid/Electric Heat PumpFuel:ElectricMax Amps:24.0Input Voltage for HPWH (V):240Pattern (Intended Usage):High-UsageFirst Hour Rating (galons):80Lewer Compressor Cut Off Temperature for HPWH (rF):7.4Drape Compressor Cut Off Temperature for HPWH (rF):9.1Storage Fifteiency (%):45.0Etertic Usage (kMh/yr):5.5Etertic Usage (kMh/yr):10.0Storage Volume (galons):6.0And6.0Tark Diametr (inches):21.8Tark Diametr (inches):21.8Tark Diametr (inches):21.8Tark Diametr (inches):21.8Tark Diametr (inches):21.8Tark Diametr (inches):20.50-11-6		
Connected Capable:YesConnects Using:WFI;CTA-2045DR Protocol:CTA-2045-BCommunication Hardware Architecture:A -Built-inTime of Use Schedule:YesTax Credit Eligible:YesENERGY STAR Certified:YesType:Hybrid/Electric Heat PumpFuel:ElectricMax Amps:24.0Input Voltage for HPWH (V):24.0Partern (Intended Usage):High-UsageFirst Hour Rating (galons):24.0Upper Compressor Cut Off Temperature for HPWH (*F):7.4Drace Schedule:9.3Refrigerant with GWP:S.1Linform Energy Factor (UEF):3.0Electric Usage (kMh/yr):5.5Electric Usage (kMh/yr):10.0Storage Volume (gallons):6.0Arcance Intended Usage):1.3And Capace Intender Usage):1.3Arcance Intender Usage):3.0Upper Compressor Cut Off Temperature for HPWH (*F):9.0Storage Volume (gallons):5.5Electric Usage (kMh/yr):1.4Storage Volume (gallons):1.8Arcance Intender1.8Storage Volume (gallons):1.8Storage Volume (gallons):3.0Storage Volume (gallons):		
Connects Using:Wi-Fi,CTA-2045DR Protocol:CTA-2045-BCommunication Hardware Architecture:A -Built-inTime of Use Schedule:YesTax Credit Eligible:VesENERGY STAR Certified:Hybrid/Electric Heat PumpFuel:ElectricMax. Amps:24.0Input Voltage for HPWH (V):240Draw Pattern (Intended Usage):High-UsageAFirst Hour Rating (gallons):80Heat Pump Type:240 Volt Integrated HPWHLower Compressor Cut Off Temperature for PHWH (*F):9.7Inform Energy Factor (UEF):3.9Refrigerant with GWP:1.9Lower Spressor Cut Off Temperature for Strage Volume (sallons):9.0Refrigerant with GWP:1.9Lower Spressor Cut Off Temperature for Strage Volume (sallons):1.9Asta Gut Cut Cut Cut Cut Cut Cut Cut Cut Cut C		
DR Protocol.CTA-2045-BCommunication Hardware Architecture:A - Built-inTime of Use Schedule:YesTax Credit Eligible:YesENERGY STAR Certified:YesType:Hybrid/Electric Heat PumpFuel:ElectricMax. Amps:24.0Input Voltage for HPWH (V):240Draw Pattern (Intended Usage):High-UsageFirst Hour Rating (gallons):80Heat Pump Type:240 Volt Integrated HPWHLower Compressor Cut Off Temperature for HPWH (*F):37.4Upper Compressor Cut Off Temperature for HPWH (*F):107.6Stardig Reiner (Nters):3.9Refrigerant with GWP:5.5Electric Usage (kWh/yr):1240.0Storage Volume (gallons):60.0Ata Diameter (inches):21.8Tank Diameter (inches):21.8Tank Height (inches):20.50-116	•	
Communication Hardware Architecture:A -Built-inTime of Use Schedule:YesTax Credit Eligible:YesType:Hybrid/Electric Heat PumpFuel:ElectricMax. Amps:24.0Input Voltage for HPWH (V):240Draw Pattern (Intended Usage):High-UsageFirst Hour Rating (gallons):30Lower Compressor Cut Off Temperature for HPWH (°F):240 Volt Integrated HPWHUpper Compressor Cut Off Temperature for HPWH (°F):37.4Refrigerant with GWP:107.6Refrigerant with GWP:5.5Electric Input (KW):5.5Electric Input (KW):10.0Tax Diage (KWh/yr):10.0Storage Volume (gallons):10.0Argen Supper Compressor Cut Off Temperature for How (%):10.0Refrigerant with GWP:10.0Refrigerant with GWP:10.0Storage Volume (gallons):6.0Argen Supper Compressor Cut Off Temperature for How (%):10.0Refrigerant with GWP:10.0Storage Volume (gallons):6.0Storage Volume (gallons):10.0Storage Volume (gallons): <td>-</td> <td></td>	-	
Time of Use Schedule:YesTax Credit Eligible:YesENERGY STAR Certified:YesType:Hybrid/Electric Heat PumpFuel:ElectricMax. Amps:24.0Daw Pattern (Intended Usage):High-UsageFirst Hour Rating (gallons):80Heat Pump Type:240 Volt Integrated HPWHLower Compressor Cut Off Temperature for HPWH ('F):37.4Differant with GWP:0.1Linform Energy Factor (UEF):0.9Electric Input (WI):.9Electric Input (WI):.9Stoage Volume (gallons):.9Stoage Volume (gallons):0.0Linform Energy Factor (UEF):.0Stoage Volume (gallons):.18Ant Diameter (inches):.18Stoage Volume (gallons):.18Stoage Volume (gallons):.18Stoage Volume (gallons):.18Stoage Course (inches):.18Tan K Diameter (inches):.20Stoage Course (inches): <td< th=""><td></td><td></td></td<>		
Tax Credit Eligible:YesENERGY STAR Certified:Kybrid/Electric Heat PumpType:Hybrid/Electric Heat PumpFuel:ElectricMax. Amps:24.0Input Voltage for HPWH (V):VageDraw Pattern (Intended Usage):High-UsageFirst Hour Rating (gallons):20Heat Pump Type:24.0 Volt Integrated HPWHLower Compressor Cut Off Temperature for HPWH (°F):7.4Upper Compressor Cut Off Temperature for HPWH (°F):9.1Stadie (Guider State)1.0Refrigerant with GWP:9.1Stadie (State)5.0Electric Input (kW):5.0Storage Volume (gallons):0.0Storage Volume (gallons):1.8Automater (inches):1.8Storage Volume (inches):0.2Storage Volume (inches		
FNERGY STAR Certified:YesType:Hybrid/Electric Heat PumpFuel:ElectricMax. Amps:24.0Input Voltage for HPWH (V):240Draw Pattern (Intended Usage):High-UsageFirst Hour Rating (gallons):80Heat Pump Type:240 Volt Integrated HPWHLower Compressor Cut Off Temperature for HPWH (*F):37.4Upper Compressor Cut Off Temperature for HPWH (*F):90.0Inform Energy Factor (UEF):3.9Refrigerant with GWP:5.5Electric Input (kW):5.5Electric Usage (kWh/yr):1240.0Storage Volume (gallons):6.0.0Tank Diameter (inches):21.8Tank Height (inches):20.50-116		
Type:Hybrid/Electric Heat PumpFuel:HectricFuel:ElectricMax. Amps:24.0Input Voltage for HPWH (V):240Draw Pattern (Intended Usage):High-UsageFirst Hour Rating (gallons):80Heat Pump Type:240 Vol Integrated HPWHLower Compressor Cut Off Temperature for HPWH (*F):7.4Differenart with GWP:R.134a (GWP:1430)Refrigerant with GWP:3.9Recovery Efficiency (%):5.5Electric Input (kW):5.0Storage Volume (gallons):0.0Att Apper Compressor Cut Off Temperature for Bettric Input (kW):1.240.0Recovery Efficiency (%):9.5Storage Volume (gallons):0.124.0Storage Volume (gallons):0.124.0Storage Volume (gallons):0.124.0Tank Height (inches):0.250.016Date Certified:205.0116	•	
Fuel:ElectricMax. Amps:24.0Input Voltage for HPWH (V):240Draw Pattern (Intended Usage):High-UsageFirst Hour Rating (gallons):80Heat Pump Type:240 Volt Integrated HPWHLower Compressor Cut Off Temperature for HPWH (*F):37.4Upper Compressor Cut Off Temperature for HPWH (*F):107.6Refrigerant with GWP:8.134a (GWP:1430)Uniform Energy Factor (UEF):3.9Recovery Efficiency (%):450.0Electric Input (kW):5.5Electric Usage (kWh/yr):1240.0Storage Volume (gallons):60.0Tank Diameter (inches):21.8Tank Height (inches):20.50-116		
Max. Amps:24.0Input Voltage for HPWH (V):240Draw Pattern (Intended Usage):High-UsageFirst Hour Rating (gallons):80Heat Pump Type:240 Volt Integrated HPWHLower Compressor Cut Off Temperature for HPWH (*F):37.4Dyper Compressor Cut Off Temperature for HPWH (*F):107.6Refrigerant with GWP:N:134a (GWP:1430)Recover Efficiency (%):5.5Electric Input (kW):5.0Electric Input (kW):1240.0Storage Volume (gallons):0.0Tank Height (inches):21.8Date Certified:21.8Compression:21.8 <th></th> <th></th>		
Input Voltage for HPWH (V):240Draw Pattern (Intended Usage):High-UsageFirst Hour Rating (gallons):80Heat Pump Type:240 Volt Integrated HPWHLower Compressor Cut Off Temperature for HPWH (*F):37.4Upper Compressor Cut Off Temperature for HPWH (*F):107.6Refrigerant with GWP:R-134a (GWP:1430)Uniform Energy Factor (UEF):3.9Recovery Efficiency (%):5.5Electric Input (kW):5.5Electric Usage (kWh/yr):1240.0Storage Volume (gallons):6.0Tank Height (inches):21.8Pate Certified:21.8Compression Cut Giff Energies21.8Compression Cut Giff Energies <td></td> <td></td>		
Draw Pattern (Intended Usage):High-UsageFirst Hour Rating (gallons):80Heat Pump Type:240 Volt Integrated HPWHLower Compressor Cut Off Temperature for HPWH (°F):37.4Upper Compressor Cut Off Temperature for HPWH (°F):107.6Refrigerant with GWP:R-134a (GWP:1430)Uniform Energy Factor (UEF):3.9Recovery Efficiency (%):450.0Electric Input (kW):5.5Electric Usage (kWh/yr):1240.0Storage Volume (gallons):6.0Tank Diameter (inches):21.8Date Certified:0250-116	•	
First Hour Rating (gallons):80Heat Pump Type:240 Volt Integrated HPWHLower Compressor Cut Off Temperature for HPWH (°F):37.4Upper Compressor Cut Off Temperature for HPWH (°F):107.6Refrigerant with GWP:R-134a (GWP:1430)Uniform Energy Factor (UEF):3.9Recovery Efficiency (%):450.0Electric Input (kW):5.5Electric Usage (kWh/yr):1240.0Storage Volume (gallons):61.0Tank Diameter (inches):21.8Date Certified:025-01-16		240
Heat Pump Type:240 Volt Integrated HPWHLower Compressor Cut Off Temperature for HPWH (°F):37.4Upper Compressor Cut Off Temperature for HPWH (°F):107.6Refrigerant with GWP:R-134a (GWP:1430)Uniform Energy Factor (UEF):3.9Recovery Efficiency (%):450.0Electric Input (kW):5.5Electric Usage (kWh/yr):60.0Storage Volume (gallons):11.8Tank Diameter (inches):21.8Tank Height (inches):2025-01-16	Draw Pattern (Intended Usage):	High-Usage
Lower Compressor Cut Off Temperature for HPWH (°F):37.4Upper Compressor Cut Off Temperature for HPWH (°F):107.6Refrigerant with GWP:R-134a (GWP:1430)Uniform Energy Factor (UEF):3.9Recovery Efficiency (%):450.0Electric Input (kW):5.5Electric Usage (kWh/yr):1240.0Storage Volume (gallons):60.0Tank Diameter (inches):21.8Tank Height (inches):45.5Date Certified:2025-01-16	First Hour Rating (gallons):	80
HPWH (*F):Image: Compression of the provided of the p	Heat Pump Type:	240 Volt Integrated HPWH
HPWH (°F):Refrigerant with GWP:R-134a (GWP:1430)Refrigerant with GWP:3.9Uniform Energy Factor (UEF):3.9Recovery Efficiency (%):450.0Electric Input (kW):5.5Electric Usage (kWh/yr):1240.0Storage Volume (gallons):60.0Tank Diameter (inches):21.8Tank Height (inches):45.5Date Certified:2025-01-16		37.4
Uniform Energy Factor (UEF):3.9Recovery Efficiency (%):450.0Electric Input (kW):5.5Electric Usage (kWh/yr):1240.0Storage Volume (gallons):60.0Tank Diameter (inches):21.8Tank Height (inches):20.5Date Certified:2025-01-16		107.6
Recovery Efficiency (%):450.0Electric Input (kW):5.5Electric Usage (kWh/yr):1240.0Storage Volume (gallons):60.0Tank Diameter (inches):21.8Tank Height (inches):20.5Date Certified:2025-01-16	Refrigerant with GWP:	R-134a (GWP:1430)
Electric Input (kW):5.5Electric Usage (kWh/yr):1240.0Storage Volume (gallons):60.0Tank Diameter (inches):21.8Date Certified:2025-01-16	Uniform Energy Factor (UEF):	3.9
Electric Usage (kWh/yr):1240.0Storage Volume (gallons):60.0Tank Diameter (inches):21.8Tank Height (inches):20.5Date Certified:2025-01-16	Recovery Efficiency (%):	450.0
Storage Volume (gallons):60.0Tank Diameter (inches):21.8Tank Height (inches):45.5Date Certified:2025-01-16	Electric Input (kW):	5.5
Tank Diameter (inches):21.8Tank Height (inches):45.5Date Certified:2025-01-16	Electric Usage (kWh/yr):	1240.0
Tank Height (inches): 45.5 Date Certified: 2025-01-16	Storage Volume (gallons):	60.0
Date Certified: 2025-01-16	Tank Diameter (inches):	21.8
	Tank Height (inches):	45.5
Markets: United States, Canada	Date Certified:	2025-01-16
	Markets:	United States, Canada

06/17/2025