

## Schneider Electric - Galaxy VS 60kW 480V w/o Batteries, Start-up 5x8 : GVSUPS60KGS

## Specifications

ENERGY STAR Unique ID:2325818Brand Name:Schneider ElectricModel Name:Galaxy VS 60kW 480V w/o Batteries, Start-up 5x8Model Number:OSUDS60KGSPower Conversion Mechanism:StaticNumber:SoutoMinimur Configuration Tested Model60000Number:60000Configuration (W):Multi-Mode Double ConversionActive Output Power Rating Minimum60000Apparent Output Power Rating Minimum60000Apparent Output Power Rating Minimumac - OtherApparent Output Power Rating MinimumBattenderApparent Output Power Rating MinimumBattenderApparent Output Power Rating Minimum60000Rated Input Voltage (Vrms):Bate CenterRated Input Voltage (Vrms):80-480Rated Input Frequency (Hz):60-60Rated Output Frequency (Hz):60-60Rated Output Frequency (Hz):1485Rated Input Singer521Porter847Normal Mode(s) Input DependencyWitage and Frequency Independent, Voltage and Frequency Independe
Model Name:Galaxy VS 60kW 480V w/o Batteries, Start-up 5x8Model Number:GVSUPS60KGSPower Conversion Mechanism:StaticPower Conversion Mechanism:GVSUPS60KGSNumber:G0000Active Output Power Rating Minimum Configuration (W):60000Apparent Output Power Rating Minimum Configuration (VA):60000Topology (ac):Multi-Mode Double ConversionTopology and Product Type Combined:ac - OtherApplication:Data CenterRated Input Voltage (V rms):480-480Rated Output Power (Hz):60-60Rated Output Prequency (Hz):60-60Rated Output Voltage (V):480-480Rated Output Frequency (Hz):60-60Rated Output Frequency (Hz):60-60Rated Input Krequency (Hz):60-60Rated Output Frequency (Hz):60-60Rated Output Frequency (Hz):60-60Rated Input Krequency (Hz):60-60Rated Input Krequency (Hz):60-60Rated Output Frequency (Hz):60-60 </th
Model Number:GVSUPS60KGSPower Conversion Mechanism:StaticMinimum Configuration Tested Model Number:GVSUPS60KGSActive Output Power Rating Minimum Configuration (W):60000Active Output Power Rating Minimum Configuration (VA):60000Apparent Output Power Rating Minimum Configuration (VA):Multi-Mode Double ConversionTopology (ac):Multi-Mode Double ConversionTopology and Product Type Combined:ac - OtherApplication:Data CenterRated Input Voltage (V rms):480-480Rated Output Frequency (Hz):60-60Rated Output Frequency (Hz):60-60Rated Output Frequency (Hz):521Utput frequency (Hz):521Depth (mm):847Normal Mode(s) Input DependencyVoltage and Frequency Independent, Voltage and Frequency Dependent
Power Conversion Mechanism:StaticMinimum Configuration Tested Model Number:GVSUPS60KGSActive Output Power Rating Minimum Configuration (W):60000Apparent Output Power Rating Minimum Configuration (VA):60000Topology (ac):Multi-Mode Double ConversionTopology (ac):Multi-Mode Double ConversionApplication:Data CenterApplication:60-60Rated Input Voltage (V rms):60-60Rated Output Frequency (Hz):60-60Rated Output Frequency (Hz):60-60Rated Output Frequency (Hz):1485Mointable:NoHeight (mm):521Depth (mm):847Normal Mode(s) Input DependencyVoltage and Frequency Independent,Voltage and Frequency Dependent
Minimum Configuration Tested ModelGVSUPS60KGSMinimum Configuration (W):60000Active Output Power Rating Minimum60000Configuration (W):60000Apparent Output Power Rating Minimum60000Configuration (VA):60000Topology (ac):Multi-Mode Double ConversionTopology (ac):Multi-Mode Double ConversionApplication:Data CenterRated Input Voltage (V rms):480-480Rated Input Frequency (Hz):60-60Rated Output Frequency (Hz):60-60Rated Output Frequency (Hz):60-60Rated Mountable:NoHeight (mm):1485Vidth (mm):521Depth (mm):847Normal Mode(s) Input DependencyVoltage and Frequency Independent, Voltage and Frequency Dependent
Number:Image: Image: Image
Configuration (W):Selection (Selection (S
Configuration (VA):Multi-Mode Double ConversionTopology (ac):Multi-Mode Double ConversionTopology and Product Type Combined:ac - OtherApplication:Data CenterRated Input Voltage (V rms):480-480Rated Input Frequency (Hz):60-60Rated Output Voltage (V):480-480Rated Output Voltage (V):480-480Rated Output Frequency (Hz):60-60Rated Output Frequency (Hz):60-60Rated Mountable:NoHeight (mm):1485Width (mm):521Depth (mm):847Normal Mode(s) Input DependencyVoltage and Frequency Independent, Voltage and Frequency Dependent
Topology and Product Type Combined:ac - OtherApplication:Data CenterRated Input Voltage (V rms):480-480Rated Input Frequency (Hz):60-60Rated Output Voltage (V):480-480Rated Output Frequency (Hz):60-60Rated Output Frequency (Hz):60-60Rated Output Frequency (Hz):50-60Rated Mountable:NoHeight (mm):1485Depth (mm):521Normal Mode(s) Input DependencyVoltage and Frequency Independent, Voltage and Frequency Dependent
Application:Data CenterRated Input Voltage (V rms):480-480Rated Input Frequency (Hz):60-60Rated Output Voltage (V):480-480Rated Output Frequency (Hz):60-60Rated Output Frequency (Hz):60-60Rated Output Frequency (Hz):50-60Rated Mountable:NoHeight (mm):1485Solution:521Depth (mm):847Normal Mode(s) Input DependencyVoltage and Frequency Independent, Voltage and Frequency Dependent
Rated Input Voltage (V rms):480-480Rated Input Frequency (Hz):60-60Rated Output Voltage (V):480-480Rated Output Frequency (Hz):60-60Rack Mountable:NoHeight (mm):1485Width (mm):521Depth (mm):847Normal Mode(s) Input DependencyVoltage and Frequency Independent, Voltage and Frequency Dependent
Rated Input Frequency (Hz):60-60Rated Output Voltage (V):480-480Rated Output Frequency (Hz):60-60Rack Mountable:NoHeight (mm):1485Width (mm):521Depth (mm):847Normal Mode(s) Input DependencyVoltage and Frequency Independent, Voltage and Frequency Dependent
Rated Output Voltage (V):480-480Rated Output Frequency (Hz):60-60Rack Mountable:NoHeight (mm):1485Width (mm):521Depth (mm):847Normal Mode(s) Input DependencyVoltage and Frequency Independent, Voltage and Frequency Dependent
Rated Output Frequency (Hz):60-60Rack Mountable:NoHeight (mm):1485Width (mm):521Depth (mm):847Normal Mode(s) Input DependencyVoltage and Frequency Independent, Voltage and Frequency Dependent
Rack Mountable:NoHeight (mm):1485Width (mm):521Depth (mm):847Normal Mode(s) Input DependencyVoltage and Frequency Independent,Voltage and Frequency Dependent
Height (mm):   1485     Width (mm):   521     Depth (mm):   847     Normal Mode(s) Input Dependency   Voltage and Frequency Independent,Voltage and Frequency Dependent
Width (mm):   521     Depth (mm):   847     Normal Mode(s) Input Dependency   Voltage and Frequency Independent, Voltage and Frequency Dependent
Depth (mm):   847     Normal Mode(s) Input Dependency   Voltage and Frequency Independent, Voltage and Frequency Dependent
Normal Mode(s) Input Dependency Voltage and Frequency Independent, Voltage and Frequency Dependent
Modular UPS: No
Number of Normal Modes:     Multiple-normal-mode
Default Normal Mode (ac):     Voltage and Frequency Independent
Test Input Voltage (V rms): 480
Test Input Frequency (Hz): 60
Test Output Voltage (V): 480
Test Output Frequency (Hz): 60
Total Input Power in W at 0% Load Min Config 348.8 Lowest Dependency (ac):

Total Input Power in W at 0% Load Min Config Highest Dependency (ac):	214.2
Efficiency at 25% Load Min Config Lowest Dependency (ac):	95.9
Efficiency at 25% Load Min Config Highest Dependency (ac):	98.4
Efficiency at 50% Load Min Config Lowest Dependency (ac):	97.0
Efficiency at 50% Load Min Config Highest Dependency (ac):	99.0
Efficiency at 75% Load Min Config Lowest Dependency (ac):	97.3
Efficiency at 75% Load Min Config Highest Dependency (ac):	99.2
Efficiency at 100% Load Min Config Lowest Dependency (ac):	97.3
Efficiency at 100% Load Min Config Highest Dependency (ac):	99.3
Weighted Efficiency Calc Min Config Lowest Dependency:	96.8
Weighted Efficiency Calc Min Config Highest Dependency:	98.9
Minimum Configuration Input Power Factor Highest-Input Dependency:	0.98
Efficiency (%):	96.8
Modular UPS Module Tested Model Number:	N/A
Energy Storage Mechanism:	Battery
Energy Storage System Technology:	Valve Regulated Lead-acid Battery
Energy Storage System Configuration:	Separate Enclosure
Energy Storage System Removable to Another Room:	Yes
Energy Storage System Runtime at 100% Load (min.):	N/A
Energy Storage System Runtime at 50% Load (min.):	N/A
Energy Storage System Warranty (yrs):	N/A
Energy Storage System Information URL:	N/A
Battery Recycling URL:	https://www.apc.com/us/en/who-we-are/sustainability/recycling- options.jsp
Network Connections Available:	Serial Port,Ethernet
Communication Protocols:	HTTP,HTTPS,Other,Modbus TCP,SNMP (v1, 2 or 3),Modbus RTU
Communication Protocol Other:	BACnet/IP
Manufacturer Take Back Program:	Yes
Manufacturer Take Back Program URL:	https://www.apc.com/us/en/who-we-are/sustainability/recycling- options.jsp
Model Web Page URL:	https://www.apc.com/shop/us/en/products/P-GVSUPS60KGS
Test Method Guidelines:	https://www.apc.com/us/en/who-we-are/sustainability/
Date Available on Market:	2021-03-01

## 2018-07-27

Markets:

United States, Canada

ENERGY STAR Certified:

Yes

## Additional Model Information

Galaxy VS 60kW 480V without Batteries, GVSUPS60KG,

Captured On: 06/13/2025