



ENERGY STAR CERTIFIED

Uninterruptible Power Supplies

Delta - RT-3K : RT-3K

Specifications

| | |
|--|-----------------------------------|
| ENERGY STAR Unique ID: | 2326091 |
| Brand Name: | Delta |
| Model Name: | RT-3K |
| Model Number: | RT-3K |
| Power Conversion Mechanism: | Static |
| Minimum Configuration Tested Model Number: | RT-3K |
| Active Output Power Rating Minimum Configuration (W): | 2700 |
| Apparent Output Power Rating Minimum Configuration (VA): | 3000 |
| Topology (ac): | Double Conversion |
| Topology and Product Type Combined: | ac - Double Conversion (VFI) |
| Application: | Consumer |
| Rated Input Voltage (V rms): | 100-120 |
| Rated Input Frequency (Hz): | 50-60 |
| Rated Output Voltage (V): | 100-120 |
| Rated Output Frequency (Hz): | 50-60 |
| Rack Mountable: | Yes |
| Height (mm): | 88 |
| Width (mm): | 440 |
| Depth (mm): | 565 |
| Normal Mode(s) Input Dependency Characteristic (ac): | Voltage and Frequency Independent |
| Modular UPS: | No |
| Number of Normal Modes: | Single-normal-mode |
| Default Normal Mode (ac): | Voltage and Frequency Independent |
| Test Input Voltage (V rms): | 120 |
| Test Input Frequency (Hz): | 60 |
| Test Output Voltage (V): | 120 |
| Test Output Frequency (Hz): | 60 |
| Total Input Power in W at 0% Load Min Config Lowest Dependency (ac): | 53.656 |
| Efficiency at 25% Load Min Config Lowest Dependency (ac): | 87.4 |

| | |
|---|-----------------------------------|
| Efficiency at 50% Load Min Config Lowest Dependency (ac): | 91.4 |
| Efficiency at 75% Load Min Config Lowest Dependency (ac): | 92.3 |
| Efficiency at 100% Load Min Config Lowest Dependency (ac): | 92.1 |
| Weighted Efficiency Calc Min Config Lowest Dependency: | 92.0 |
| Efficiency (%): | 92 |
| Modular UPS Module Tested Model Number: | N/A |
| Energy Storage Mechanism: | Battery |
| Energy Storage System Technology: | Valve Regulated Lead-acid Battery |
| Energy Storage System Configuration: | Integral |
| Energy Storage System Removable to Another Room: | N/A |
| Energy Storage System Runtime at 100% Load (min.): | 3 |
| Energy Storage System Runtime at 50% Load (min.): | 12 |
| Energy Storage System Warranty (yrs): | 3 |
| Energy Storage System Information URL: | N/A |
| Network Connections Available: | Serial Port,Ethernet,USB Port |
| Communication Protocols: | Other |
| Communication Protocol Other: | USB HID Power Devices |
| Manufacturer Take Back Program: | No |
| Model Web Page URL: | N/A |
| Test Method Guidelines: | N/A |
| Date Available on Market: | 2018-11-01 |
| Date Certified: | 2018-09-19 |
| Markets: | United States, Taiwan, Canada |
| ENERGY STAR Certified: | Yes |

Captured On:
05/02/2025