

## APC by Schneider Electric - APC Smart-UPS SRT 3000VA RM 208V Network Card : SRT3000RMXLT-NC

| Specifications  |  |
|---|--|
| ENERGY STAR Unique ID:                                      | 2332849  |
| Brand Name:   | APC by Schneider Electric  |
| Model Name:   | APC Smart-UPS SRT 3000VA RM 208V Network Card                      |
| Model Number:   | SRT3000RMXLT-NC  |
| Power Conversion Mechanism:                                 | Static   |
| Minimum Configuration Tested Model<br>Number:               | SRT3000RMXLT-NC  |
| Active Output Power Rating Minimum<br>Configuration (W):    | 2700   |
| Apparent Output Power Rating Minimum<br>Configuration (VA): | 3000   |
| Topology (ac):  | Multi-Mode Double Conversion                                       |
| Topology and Product Type Combined:                         | ac - Other   |
| Application:  | Commercial   |
| Rated Input Voltage (V rms):                                | 208-240  |
| Rated Input Frequency (Hz):                                 | 50-60  |
| Rated Output Voltage (V):                                   | 208-240  |
| Rated Output Frequency (Hz):                                | 50-60  |
| Rack Mountable:   | Yes  |
| Rack Mount Height (U):                                      | 2  |
| Height (mm):  | 85   |
| Width (mm):   | 432  |
| Depth (mm):   | 635  |
| Total Number of Outlets:                                    | 3  |
| Number of Battery Backup and Surge<br>Protected Outlets:    | 3  |
| Number of Surge Protected Only Outlets:                     | 0  |
| Normal Mode(s) Input Dependency<br>Characteristic (ac):     | Voltage and Frequency Dependent, Voltage and Frequency Independent |
| Modular UPS:  | No   |
| Number of Normal Modes:                                     | Multiple-normal-mode   |
| Default Normal Mode (ac):                                   | Voltage and Frequency Independent                                  |
| Test Input Voltage (V rms):                                 | 240  |
| Test Input Frequency (Hz):                                  | 60   |

| Test Output Voltage (V):   | 240  |
|--|--|
| Test Output Frequency (Hz):  | 60   |
| Total Input Power in W at 0% Load Min Config<br>Lowest Dependency (ac):  | 57.68  |
| Total Input Power in W at 0% Load Min Config<br>Highest Dependency (ac): | 46.68  |
| Efficiency at 25% Load Min Config Lowest<br>Dependency (ac):             | 89.7   |
| Efficiency at 25% Load Min Config Highest<br>Dependency (ac):            | 93.4   |
| Efficiency at 50% Load Min Config Lowest<br>Dependency (ac):             | 92.9   |
| Efficiency at 50% Load Min Config Highest<br>Dependency (ac):            | 96.4   |
| Efficiency at 75% Load Min Config Lowest<br>Dependency (ac):             | 93.5   |
| Efficiency at 75% Load Min Config Highest<br>Dependency (ac):            | 97.4   |
| Efficiency at 100% Load Min Config Lowest<br>Dependency (ac):            | 93.8   |
| Efficiency at 100% Load Min Config Highest<br>Dependency (ac):           | 97.9   |
| Weighted Efficiency Calc Min Config Lowest<br>Dependency:                | 93.4   |
| Weighted Efficiency Calc Min Config Highest<br>Dependency:               | 97.3   |
| Minimum Configuration Input Power Factor<br>Highest-Input Dependency:    | 1.0  |
| Efficiency (%):  | 93.4   |
| Modular UPS Module Tested Model Number:                                  | N/A  |
| Energy Storage Mechanism:  | Battery  |
| Energy Storage System Technology:  | Valve Regulated Lead-acid Battery                                  |
| Energy Storage System Configuration:                                     | Integral   |
| Energy Storage System Removable to Another Room:                         | No   |
| Energy Storage System Runtime at 100% Load (min.):                       | 4  |
| Energy Storage System Runtime at 50% Load (min.):                        | 11   |
| Energy Storage System Warranty (yrs):                                    | 2  |
| Energy Storage System Information URL:                                   | http://www.apc.com/shop/us/en/products/P-APCRBC152                 |
| Battery Recycling URL:   | http://www.apc.com/company/us/en/sustainability/recycling-options/ |
| Network Connections Available:   | Serial Port,USB Port,Ethernet                                      |
| Communication Protocols:   | Modbus TCP,HTTPS,Other,HTTP,Modbus RTU                             |
| Communication Protocol Other:  | USB Power Summary, Micro-Link, Simple Signaling                    |
| Manufacturer Take Back Program:  | Yes  |
| Manufacturer Take Back Program URL:                                      | http://www.apc.com/company/us/en/sustainability/recycling-options/ |

| Model Web Page URL:       | http://www.apc.com/shop/us/en/products/P-SRT3000RMXLT-NC           |
|---------------------------|--|
| Test Method Guidelines:   | http://www.apc.com/company/us/en/sustainability/energy-efficiency/ |
| Date Available on Market: | 2016-06-16   |
| Date Certified:           | 2018-12-28   |
| Markets:                  | United States, Canada  |
| ENERGY STAR Certified:    | Yes  |

## Additional Model Information

APC Smart-UPS SRT 3000VA RM 208V Network Card Factory Serviced,SRT3000RXLTNCW,; Std Exch APC Smart-UPS SR T 3000VA RM 208V,SRT3000RXLTNCQ,

**UPC Codes** 731304327608

Captured On: 06/19/2025