



ENERGY STAR CERTIFIED

Uninterruptible Power Supplies

APC by Schneider Electric - APC Back-UPS Pro 1500VA
Tower 120V 10 NEMA 5-15RAPC Back-UPS Pro 1500VA
Tower 120V 10 NEMA 5-15R outlets LCD 1 USB Type C + 1
USB Type A ports : BN1500M2

Specifications

ENERGY STAR Unique ID:	2333482
Brand Name:	APC by Schneider Electric
Model Name:	APC Back-UPS Pro 1500VA Tower 120V 10 NEMA 5-15RAPC Back-UPS Pro 1500VA Tower 120V 10 NEMA 5-15R outlets LCD 1 USB Type C + 1 USB Type A ports
Model Number:	BN1500M2
Power Conversion Mechanism:	Static
Minimum Configuration Tested Model Number:	BN1500M2
Active Output Power Rating Minimum Configuration (W):	900
Apparent Output Power Rating Minimum Configuration (VA):	1500
Topology (ac):	Line Interactive
Topology and Product Type Combined:	ac Line Interactive (VI)
Application:	Consumer
Rated Input Voltage (V rms):	120-120
Rated Input Frequency (Hz):	60-60
Rated Output Voltage (V):	120-120
Rated Output Frequency (Hz):	60-60
Rack Mountable:	No
Height (mm):	260
Width (mm):	100
Depth (mm):	368
Total Number of Outlets:	10
Number of Battery Backup and Surge Protected Outlets:	6
Number of Surge Protected Only Outlets:	4
Normal Mode(s) Input Dependency Characteristic (ac):	Voltage and Frequency Dependent
Modular UPS:	No
Number of Normal Modes:	Single-normal-mode

Default Normal Mode (ac):	Voltage and Frequency Dependent
Test Input Voltage (V rms):	120
Test Input Frequency (Hz):	60
Test Output Voltage (V):	120
Test Output Frequency (Hz):	60
Total Input Power in W at 0% Load Min Config Lowest Dependency (ac):	3.06
Efficiency at 25% Load Min Config Lowest Dependency (ac):	98.5
Efficiency at 50% Load Min Config Lowest Dependency (ac):	99.0
Efficiency at 75% Load Min Config Lowest Dependency (ac):	99.1
Efficiency at 100% Load Min Config Lowest Dependency (ac):	99.1
Weighted Efficiency Calc Min Config Lowest Dependency:	99.0
Efficiency (%):	99
Modular UPS Module Tested Model Number:	N/A
Energy Storage Mechanism:	Battery
Energy Storage System Technology:	Valve Regulated Lead-acid Battery
Energy Storage System Configuration:	Integral
Energy Storage System Removable to Another Room:	No
Energy Storage System Runtime at 100% Load (min.):	3
Energy Storage System Runtime at 50% Load (min.):	11
Energy Storage System Warranty (yrs):	3
Energy Storage System Information URL:	https://www.se.com/us/en/product/APCRBC161
Battery Recycling URL:	https://www.apc.com/us/en/who-we-are/sustainability/recycling-options.jsp
Network Connections Available:	USB Port
Communication Protocols:	Other
Communication Protocol Other:	USB Power Summary
Manufacturer Take Back Program:	Yes
Manufacturer Take Back Program URL:	https://www.apc.com/us/en/who-we-are/sustainability/recycling-options.jsp
Model Web Page URL:	https://www.se.com/us/en/product/BN1500M2
Test Method Guidelines:	N/A
Date Available on Market:	2017-12-03
Date Certified:	2019-02-12
Markets:	United States
ENERGY STAR Certified:	Yes

Additional Model Information

APC Back-UPS Pro 1500VA Tower 120V 10 NEMA 5-15R outlets LCD 1 USB Type C + 1 USB Type A ports Factory Serviced,BN1500M2W,; Std Exch APC Back-UPS Pro 1500VA Tower 120V 10 NEMA 5-15R outlets LCD 1 USB Type C + 1 USB Type A ports,BN1500M2Q,

UPC Codes	731304335375
-----------	--------------

Captured On:
05/01/2025