



ENERGY STAR CERTIFIED

Uninterruptible Power Supplies

APC by Schneider Electric - APC Smart-UPS SRT 3000VA 120V : SRT3000XLA

Specifications

ENERGY STAR Unique ID:	2333700
Brand Name:	APC by Schneider Electric
Model Name:	APC Smart-UPS SRT 3000VA 120V
Model Number:	SRT3000XLA
Power Conversion Mechanism:	Static
Minimum Configuration Tested Model Number:	SRT3000RMXLA
Active Output Power Rating Minimum Configuration (W):	2700
Apparent Output Power Rating Minimum Configuration (VA):	3000
Topology (ac):	Multi-Mode Double Conversion
Topology and Product Type Combined:	ac - Other
Application:	Commercial
Rated Input Voltage (V rms):	120-120
Rated Input Frequency (Hz):	50-60
Rated Output Voltage (V):	120-120
Rated Output Frequency (Hz):	50-60
Rack Mountable:	No
Height (mm):	432
Width (mm):	85
Depth (mm):	635
Total Number of Outlets:	9
Number of Battery Backup and Surge Protected Outlets:	9
Number of Surge Protected Only Outlets:	0
Normal Mode(s) Input Dependency Characteristic (ac):	Voltage and Frequency Dependent,Voltage and Frequency Independent
Modular UPS:	No
Number of Normal Modes:	Multiple-normal-mode
Default Normal Mode (ac):	Voltage and Frequency Independent
Test Input Voltage (V rms):	120
Test Input Frequency (Hz):	60
Test Output Voltage (V):	120

Test Output Frequency (Hz):	60
Total Input Power in W at 0% Load Min Config Lowest Dependency (ac):	44.16
Total Input Power in W at 0% Load Min Config Highest Dependency (ac):	34.48
Efficiency at 25% Load Min Config Lowest Dependency (ac):	91.2
Efficiency at 25% Load Min Config Highest Dependency (ac):	94.9
Efficiency at 50% Load Min Config Lowest Dependency (ac):	93.2
Efficiency at 50% Load Min Config Highest Dependency (ac):	97.0
Efficiency at 75% Load Min Config Lowest Dependency (ac):	93.3
Efficiency at 75% Load Min Config Highest Dependency (ac):	97.5
Efficiency at 100% Load Min Config Lowest Dependency (ac):	92.5
Efficiency at 100% Load Min Config Highest Dependency (ac):	97.6
Weighted Efficiency Calc Min Config Lowest Dependency:	93.0
Weighted Efficiency Calc Min Config Highest Dependency:	97.4
Minimum Configuration Input Power Factor Highest-Input Dependency:	1.0
Efficiency (%):	93
Modular UPS Module Tested Model Number:	N/A
Energy Storage Mechanism:	Battery
Energy Storage System Technology:	Valve Regulated Lead-acid Battery
Energy Storage System Configuration:	Integral
Energy Storage System Removable to Another Room:	No
Energy Storage System Runtime at 100% Load (min.):	3
Energy Storage System Runtime at 50% Load (min.):	10
Energy Storage System Warranty (yrs):	2
Energy Storage System Information URL:	http://www.apc.com/shop/us/en/products/P-APCRBC152
Battery Recycling URL:	http://www.apc.com/company/us/en/sustainability/recycling-options/
Network Connections Available:	Serial Port,USB Port
Communication Protocols:	Other,Modbus RTU
Communication Protocol Other:	USB Power Summary, Micro-Link, Simple Signaling
Manufacturer Take Back Program:	Yes
Manufacturer Take Back Program URL:	http://www.apc.com/company/us/en/sustainability/recycling-options/
Model Web Page URL:	http://www.apc.com/shop/us/en/products/P-SRT3000XLA

Test Method Guidelines:	http://www.apc.com/company/us/en/sustainability/energy-efficiency/
Date Available on Market:	2019-01-01
Date Certified:	2019-02-14
Markets:	United States, Canada
ENERGY STAR Certified:	Yes

Additional Model Information

APC Smart-UPS SRT 3000VA 120V Factory Serviced,SRT3000XLAW;; Std Exch APC Smart-UPS SRT 3000VA 120V,SRT3000XLAQ,

UPC Codes	731304325185
------------------	--------------

Captured On:
06/18/2025