

Schneider Electric - Galaxy VM 225 kVA UPS Single 480-480 V, 65kAIC, : GVMSB225KG65S

Specifications

ENERGY STAR Unique ID:	2333995
Brand Name:	Schneider Electric
Model Name:	Galaxy VM 225 kVA UPS Single 480-480 V, 65kAIC,
Model Number:	GVMSB225KG65S
Power Conversion Mechanism:	Static
Minimum Configuration Tested Model Number:	GVMPB225KGS
Active Output Power Rating Minimum Configuration (W):	202500
Apparent Output Power Rating Minimum Configuration (VA):	225000
Topology (ac):	Double Conversion
Topology and Product Type Combined:	ac - Double Conversion (VFI)
Application:	Data Center
Rated Input Voltage (V rms):	480-480
Rated Input Frequency (Hz):	50-60
Rated Output Voltage (V):	480-480
Rated Output Frequency (Hz):	50-60
Rack Mountable:	No
Height (mm):	1970
Width (mm):	1002
Depth (mm):	854
Normal Mode(s) Input Dependency Characteristic (ac):	Voltage and Frequency Dependent, Voltage and Frequency Independent
Modular UPS:	No
Number of Normal Modes:	Multiple-normal-mode
Default Normal Mode (ac):	Voltage and Frequency Independent
Test Input Voltage (V rms):	480
Test Input Frequency (Hz):	60
Test Output Voltage (V):	480
Test Output Frequency (Hz):	60
Total Input Power in W at 0% Load Min Config Lowest Dependency (ac):	1038.0

Total Input Power in W at 0% Load Min Config Highest Dependency (ac):	530.0	
Efficiency at 25% Load Min Config Lowest Dependency (ac):	95.8	
Efficiency at 25% Load Min Config Highest Dependency (ac):	98.5	
Efficiency at 50% Load Min Config Lowest Dependency (ac):	96.4	
Efficiency at 50% Load Min Config Highest Dependency (ac):	99.1	
Efficiency at 75% Load Min Config Lowest Dependency (ac):	96.6	
Efficiency at 75% Load Min Config Highest Dependency (ac):	99.4	
Efficiency at 100% Load Min Config Lowest Dependency (ac):	96.4	
Efficiency at 100% Load Min Config Highest Dependency (ac):	99.5	
Weighted Efficiency Calc Min Config Lowest Dependency:	96.3	
Weighted Efficiency Calc Min Config Highest Dependency:	99.0	
Minimum Configuration Input Power Factor Highest-Input Dependency:	1.0	
Efficiency (%):	97	
Modular UPS Module Tested Model Number:	N/A	
Energy Storage Mechanism:	Battery	
Energy Storage System Technology:	Valve Regulated Lead-acid Battery	
Energy Storage System Configuration:	Separate Enclosure	
Energy Storage System Removable to Another Room:	Yes	
Energy Storage System Runtime at 100% Load (min.):	N/A	
Energy Storage System Runtime at 50% Load (min.):	N/A	
Energy Storage System Warranty (yrs):	N/A	
Energy Storage System Information URL:	https://www.apc.com/template/size/apc/sizing_display_options.cfm? option_type=Battery&interface=UPS&famid=483&ups_sku=GVMSB225KG	65S
Battery Recycling URL:	https://www.apc.com/company/us/en/sustainability/recycling-options/	
Network Connections Available:	Serial Port,Ethernet	
Communication Protocols:	Modbus TCP,HTTPS,HTTP,Modbus RTU	
Communication Protocol Other:	SNMP (v1, 2 or 3)	
Manufacturer Take Back Program:	Yes	
Manufacturer Take Back Program URL:	https://www.apc.com/company/us/en/sustainability/recycling-options/	
Model Web Page URL:	https://www.apc.com/shop/us/en/products/P-GVMSB225KG65S	
Test Method Guidelines:	https://www.apc.com/company/us/en/sustainability/energy-efficiency/	
Date Available on Market:	2015-09-23	

Additional Model Information

,GVMSB225KGS,

UPC Codes 7313

731304326571

Captured On: 06/17/2025