

## Tripp Lite - AGPS8295 : SUINT1500LCD2U

Specifications	
ENERGY STAR Unique ID:	2337297
Brand Name:	Tripp Lite
Model Name:	AGPS8295
Model Number:	SUINT1500LCD2U
Power Conversion Mechanism:	Static
Minimum Configuration Tested Model Number:	AGPS8295
Active Output Power Rating Minimum Configuration (W):	1350
Apparent Output Power Rating Minimum Configuration (VA):	240
Topology (ac):	Multi-Mode Double Conversion
Topology and Product Type Combined:	ac - Other
Application:	Commercial,Consumer
Rated Input Voltage (V rms):	200-240
Rated Input Frequency (Hz):	50-60
Rated Output Voltage (V):	200-240
Rated Output Frequency (Hz):	50-60
Rack Mountable:	Yes
Rack Mount Height (U):	2
Height (mm):	88
Width (mm):	438
Depth (mm):	496
Total Number of Outlets:	6
Number of Battery Backup and Surge Protected Outlets:	6
Number of Surge Protected Only Outlets:	0
Normal Mode(s) Input Dependency Characteristic (ac):	Voltage and Frequency Dependent, Voltage and Frequency Independent
Modular UPS:	No
Number of Normal Modes:	Multiple-normal-mode
Default Normal Mode (ac):	Voltage and Frequency Dependent
Test Input Voltage (V rms):	240
Test Input Frequency (Hz):	60
Test Output Voltage (V):	1350

Test Output Frequency (Hz):	1350
Total Input Power in W at 0% Load Min Config Lowest Dependency (ac):	0.445
Total Input Power in W at 0% Load Min Config Highest Dependency (ac):	0.407
Efficiency at 25% Load Min Config Lowest Dependency (ac):	86.8
Efficiency at 25% Load Min Config Highest Dependency (ac):	89.4
Efficiency at 50% Load Min Config Lowest Dependency (ac):	91.4
Efficiency at 50% Load Min Config Highest Dependency (ac):	94.5
Efficiency at 75% Load Min Config Lowest Dependency (ac):	92.9
Efficiency at 75% Load Min Config Highest Dependency (ac):	96.2
Efficiency at 100% Load Min Config Lowest Dependency (ac):	93.6
Efficiency at 100% Load Min Config Highest Dependency (ac):	98.9
Weighted Efficiency Calc Min Config Lowest Dependency:	92.6
Weighted Efficiency Calc Min Config Highest Dependency:	95.3
Minimum Configuration Input Power Factor Highest-Input Dependency:	0.99
Efficiency (%):	93.3
Modular UPS Module Tested Model Number:	N/A
Energy Storage Mechanism:	Battery
Energy Storage System Technology:	Valve Regulated Lead-acid Battery
Energy Storage System Configuration:	Integral
Energy Storage System Removable to Another Room:	No
Energy Storage System Runtime at 100% Load (min.):	4
Energy Storage System Runtime at 50% Load (min.):	13
Energy Storage System Warranty (yrs):	3
Energy Storage System Information URL:	N/A
Battery Recycling URL:	http://www.tripplite.com/en/support/recycling-program.cfm
Network Connections Available:	Serial Port,USB Port,Ethernet
Communication Protocols:	None
Manufacturer Take Back Program:	Yes
Manufacturer Take Back Program URL:	http://www.tripplite.com/en/support/recycling-program.cfm
Model Web Page URL:	https://www.tripplite.com/smartonline-208-230v-1.5kva-1.35kw-double-conversion-ups-2u-extended-run-snmp-card-option-lcd-usb-db9-energy-star~SUINT1500LCD2U

Test Method Guidelines:	N/A
Date Available on Market:	2019-01-28
Date Certified:	2016-02-03
Markets:	United States, Canada
<b>ENERGY STAR Certified:</b>	Yes

## Additional Model Information

,SUINT1500LCD2N,

**Captured On:** 05/02/2025