

APC by Schneider Electric - APC SMART-UPS SRT 2200VA RM 120V Network Card With 10FT Input Cord : SRT2K2RXLNX145

Specifications

•	
ENERGY STAR Unique ID:	2354534
Brand Name:	APC by Schneider Electric
Model Name:	APC SMART-UPS SRT 2200VA RM 120V Network Card With 10FT Input Cord
Model Number:	SRT2K2RXLNX145
Power Conversion Mechanism:	Static
Minimum Configuration Tested Model Number:	SRT2K2RXLNX145
Active Output Power Rating Minimum Configuration (W):	1800
Apparent Output Power Rating Minimum Configuration (VA):	2200
Topology (ac):	Multi-Mode Double Conversion
Topology and Product Type Combined:	ac - Other
Application:	Commercial
Rated Input Voltage (V rms):	120-120
Rated Input Frequency (Hz):	50-60
Rated Output Voltage (V):	120-120
Rated Output Frequency (Hz):	50-60
Rack Mountable:	Yes
Rack Mount Height (U):	2
Height (mm):	85
Width (mm):	432
Depth (mm):	584
Total Number of Outlets:	7
Number of Battery Backup and Surge Protected Outlets:	7
Number of Surge Protected Only Outlets:	0
Normal Mode(s) Input Dependency Characteristic (ac):	Voltage and Frequency Independent, Voltage and Frequency Dependent
Modular UPS:	No
Number of Normal Modes:	Multiple-normal-mode
Default Normal Mode (ac):	Voltage and Frequency Independent

Test Input Voltage (V rms):	120
Test Input Frequency (Hz):	60
Test Output Voltage (V):	120
Test Output Frequency (Hz):	60
Total Input Power in W at 0% Load Min Config	46.396
Lowest Dependency (ac):	+0.570
Total Input Power in W at 0% Load Min Config Highest Dependency (ac):	36.196
Efficiency at 25% Load Min Config Lowest Dependency (ac):	88.4
Efficiency at 25% Load Min Config Highest Dependency (ac):	92.3
Efficiency at 50% Load Min Config Lowest Dependency (ac):	91.9
Efficiency at 50% Load Min Config Highest Dependency (ac):	95.7
Efficiency at 75% Load Min Config Lowest Dependency (ac):	92.2
Efficiency at 75% Load Min Config Highest Dependency (ac):	96.6
Efficiency at 100% Load Min Config Lowest Dependency (ac):	92.3
Efficiency at 100% Load Min Config Highest Dependency (ac):	97.0
Weighted Efficiency Calc Min Config Lowest Dependency:	92.2
Weighted Efficiency Calc Min Config Highest Dependency:	96.5
Minimum Configuration Input Power Factor Highest-Input Dependency:	1.0
Efficiency (%):	92.2
Modular UPS Module Tested Model Number:	N/A
Energy Storage Mechanism:	Battery
Energy Storage System Technology:	Valve Regulated Lead-acid Battery
Energy Storage System Configuration:	Integral
Energy Storage System Removable to Another Room:	No
Energy Storage System Runtime at 100% Load (min.):	3
Energy Storage System Runtime at 50% Load (min.):	10
Energy Storage System Warranty (yrs):	2
Energy Storage System Information URL:	https://www.apc.com/shop/us/en/products/P-APCRBC141
Battery Recycling URL:	https://www.apc.com/us/en/who-we-are/sustainability/recycling- options.jsp
Network Connections Available:	Serial Port,USB Port,Ethernet
Communication Protocols:	HTTP,HTTPS,Other,Modbus TCP,SNMP (v1, 2 or 3),Modbus RTU
Communication Protocol Other:	USB Power Summary, Micro-Link, Simple Signaling

Manufacturer Take Back Program:	Yes
Manufacturer Take Back Program URL:	https://www.apc.com/us/en/who-we-are/sustainability/recycling- options.jsp
Model Web Page URL:	https://www.apc.com/shop/us/en/products/P-SRT2K2RXLNX145
Test Method Guidelines:	https://www.apc.com/us/en/who-we-are/sustainability/
Date Available on Market:	2020-02-28
Date Certified:	2020-02-06
Markets:	United States, Canada
ENERGY STAR Certified:	Yes

Additional Model Information

APC SMART-UPS SRT 2200VA RM 120V Network Card With 10FT Input Cord Factory Serviced,SRT2K2RXLNX145W,; Std Exch APC SMART-UPS SRT 2200VA RM 120V Network Card With 10FT Input Cord,SRT2K2RXLNX145Q,

UPC Codes 731304406266

Captured On: 06/18/2025