

APC by Schneider Electric - Back UPS PRO BR 1500VA SineWave 10 Outlets 2 USB Charging Ports AVR LCD interface: BR1500MS2

ENERGY STAR Unique ID: 2365322 Brand Name: APC by Schneider Electric Back UPS PRO BR 1500VA SineWave 10 Outlets 2 USB Charging Ports AVR LCD interface		
Brand Name: APC by Schneider Electric Model Name: Back UPS PRO BR 1500VA SineWave 10 Outlets 2 USB Charging Ports AVR LCD Interface Model Number: BR1500MS2 Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: BR1500MS Active Output Power Rating Minimum Configuration (W): 900 Apparent Output Power Rating Minimum Configuration (VA): 1500 Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Consumer Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 60-60 Rated Output Frequency (Hz): 60-60 Rated Output Frequency (Hz): 60-60 Rated Muntable: No Height (mm): 260 Wildth (mm): 100 Depth (mm): 368 Total Number of Outlets: 10 Number of Battery Backup and Surge Protected Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): No Modular UPS: No Modular UPS:<	Specifications	
Model Name: Back UPS PRO BR 1500VA SineWave 10 Outlets 2 USB Charging Ports AVR LCD interface Model Number: BR1500MS2 Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: BR1500MS Active Output Power Rating Minimum Configuration (W): 900 Apparent Output Power Rating Minimum Configuration (VA): 1500 Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Consumer Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 120-120 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 260 Width (mm): 100 Depth (mm): 368 Total Number of Outlets: 10 Number of Battery Backup and Surge Protected Outly Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): No Modular UPS: No No Induction	ENERGY STAR Unique ID:	2365322
Model Number: BR1500MS2 Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: BR1500MS Active Output Power Rating Minimum Pooriguration (W): Apparent Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Consumer Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 60-60 Rated Output Power (Hz): 60-60 Rack Mountable: No Height (mm): 260 Width (mm): 100 Depth (mm): 368 Total Number of Battery Backup and Surge Protected Outlets: 10 Number of Surge Protected Only Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent	Brand Name:	APC by Schneider Electric
Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: BR1500MS Active Output Power Rating Minimum Configuration (W): 900 Apparent Output Power Rating Minimum Configuration (VA): 1500 Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Consumer Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 260 Width (mm): 100 Depth (mm): 368 Total Number of Outlets: 10 Number of Sattery Backup and Surge Protected Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): Voltage Independent Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent	Model Name:	Back UPS PRO BR 1500VA SineWave 10 Outlets 2 USB Charging Ports AVR LCD interface
Minimum Configuration Tested Model Number: Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Topology and Product Type Combined: Application: Rated Input Voltage (V rms): Rated Input Frequency (Hz): Rated Output Voltage (V): Rated Output Voltage (V): Rated Output Voltage (V): Rated Output Frequency (Hz): Ro-60 Rated Output Frequency (Hz): Ro-60 Rack Mountable: No Height (mm): 260 Width (mm): 100 Depth (mm): 368 Total Number of Outlets: Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent	Model Number:	BR1500MS2
Number: Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Consumer Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 120-120 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 260 Width (mm): 100 Depth (mm): 368 Total Number of Outlets: 10 Number of Battery Backup and Surge Protected Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): No No Nomal Mode(s) Input Dependency Characteristic (ac): No No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent	Power Conversion Mechanism:	Static
Configuration (W): 1500 Apparent Output Power Rating Minimum Configuration (VA): 1500 Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Consumer Rated Input Voltage (V rms): 120-120 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 260 Width (mm): 100 Depth (mm): 368 Total Number of Outlets: 10 Number of Battery Backup and Surge Protected Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): Voltage Independent Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent		BR1500MS
Configuration (VA):Line InteractiveTopology (ac):Line Interactive (VI)Application:ConsumerRated Input Voltage (V rms):120-120Rated Input Frequency (Hz):60-60Rated Output Voltage (V):120-120Rated Output Frequency (Hz):60-60Rack Mountable:NoHeight (mm):260Width (mm):100Depth (mm):368Total Number of Outlets:10Number of Battery Backup and Surge Protected Outlets:6Number of Surge Protected Only Outlets:4Normal Mode(s) Input Dependency Characteristic (ac):NoModular UPS:NoNumber of Normal Modes:Single-normal-modeDefault Normal Mode (ac):Voltage Independent		900
Topology and Product Type Combined: Application: Consumer Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 260 Width (mm): 100 Depth (mm): 368 Total Number of Outlets: 10 Number of Battery Backup and Surge Protected Only Outlets: Voltage Independent Characteristic (ac): No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent		1500
Application: Consumer Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 260 Width (mm): 100 Depth (mm): 368 Total Number of Outlets: 10 Number of Battery Backup and Surge Protected Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): Voltage Independent Mumber of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent	Topology (ac):	Line Interactive
Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 260 Width (mm): 100 Depth (mm): 368 Total Number of Outlets: 10 Number of Battery Backup and Surge Protected Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): Voltage Independent Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent	Topology and Product Type Combined:	ac Line Interactive (VI)
Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 260 Width (mm): 100 Depth (mm): 368 Total Number of Outlets: 10 Number of Battery Backup and Surge Protected Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent	Application:	Consumer
Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 260 Width (mm): 100 Depth (mm): 368 Total Number of Outlets: 10 Number of Battery Backup and Surge Protected Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent	Rated Input Voltage (V rms):	120-120
Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 260 Width (mm): 100 Depth (mm): 368 Total Number of Outlets: 10 Number of Battery Backup and Surge Protected Outlets: 4 Number of Surge Protected Only Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent	Rated Input Frequency (Hz):	60-60
Rack Mountable: Height (mm): 260 Width (mm): 100 Depth (mm): 368 Total Number of Outlets: 10 Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent	Rated Output Voltage (V):	120-120
Height (mm): 260 Width (mm): 100 Depth (mm): 368 Total Number of Outlets: 10 Number of Battery Backup and Surge Protected Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent	Rated Output Frequency (Hz):	60-60
Width (mm): 100 Depth (mm): 368 Total Number of Outlets: 10 Number of Battery Backup and Surge Protected Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): Voltage Independent Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent	Rack Mountable:	No
Depth (mm): Total Number of Outlets: Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: Voltage Independent Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent	Height (mm):	260
Total Number of Outlets: Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Voltage Independent	Width (mm):	100
Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Outlets: 4 Voltage Independent Voltage Independent	Depth (mm):	368
Number of Surge Protected Only Outlets: Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Voltage Independent	Total Number of Outlets:	10
Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent		6
Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Voltage Independent	Number of Surge Protected Only Outlets:	4
Number of Normal Modes: Default Normal Mode (ac): Voltage Independent		Voltage Independent
Default Normal Mode (ac): Voltage Independent	Modular UPS:	No
	Number of Normal Modes:	Single-normal-mode
Test Input Voltage (V rms): 120	Default Normal Mode (ac):	Voltage Independent
	Test Input Voltage (V rms):	120

Test Input Frequency (Hz):	60
Test Output Voltage (V):	120
Test Output Frequency (Hz):	60
Total Input Power in W at 0% Load Min Config Lowest Dependency (ac):	3.104
Efficiency at 25% Load Min Config Lowest Dependency (ac):	98.5
Efficiency at 50% Load Min Config Lowest Dependency (ac):	99.0
Efficiency at 75% Load Min Config Lowest Dependency (ac):	99.0
Efficiency at 100% Load Min Config Lowest Dependency (ac):	99.0
Weighted Efficiency Calc Min Config Lowest Dependency:	99.1
Efficiency (%):	99.1
Modular UPS Module Tested Model Number:	N/A
Energy Storage Mechanism:	Battery
Energy Storage System Technology:	Valve Regulated Lead-acid Battery
Energy Storage System Configuration:	Integral
Energy Storage System Removable to Another Room:	No
Energy Storage System Runtime at 100% Load (min.):	4
Energy Storage System Runtime at 50% Load (min.):	14
Energy Storage System Warranty (yrs):	3
Energy Storage System Information URL:	http://www.apc.com/shop/us/en/products/P-APCRBC163
Battery Recycling URL:	http://www.apc.com/us/en/who-we-are/sustainability/recycling-options.jsp
Network Connections Available:	USB Port
Communication Protocols:	Other
Communication Protocol Other:	USB Power Summary
Manufacturer Take Back Program:	Yes
Manufacturer Take Back Program URL:	http://www.apc.com/us/en/who-we-are/sustainability/recycling-options.jsp
Model Web Page URL:	http://www.apc.com/shop/us/en/products/P-BR1500MS2
Test Method Guidelines:	http://www.apc.com/us/en/who-we-are/sustainability/
Date Available on Market:	2020-08-30
Date Certified:	2020-08-30
Markets:	United States, Canada
ENERGY STAR Certified:	Yes

Additional Model Information

Back UPS PRO 1500VA Sinewave 10 outlets 2 USB Charging ports AVR LCD Factory Serviced, BR1500MS2W,; Std Exch B ack UPS PRO 1500VA Sinewave 10 outlets 2 USB Charging ports AVR LCD, BR1500MS2Q,

UPC Codes 731304426103

Captured On: 06/17/2025