

Tripp Lite - AG-0552 : AG-0552

BRANCH STAR Unique ID: 2368881 Brand Name: Tripp Lite Model Name: AG-0552 Model Number: AG-0552 Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: AC-0552 Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Line Interactive Topology (ac): Line Interactive (VI) Application: Data Center, Consumer, Commercial Rated Input Voltage (V rms): 120-120 Rated Input Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rated Output Frequency (Hz): 60-60 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 305 Width (mm): 105 Total Number of Outlets: 12 Number of Battery Backup and Surge Protected Outlets: 12 Number of Surge Protected Only Outlets: 6 Normal Mode(s) Input Dependency Characteristic (ac): Mo Mumber of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V) rms): 120 Test Input Voltage (V) rms): 120 Test Input Voltage (V rms): 120 Test Input Voltage (V): 120	Specifications	
Brand Name: Tripp Lite Model Name: AG-0552 Model Number: AG-0552 Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: AG-0552 Active Output Power Rating Minimum Configuration (W): 340 Apparent Output Power Rating Minimum Configuration (VA): 550 Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Data Center, Consumer, Commercial Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (rmm): 105 Obeth (rmm): 105 Total Number of Outlets: 12 Number of Battery Backup and Surge protected Only Outlets: 6 Nomal Mode(s) Input Dependency Characteristic (ac): No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (•	2368881
Model Name: AG-0552 Model Number: AG-0552 Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: AG-0552 Active Output Power Rating Minimum Configuration (W): 340 Apparent Output Power Rating Minimum Configuration (W): 550 Apparent Output Power Rating Minimum Configuration (W): Line Interactive Topology (ac): Line Interactive (VI) Apparent Output Power Rating Minimum Configuration (W): Data Center, Consumer, Commercial Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 60-60 Rated Output Frequency (Hz): 60-60 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 305 Width (mm): 190 Depth (mm): 105 Total Number of Outlets: 12 Number of Battery Backup and Surge Protected Only Outlets: 6 Nommal Mode(s) Input Dependency Characteristic (ac): No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent	•	
Model Number: AG-0552 Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: AG-0552 Active Output Power Rating Minimum Configuration (W): 340 Apparent Output Power Rating Minimum Configuration (VA): 550 Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Data Center,Consumer,Commercial Rated Input Voltage (V rms): 120-120 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 305 Width (mm): 190 Depth (mm): 105 Total Number of Outlets: 12 Number of Battery Backup and Surge Protected Outlets: 6 Number of Surge Protected Only Outlets: 6 Normal Mode(s) Input Dependency Characteristic (ac): No Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): <th></th> <th></th>		
Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: AG-0552 Active Output Power Rating Minimum Configuration (W): 340 Apparent Output Power Rating Minimum Configuration (VA): 550 Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: 120-120 Rated Input Voltage (V rms): 120-120 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 305 Width (mm): 190 Depth (mm): 105 Total Number of Outlets: 12 Number of Battery Backup and Surge Protected Outlets: 6 Number of Surge Protected Only Outlets: 6 Normal Mode(s) Input Dependency Characteristic (ac): No Nounber of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Voltage (V): 120		
Minimum Configuration Tested Model Number: Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Data Center,Consumer,Commercial Rated Input Voltage (V rms): Rated Input Voltage (V rms): Rated Input Frequency (Hz): Rated Output Voltage (V): Rate Output		
Number: Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Data Center,Consumer,Commercial Rated Input Voltage (V rms): Rated Input Voltage (V rms): Rated Input Voltage (V): Rated Output Frequency (Hz): Robert Momitable: No Height (mm): 190 Depth (mm): 190 Depth (mm): 105 Total Number of Outlets: 12 Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: Aumber of Surge Protected Only Outlets: Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120		
Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Data Center, Consumer, Commercial Rated Input Voltage (V rms): Rated Input Voltage (V rms): Rated Input Voltage (V rms): Rated Output Voltage (V): Rated Output Voltage (V): Rated Output Voltage (V): Rated Output Frequency (Hz): Rock Mountable: No Height (mm): Depth (mm): Depth (mm): Depth (mm): Depth (mm): Depth G Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: Number of Surge Protected Only Outlets: Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Default Normal Modes: Default Normal Mode (ac): Voltage Independent Test Input Voltage (V): 120 Test Input Voltage (V): 120 Test Output Voltage (V): 120 Test Output Voltage (V): 120	_	AG-U552
Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: Application: Data Center,Consumer,Commercial Rated Input Voltage (V rms): Rated Input Frequency (Hz): Application: Defact Output Voltage (V): Rated Output Voltage (V): Rated Output Voltage (V): Rated Output Frequency (Hz): Application: Application: Brated Output Frequency (Hz): Application: Brated Output Frequency (Hz): Application: Application: Brated Output Frequency (Hz): Application: Brated Output Frequency (Hz): Application: Application: Brated Output Frequency (Hz): Brated Output Frequ		340
Topology and Product Type Combined:ac Line Interactive (VI)Application:Data Center, Consumer, CommercialRated Input Voltage (V rms):120-120Rated Output Frequency (Hz):60-60Rated Output Voltage (V):120-120Rated Output Frequency (Hz):60-60Rack Mountable:NoHeight (mm):305Width (mm):190Depth (mm):105Total Number of Outlets:12Number of Battery Backup and Surge Protected Outlets:6Number of Surge Protected Only Outlets:6Normal Mode(s) Input Dependency Characteristic (ac):Voltage IndependentModular UPS:NoNumber of Normal Modes:Single-normal-modeDefault Normal Mode (ac):Voltage IndependentTest Input Voltage (V rms):120Test Input Voltage (V):120		550
Application: Data Center,Consumer,Commercial Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 305 Width (mm): 190 Depth (mm): 105 Total Number of Outlets: 12 Number of Battery Backup and Surge Protected Outlets: 12 Number of Surge Protected Only Outlets: 6 Normal Mode(s) Input Dependency Characteristic (ac): No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120	Topology (ac):	Line Interactive
Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 305 Width (mm): 190 Depth (mm): 105 Total Number of Outlets: 12 Number of Battery Backup and Surge Protected Outlets: 6 Normal Mode(s) Input Dependency Characteristic (ac): Voltage Independent Number of Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Voltage (V): 120 Test Output Voltage (V): 120	Topology and Product Type Combined:	ac Line Interactive (VI)
Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 305 Width (mm): 190 Depth (mm): 105 Total Number of Outlets: 12 Number of Battery Backup and Surge Protected Outlets: 6 Normal Mode(s) Input Dependency Voltage Independent Voltage (Ac): No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Voltage (V): 120	Application:	Data Center,Consumer,Commercial
Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 305 Width (mm): 190 Depth (mm): 105 Total Number of Outlets: 12 Number of Battery Backup and Surge Protected Outlets: 6 Normal Mode(s) Input Dependency Characteristic (ac): Voltage Independent Mumber of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Voltage (V): 120	Rated Input Voltage (V rms):	120-120
Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 305 Width (mm): 190 Depth (mm): 105 Total Number of Outlets: 12 Number of Battery Backup and Surge Protected Outlets: 6 Normal Mode(s) Input Dependency Characteristic (ac): No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Voltage (V): 120	Rated Input Frequency (Hz):	60-60
Rack Mountable: Height (mm): 305 Width (mm): 190 Depth (mm): 105 Total Number of Outlets: 12 Number of Battery Backup and Surge Protected Only Outlets: 6 Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Voltage (V): 120	Rated Output Voltage (V):	120-120
Height (mm): 305 Width (mm): 190 Depth (mm): 105 Total Number of Outlets: 12 Number of Battery Backup and Surge Protected Outlets: 6 Normal Mode(s) Input Dependency Characteristic (ac): No Number of Normal Modes: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Voltage (V): 120	Rated Output Frequency (Hz):	60-60
Width (mm):190Depth (mm):105Total Number of Outlets:12Number of Battery Backup and Surge Protected Outlets:6Number of Surge Protected Only Outlets:6Normal Mode(s) Input Dependency Characteristic (ac):Voltage IndependentModular UPS:NoNumber of Normal Modes:Single-normal-modeDefault Normal Mode (ac):Voltage IndependentTest Input Voltage (V rms):120Test Input Frequency (Hz):60Test Output Voltage (V):120	Rack Mountable:	No
Depth (mm): 105 Total Number of Outlets: 12 Number of Battery Backup and Surge Protected Outlets: 6 Normal Mode(s) Input Dependency Characteristic (ac): Voltage Independent Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Output Voltage (V): 120	Height (mm):	305
Total Number of Outlets: Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Output Voltage (V): 120	Width (mm):	190
Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Output Voltage (V): 120	Depth (mm):	105
Number of Surge Protected Only Outlets: Normal Mode(s) Input Dependency Characteristic (ae): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Voltage Independent Test Input Voltage (V rms): 120 Test Output Voltage (V): 120	Total Number of Outlets:	12
Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120		6
Characteristic (ac):NoModular UPS:NoNumber of Normal Modes:Single-normal-modeDefault Normal Mode (ac):Voltage IndependentTest Input Voltage (V rms):120Test Input Frequency (Hz):60Test Output Voltage (V):120	Number of Surge Protected Only Outlets:	6
Number of Normal Modes: Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120		Voltage Independent
Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120	Modular UPS:	No
Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120	Number of Normal Modes:	Single-normal-mode
Test Input Frequency (Hz): 60 Test Output Voltage (V): 120	Default Normal Mode (ac):	Voltage Independent
Test Output Voltage (V): 120	Test Input Voltage (V rms):	120
	Test Input Frequency (Hz):	60
Test Output Frequency (Hz): 60	Test Output Voltage (V):	120
	Test Output Frequency (Hz):	60

Efficiency at 25% Load Min Config Lowest Dependency (ac):	97.2
Efficiency at 50% Load Min Config Lowest Dependency (ac):	98.4
Efficiency at 75% Load Min Config Lowest Dependency (ac):	98.5
Efficiency at 100% Load Min Config Lowest Dependency (ac):	98.5
Weighted Efficiency Calc Min Config Lowest Dependency:	98.5
Efficiency (%):	98.5
Modular UPS Module Tested Model Number:	N/A
Energy Storage Mechanism:	Battery
Energy Storage System Technology:	Valve Regulated Lead-acid Battery
Energy Storage System Configuration:	Integral
Energy Storage System Removable to Another Room:	N/A
Energy Storage System Runtime at 100% Load (min.):	3
Energy Storage System Runtime at 50% Load (min.):	10
Energy Storage System Warranty (yrs):	1
Energy Storage System Information URL:	http://www.tripplite.com
Battery Recycling URL:	http://www.tripplite.com/en/support/recycling-program.cfm
Network Connections Available:	USB Port,Ethernet
Communication Protocols:	None
Manufacturer Take Back Program:	Yes
Manufacturer Take Back Program URL:	http://www.tripplite.com/en/support/recycling-program.cfm
Model Web Page URL:	http://www.tripplite.com
Test Method Guidelines:	N/A
Date Available on Market:	2021-02-06
Date Certified:	2020-10-29
Markets:	United States, Canada
ENERGY STAR Certified:	Yes

Captured On: 05/02/2025