

Schneider Electric - Galaxy VS 120kW 480V without Batteries, Start-up 5x8 : GVSUPS120KGS

Specifications

BRRGY STAR Unique D:203506Brad Name:Galva Cla Cla Cla Cla Cla Cla Cla Cla Cla Cl	•	
Model Name:Galaxy VS 120kW 480V without Batteries, Start-up 5x8Model Number:GVSUPS120KGSPower Conversion Mechanism:StaticMinimum Configuration Tested Model Number:CVSUPS120KGSActive Output Power Rating Minimum Configuration (VA):12000Apparent Output Power Rating Minimum Configuration (VA):12000Apport Output Power Rating Minimum Configuration (VA):Nulti-Mode Double ConversionAppleatingMulti-Mode Double ConversionApploatingActive Output Power Rating Minimum Configuration (VA):ApploatingMulti-Mode Double ConversionApploatingBata CenterRated Input Voltage (V rms):60-60Rated Noutput Frequency (Hz):60-60Rated Output Voltage (V):480-480Rated Noutpatel:NoHeight (mm):521Soutpate:Soutpate Soutpate	ENERGY STAR Unique ID:	2375506
Model Number:GVSUPS120KGSPower Conversion Mechanism:StaticMinimum Configuration Tested Model Number:GVSUPS120KGSActive Output Power Rating Minimum Configuration (W):120000Apparent Output Power Rating Minimum Configuration (VA):120000Topology (ac):Multi-Mode Double ConversionTopology (ac):Multi-Mode Double ConversionApplication:Data CenterRated Input Voltage (V rms):480-480Rated Input Voltage (V):480-480Rated Output Frequency (Hz):60-60Rated Output Frequency (Hz):60-60Rated Numble:NoHeight (rmm):521Depth (rmm):521Normal Mode(s) Input Dependency Characteristic (ac):NoNotage and Frequency Independenty Voltage and Frequency Dependent Characteristic (ac):NoNotage and Frequency Independenty Characteristic (ac):NoNotage and Frequency Independent Characteristic (ac):NoStatistic Ansame Characteristic (ac):NoNotage and Frequency Independent Characteristic (ac):NoStatistic Application:480Statistic Application:NoStatistic Application:NoStatistic Application:NoStatistic Application:NoStatistic Application:NoStatistic Application:NoStatistic Application:NoStatistic Application:NoStatistic Application:NoStatistic Application:No	Brand Name:	Schneider Electric
Power Conversion Mechanism:StaticMinimum Configuration Tested Model Number:GVSUPS120KGSActive Output Power Rating Minimum Configuration (W):120000Apparent Output Power Rating Minimum Configuration (VA):120000Topology (ac):Multi-Mode Double ConversionTopology (ac):Multi-Mode Double ConversionApplication:Data CenterRated Input Voltage (Vrms):480-480Rated Input Frequency (Hz):60-60Rated Output Frequency (Hz):60-60Rated Nuthalle:NoRated Nuthalle:NoRated Nuthalle:S1Mithing:521Depth (rmn):521NomerNoNuthalerNoNuthalerNoNuthalerNoNuthalerNoNuthalerNoNuthalerS1NuthalerNoNuthaler <t< th=""><th>Model Name:</th><th>Galaxy VS 120kW 480V without Batteries, Start-up 5x8</th></t<>	Model Name:	Galaxy VS 120kW 480V without Batteries, Start-up 5x8
Number:GVSUPS120KGSActive Output Power Rating Minimum Configuration (W):20000Apparent Output Power Rating Minimum configuration (WA):20000Apparent Output Power Rating Minimum Configuration (VA):20000Topolog (ac):Multi-Mode Double ConversionTopology and Product Type Combined:ac • OtherApplication:Data CenterRated Input Voltage (Vrms):480-480Rated Input Frequency (Hz):60-60Rated Output Frequency (Hz):60-60Rated Output Frequency (Hz):60-60Rated Nountable:NoHeight (mm):521Depth (mm):521Nomal Mode(s) Input Dependency Characeristic (ac):NoMulti-Pormal-Mode(sc):NoNumber of Normal Mode (ac):NoDefault Normal Mode (ac):Voltage and Frequency IndependentDefault Normal Mode (ac):SilaTest Input Voltage (V):480Test Input Voltage (V):60Test Input Voltage (V):54.8	Model Number:	GVSUPS120KGS
Number:Image:Active Output Power Rating Minimum Configuration (W):20000Apparent Output Power Rating Minimum configuration (WA):20000Topolog (ac):Multi-Mode Double ConversionTopology and Product Type Combined:ac • OtherApplication:Data CenterRated Input Voltage (Vrms):480-480Rated Input Frequency (Hz):60-60Rated Output Frequency (Hz):60-60Rated Output Frequency (Hz):60-60Rated Nountable:NoHeight (mm):521Depth (mm):521Nomal Mode(s) Input PoependencyNoMulti-Pornal-Mode(shiput Dependency)Voltage and Frequency Independent, Voltage Independent, Volta	Power Conversion Mechanism:	Static
Configuration (W):IApparent Output Power Rating Minimum Configuration (VA):120000Topology (ac):Multi-Mode Double ConversionTopology and Product Type Combined:ac - OtherApplication:Data CenterRated Input Voltage (Vrms):480-480Rated Input Frequency (Hz):60-60Rated Output Voltage (V):480-480Rated Output Frequency (Hz):60-60Rated Output Frequency (Hz):50-60Rated Noutable:NoHeight (mm):1485Dother847Nomal Mode(s) Input Dependency Characteristic (ac):NoMulti-Inoreal Mode(s) Input Dependency Characteristic (ac):NoModular UPS:NoNomal Mode (ac):Voltage and Frequency Independent, Voltage and Frequency IndependentDefault Normal Mode (ac):Voltage and Frequency IndependentTots Input Voltage (V):480Application:Singa and Frequency IndependentTots Input Voltage (Vrms):Singa and Frequency IndependentTots Input Voltage (Vrms):400Application Mode (ac):Singa and Frequency IndependentTots Input Voltage (Vrms):Singa and Frequency IndependentTots Untput V	-	GVSUPS120KGS
Configuration (VA):Multi-Mode Double ConversionTopology (ac):Ac - OtherApplication:Data CenterRated Input Voltage (Vrms):480-480Rated Input Frequency (Hz):60-60Rated Output Voltage (V):480-480Rated Output Frequency (Hz):60-60Rated Output Frequency (Hz):60-60Rated Output Frequency (Hz):521Popth (mm):521Popth (mm):847Normal Mode(s) Input Dependency Characteristic (ac):Voltage and Frequency Independent,Voltage and Frequency Dependent Voltage and Frequency Independent,Voltage and Frequency DependentModular UPS:NoPofault Normal Mode (ac):Voltage and Frequency IndependentTots Input Voltage (Vrms):480Test Input Voltage (V):60Test Unput Voltage (V):60Test Output Voltage (V):60Test Unput Frequency (Hz):60Test Output Voltage (V):551.8		120000
Topology and Product Type Combined:ac - OtherApplication:Data CenterRated Input Voltage (V rms):480-480Rated Input Frequency (Hz):60-60Rated Output Voltage (V):480-480Rated Output Frequency (Hz):60-60Rack Mountable:NoHeight (mm):1485Vidth (mm):521Depth (mm):847Normal Mode(s) Input Dependency (Haz):NoNormal Mode(s) Input Dependency (Haz):NoNormal Mode(s) Input Dependency (Haz):NoState Input Frequency (Hz):NoState Input Frequency (Hz):NoState Input Voltage (V rms):SaAnamel Mode(ac):NoState Input Voltage (V):480Test Input Frequency (Hz):60Test Output Voltage (V):480Test Output Voltage (V):480Test Output Voltage (V):554.8		120000
Application:Data CenterRated Input Voltage (V rms):480-480Rated Input Frequency (Hz):60-60Rated Output Voltage (V):480-480Rated Output Frequency (Hz):60-60Rack Mountable:NoHeight (mm):1485Width (mm):521Depth (mm):847Normal Mode(s) Input Dependency Characteristic (ac):NoModular UPS:NoNumber of Normal Modes:NoDefault Normal Mode (ac):Voltage and Frequency Independent, Voltage and Frequency DependentDefault Normal Mode (ac):Voltage and Frequency IndependentTest Input Frequency (Hz):60Test Output Voltage (V):480Test Output Voltage (V):480Test Output Voltage (V):554.8	Topology (ac):	Multi-Mode Double Conversion
Art480-480Rated Input Voltage (V rms):60-60Rated Output Voltage (V):480-480Rated Output Voltage (V):60-60Rated Output Frequency (Hz):60-60Rack Mountable:NoHeight (mm):1485Width (mm):521Depth (mm):847Normal Mode(s) Input Dependency Characteristic (ac):Voltage and Frequency Independent,Voltage and Frequency Dependent Voltage and Frequency Independent,Voltage and Frequency Independent, NoNumber of Normal Mode (ac):Voltage and Frequency IndependentDefault Normal Mode (ac):Voltage and Frequency IndependentTest Input Frequency (Hz):60Test Output Voltage (V):480Test Output Voltage (V):60Test Output Frequency (Hz):60Test Output Frequency	Topology and Product Type Combined:	ac - Other
Rated Input Frequency (Hz):60-60Rated Output Voltage (V):480-480Rated Output Frequency (Hz):60-60Rack Mountable:NoHeight (mm):1485Width (mm):521Depth (mm):847Normal Mode(s) Input Dependency Characteristic (ac):Voltage and Frequency Independent, Voltage and Frequency Dependent Voltage and Frequency Independent, Voltage and Frequency DependentNoNoNumber of Normal Modes:Voltage and Frequency IndependentDefault Normal Mode (ac):Voltage and Frequency IndependentTest Input Voltage (Vrms):480Test Input Frequency (Hz):60Test Output Frequency (Hz):60Test Output Frequency (Hz):551.8	Application:	Data Center
Rated Output Voltage (V):480-480Rated Output Frequency (Hz):60-60Rack Mountable:NoHeight (mm):1485Width (mm):521Depth (mm):847Normal Mode(s) Input Dependency Characteristic (ac):Voltage and Frequency Independent,Voltage and Frequency DependentModular UPS:NoNumber of Normal Modes:Multiple-normal-modeDefault Normal Mode (ac):480Test Input Voltage (V rms):480Test Input Frequency (Hz):60Test Output Voltage (V):480Test Output Voltage (V):554.8	Rated Input Voltage (V rms):	480-480
Rated Output Frequency (Hz):60-60Rack Mountable:NoHeight (mm):1485Width (mm):521Depth (mm):847Normal Mode(s) Input Dependency Characteristic (ac):Voltage and Frequency Independent,Voltage and Frequency Dependent Voltage and Frequency Independent,Voltage and Frequency DependentModular UPS:NoMuthiple-normal-modeVoltage and Frequency Independent,Voltage and Frequency DependentVoltage of Normal Mode(ac):NoTest Input Voltage (Vrms):480Test Input Frequency (Hz):60Test Output Frequency (Hz):60Test Output Frequency (Hz):554.8	Rated Input Frequency (Hz):	60-60
Rack Mountable:NoHeight (mm):1485Width (mm):521Depth (mm):847Normal Mode(s) Input Dependency Characteristic (ac):Voltage and Frequency Independent, Voltage and Frequency DependentModular UPS:NoNumber of Normal Modes:Multiple-normal-modeDefault Normal Mode (ac):Voltage and Frequency IndependentTest Input Voltage (Vrms):480Test Input Frequency (Hz):60Test Output Frequency (Hz):60Total Input Power in W at 0% Load Min Config554.8	Rated Output Voltage (V):	480-480
Height (mm):1485Width (mm):521Depth (mm):847Normal Mode(s) Input Dependency Characteristic (ac):Voltage and Frequency Independent, Voltage and Frequency DependentModular UPS:NoNumber of Normal Modes:Multiple-normal-modeDefault Normal Mode (ac):Voltage and Frequency IndependentTest Input Voltage (Vrms):480Test Input Frequency (Hz):60Test Output Frequency (Hz):60Test Output Frequency (Hz):554.8	Rated Output Frequency (Hz):	60-60
Width (mm):521Depth (mm):847Normal Mode(s) Input Dependency Characteristic (ac):Voltage and Frequency Independent, Voltage and Frequency DependentModular UPS:NoNumber of Normal Modes:Multiple-normal-modeDefault Normal Mode (ac):Voltage and Frequency IndependentTest Input Voltage (V rms):480Test Input Frequency (Hz):60Test Output Voltage (V):480Test Output Voltage (V):554.8	Rack Mountable:	No
Depth (mm):847Dormal Mode(s) Input Dependency Characteristic (ac):Voltage and Frequency Independent, Voltage and Frequency DependentModular UPS:NoNumber of Normal Modes:Multiple-normal-modeDefault Normal Mode (ac):Voltage and Frequency IndependentTest Input Voltage (Vrms):480Test Input Frequency (Hz):60Test Output Voltage (V):480Test Output Frequency (Hz):60Test Output Frequency (Hz):554.8	Height (mm):	1485
Normal Mode(s) Input Dependency Characteristic (ac):Voltage and Frequency Independent, Voltage and Frequency DependentModular UPS:NoNumber of Normal Modes:Multiple-normal-modeDefault Normal Mode (ac):Voltage and Frequency IndependentTest Input Voltage (Vrms):480Test Input Frequency (Hz):60Test Output Voltage (V):480Test Output Voltage (V):50Test Output Frequency (Hz):60Test Output Frequency (Hz):60	Width (mm):	521
Characteristic (ac):Image: Characteristic (ac):Modular UPS:NoNumber of Normal Modes:Multiple-normal-modeDefault Normal Mode (ac):Voltage and Frequency IndependentTest Input Voltage (V rms):480Test Input Frequency (Hz):60Test Output Voltage (V):480Test Output Voltage (V):60Test Output Frequency (Hz):60Test Output Frequency (Hz):554.8	Depth (mm):	847
Number of Normal Modes:Multiple-normal-modeDefault Normal Mode (ac):Voltage and Frequency IndependentTest Input Voltage (V rms):480Test Input Frequency (Hz):60Test Output Voltage (V):480Test Output Voltage (V):60Test Output Frequency (Hz):60Test Output Frequency (Hz):60Test Output Frequency (Hz):60Stal Input Power in W at 0% Load Min Config554.8		Voltage and Frequency Independent, Voltage and Frequency Dependent
Default Normal Mode (ac):Voltage and Frequency IndependentTest Input Voltage (V rms):480Test Input Frequency (Hz):60Test Output Voltage (V):480Test Output Voltage (V):60Test Output Frequency (Hz):60Total Input Power in W at 0% Load Min Config554.8	Modular UPS:	No
Test Input Voltage (V rms):480Test Input Frequency (Hz):60Test Output Voltage (V):480Test Output Frequency (Hz):60Total Input Power in W at 0% Load Min Config554.8	Number of Normal Modes:	Multiple-normal-mode
Test Input Frequency (Hz):60Test Output Voltage (V):480Test Output Frequency (Hz):60Total Input Power in W at 0% Load Min Config554.8	Default Normal Mode (ac):	Voltage and Frequency Independent
Test Output Voltage (V):480Test Output Frequency (Hz):60Total Input Power in W at 0% Load Min Config554.8	Test Input Voltage (V rms):	480
Test Output Frequency (Hz): 60 Total Input Power in W at 0% Load Min Config 554.8	Test Input Frequency (Hz):	60
Total Input Power in W at 0% Load Min Config 554.8	Test Output Voltage (V):	480
•	Test Output Frequency (Hz):	60
		554.8

Total Input Power in W at 0% Load Min Config Highest Dependency (ac):	323.3
Efficiency at 25% Load Min Config Lowest Dependency (ac):	96.3
Efficiency at 25% Load Min Config Highest Dependency (ac):	98.7
Efficiency at 50% Load Min Config Lowest Dependency (ac):	97.1
Efficiency at 50% Load Min Config Highest Dependency (ac):	99.2
Efficiency at 75% Load Min Config Lowest Dependency (ac):	97.3
Efficiency at 75% Load Min Config Highest Dependency (ac):	99.3
Efficiency at 100% Load Min Config Lowest Dependency (ac):	97.2
Efficiency at 100% Load Min Config Highest Dependency (ac):	99.4
Weighted Efficiency Calc Min Config Lowest Dependency:	97.0
Weighted Efficiency Calc Min Config Highest Dependency:	99.1
Minimum Configuration Input Power Factor Highest-Input Dependency:	0.99
Efficiency (%):	97
Modular UPS Module Tested Model Number:	N/A
Energy Storage Mechanism:	Battery
Energy Storage System Technology:	Valve Regulated Lead-acid Battery
Energy Storage System Configuration:	Separate Enclosure
Energy Storage System Removable to Another Room:	Yes
Energy Storage System Runtime at 100% Load (min.):	N/A
Energy Storage System Runtime at 50% Load (min.):	N/A
Energy Storage System Warranty (yrs):	N/A
Energy Storage System Information URL:	N/A
Battery Recycling URL:	https://www.apc.com/us/en/who-we-are/sustainability/recycling- options.jsp
Network Connections Available:	Serial Port,Ethernet
Communication Protocols:	HTTP,HTTPS,Other,Modbus TCP,SNMP (v1, 2 or 3),Modbus RTU
Communication Protocol Other:	BACnet/IP
Manufacturer Take Back Program:	Yes
Manufacturer Take Back Program URL:	https://www.apc.com/us/en/who-we-are/sustainability/recycling- options.jsp
Model Web Page URL:	https://www.apc.com/shop/us/en/products/P-GVSUPS60KGS
Test Method Guidelines:	https://www.apc.com/us/en/who-we-are/sustainability/
Date Available on Market:	2021-03-01

2021-02-24

Markets:

United States, Canada

ENERGY STAR Certified:

Yes

Additional Model Information

Galaxy VS 120kW 480V without Batteries, GVSUPS120KG,

UPC Codes 731304418436

Captured On: 06/18/2025