



ENERGY STAR CERTIFIED

Uninterruptible Power Supplies

APC by Schneider Electric - APC Smart-UPS 1000VA Tower LCD 120V APC Smart-UPS 1000VA Tower LCD 120V with SmartConnect Port TAA-Compliant : SMT1000CUS

Specifications

| | |
|--|--|
| ENERGY STAR Unique ID: | 2377980 |
| Brand Name: | APC by Schneider Electric |
| Model Name: | APC Smart-UPS 1000VA Tower LCD 120V APC Smart-UPS 1000VA Tower LCD 120V with SmartConnect Port TAA-Compliant |
| Model Number: | SMT1000CUS |
| Power Conversion Mechanism: | Static |
| Minimum Configuration Tested Model Number: | SMT1000C |
| Active Output Power Rating Minimum Configuration (W): | 700 |
| Apparent Output Power Rating Minimum Configuration (VA): | 1000 |
| Topology (ac): | Line Interactive |
| Topology and Product Type Combined: | ac Line Interactive (VI) |
| Application: | Commercial |
| Rated Input Voltage (V rms): | 110-125 |
| Rated Input Frequency (Hz): | 50-60 |
| Rated Output Voltage (V): | 110-125 |
| Rated Output Frequency (Hz): | 50-60 |
| Rack Mountable: | No |
| Height (mm): | 219 |
| Width (mm): | 171 |
| Depth (mm): | 439 |
| Total Number of Outlets: | 8 |
| Number of Battery Backup and Surge Protected Outlets: | 8 |
| Number of Surge Protected Only Outlets: | 0 |
| Normal Mode(s) Input Dependency Characteristic (ac): | Voltage Independent |
| Modular UPS: | No |
| Number of Normal Modes: | Single-normal-mode |
| Default Normal Mode (ac): | Voltage Independent |
| Test Input Voltage (V rms): | 125 |

| | |
|---|---|
| Test Input Frequency (Hz): | 60 |
| Test Output Voltage (V): | 125 |
| Test Output Frequency (Hz): | 60 |
| Total Input Power in W at 0% Load Min Config Lowest Dependency (ac): | 3.56 |
| Efficiency at 25% Load Min Config Lowest Dependency (ac): | 97.9 |
| Efficiency at 50% Load Min Config Lowest Dependency (ac): | 98.8 |
| Efficiency at 75% Load Min Config Lowest Dependency (ac): | 99.0 |
| Efficiency at 100% Load Min Config Lowest Dependency (ac): | 99.0 |
| Weighted Efficiency Calc Min Config Lowest Dependency: | 98.9 |
| Efficiency (%): | 98.9 |
| Modular UPS Module Tested Model Number: | N/A |
| Energy Storage Mechanism: | Battery |
| Energy Storage System Technology: | Valve Regulated Lead-acid Battery |
| Energy Storage System Configuration: | Integral |
| Energy Storage System Removable to Another Room: | No |
| Energy Storage System Runtime at 100% Load (min.): | 5 |
| Energy Storage System Runtime at 50% Load (min.): | 19 |
| Energy Storage System Warranty (yrs): | 2 |
| Energy Storage System Information URL: | https://www.apc.com/shop/us/en/products/P-RBC6 |
| Battery Recycling URL: | https://www.apc.com/us/en/who-we-are/sustainability/recycling-options.jsp |
| Network Connections Available: | Serial Port,USB Port,Ethernet |
| Communication Protocols: | Other,Modbus TCP,Modbus RTU |
| Communication Protocol Other: | USB Power Summary, Micro-Link, Simple Signaling, SmartConnect |
| Manufacturer Take Back Program: | Yes |
| Manufacturer Take Back Program URL: | https://www.apc.com/us/en/who-we-are/sustainability/recycling-options.jsp |
| Model Web Page URL: | https://www.apc.com/shop/us/en/products/P-SMT1000CUS |
| Test Method Guidelines: | https://www.apc.com/us/en/who-we-are/sustainability/ |
| Date Available on Market: | 2021-07-16 |
| Date Certified: | 2019-04-10 |
| Markets: | United States |
| ENERGY STAR Certified: | Yes |

Additional Model Information

APC Smart-UPS 1000VA Tower LCD 120V with SmartConnect Port TAA-Compliant Factory Serviced,SMT1000CUSW;; Std Exch APC Smart-UPS 1000VA Tower LCD 120V with SmartConnect Port TAA-Compliant,SMT1000CUSQ,

Captured On:
06/17/2025