

## Tripp Lite - AG-030D : BC500

Specifications  ENERGY STAR Unique ID: 2384214  Brand Name: Tripp Lite  Model Name: AG-030D  Model Number: BC500  Power Conversion Mechanism: Static  Minimum Configuration Tested Model Number: AG-030D  Active Output Power Rating Minimum Configuration (W):  Apparent Output Power Rating Minimum Configuration (VA): 500	
Brand Name: Tripp Lite  Model Name: AG-030D  Model Number: BC500  Power Conversion Mechanism: Static  Minimum Configuration Tested Model Number: AG-030D  Active Output Power Rating Minimum Configuration (W):  Apparent Output Power Rating Minimum 500	
Model Name:  Model Number:  BC500  Power Conversion Mechanism:  Static  Minimum Configuration Tested Model Number:  Active Output Power Rating Minimum Configuration (W):  Apparent Output Power Rating Minimum 500	
Model Number:  Power Conversion Mechanism:  Static  Minimum Configuration Tested Model Number:  Active Output Power Rating Minimum Configuration (W):  Apparent Output Power Rating Minimum 500	
Power Conversion Mechanism: Static  Minimum Configuration Tested Model AG-030D  Number:  Active Output Power Rating Minimum Configuration (W):  Apparent Output Power Rating Minimum 500	
Minimum Configuration Tested Model Number:  Active Output Power Rating Minimum Configuration (W):  Apparent Output Power Rating Minimum 500	
Number:  Active Output Power Rating Minimum Configuration (W):  Apparent Output Power Rating Minimum 500	
Configuration (W):  Apparent Output Power Rating Minimum 500	
Topology (ac): Passive Standby	
<b>Topology and Product Type Combined:</b> Alternating Current (ac) - Offline (VFD)	
Application: Consumer,Commercial	
Rated Input Voltage (V rms): 185-120	
Rated Input Frequency (Hz): 50-60	
Rated Output Voltage (V): 120-120	
Rated Output Frequency (Hz): 50-60	
Rack Mountable: No	
Height (mm): 105	
<b>Width (mm):</b> 110	
<b>Depth (mm):</b> 185	
Total Number of Outlets: 8	
Number of Battery Backup and Surge 4 Protected Outlets:	
Number of Surge Protected Only Outlets: 4	
Normal Mode(s) Input Dependency Characteristic (ac):  Voltage and Frequency Dependent	
Modular UPS: No	
Number of Normal Modes: Single-normal-mode	
Default Normal Mode (ac): Voltage and Frequency Dependent	
Test Input Voltage (V rms): 120	
Test Input Frequency (Hz): 60	
Test Output Voltage (V): 120	
Test Output Frequency (Hz): 60	

Total Input Power in W at 0% Load Min Config Lowest Dependency (ac):	2.15
Efficiency at 25% Load Min Config Lowest Dependency (ac):	97.1
Efficiency at 50% Load Min Config Lowest Dependency (ac):	98.6
Efficiency at 75% Load Min Config Lowest Dependency (ac):	99.0
Efficiency at 100% Load Min Config Lowest Dependency (ac):	99.2
Weighted Efficiency Calc Min Config Lowest Dependency:	97.6
Efficiency (%):	97.6
Modular UPS Module Tested Model Number:	N/A
Energy Storage Mechanism:	Battery
Energy Storage System Technology:	Valve Regulated Lead-acid Battery
<b>Energy Storage System Configuration:</b>	Integral
Energy Storage System Removable to Another Room:	No
Energy Storage System Runtime at 100% Load (min.):	2
Energy Storage System Runtime at 50% Load (min.):	7
Energy Storage System Warranty (yrs):	3
Energy Storage System Information URL:	N/A
Battery Recycling URL:	http://www.tripplite.com/en/support/recycling-program.cfm
Network Connections Available:	None
Communication Protocols:	None
Manufacturer Take Back Program:	Yes
Manufacturer Take Back Program URL:	http://www.tripplite.com/en/support/recycling-program.cfm
Model Web Page URL:	https://www.tripplite.com/120v-500va-260w-standby-ups-8-outlets- nema-5-15r-5-15p-plug-5-ft-cord-desktop-wall-mount~bc500
Test Method Guidelines:	N/A
Date Available on Market:	2018-01-15
Date Certified:	2021-09-07
Markets:	United States, Canada
ENERGY STAR Certified:	Yes

**Captured On:** 05/01/2025