

## Tripp Lite - AG-052B: SMART1200PSGLCD

| Specifications   |                          |
|--|--------------------------|
| ENERGY STAR Unique ID:   | 2389342                  |
| Brand Name:  | Tripp Lite               |
| Model Name:  | AG-052B                  |
| Model Number:  | SMART1200PSGLCD          |
| Power Conversion Mechanism:  | Static                   |
| Minimum Configuration Tested Model Number:                           | N/A                      |
| Active Output Power Rating Minimum Configuration (W):                | 720                      |
| Apparent Output Power Rating Minimum Configuration (VA):             | 1200                     |
| Maximum Configuration Tested Model Number:                           | N/A                      |
| Topology (ac):   | Line Interactive         |
| Topology and Product Type Combined:                                  | ac Line Interactive (VI) |
| Application:   | Consumer                 |
| Rated Input Voltage (V rms):   | 430-120                  |
| Rated Input Frequency (Hz):  | 50-60                    |
| Rated Output Voltage (V):  | 120-120                  |
| Rated Output Frequency (Hz):   | 50-60                    |
| Rack Mountable:  | No                       |
| Height (mm):   | 280                      |
| Width (mm):  | 105                      |
| Depth (mm):  | 430                      |
| Normal Mode(s) Input Dependency Characteristic (ac):                 | Voltage Independent      |
| Modular UPS:   | No                       |
| Number of Normal Modes:  | Single-normal-mode       |
| Default Normal Mode (ac):  | Voltage Independent      |
| Test Input Voltage (V rms):  | 120                      |
| Test Input Frequency (Hz):   | 60                       |
| Test Output Voltage (V):   | 120                      |
| Test Output Frequency (Hz):  | 60                       |
| Total Input Power in W at 0% Load Min Config Lowest Dependency (ac): | 0.3                      |
|  |                          |

| Efficiency at 25% Load Min Config Lowest Dependency (ac):  | 99.8  |
|--|---|
| Efficiency at 50% Load Min Config Lowest Dependency (ac):  | 99.8  |
| Efficiency at 75% Load Min Config Lowest Dependency (ac):  | 99.7  |
| Efficiency at 100% Load Min Config Lowest Dependency (ac): | 99.4  |
| Weighted Efficiency Calc Min Config Lowest Dependency:     | 99.6  |
| Efficiency (%):  | 99.6  |
| Modular UPS Module Tested Model Number:                    | N/A   |
| Energy Storage Mechanism:                                  | Battery   |
| Energy Storage System Technology:                          | Valve Regulated Lead-acid Battery                         |
| <b>Energy Storage System Configuration:</b>                | Integral  |
| Energy Storage System Removable to Another Room:           | No  |
| Energy Storage System Runtime at 100% Load (min.):         | 3   |
| Energy Storage System Runtime at 50% Load (min.):          | 10  |
| Energy Storage System Warranty (yrs):                      | 3   |
| Energy Storage System Information URL:                     | N/A   |
| Network Connections Available:                             | USB Port  |
| Communication Protocols:                                   | None  |
| Manufacturer Take Back Program:                            | Yes   |
| Manufacturer Take Back Program URL:                        | http://www.tripplite.com/en/support/recycling-program.cfm |
| Model Web Page URL:  | N/A - Product not available to the market yet             |
| Test Method Guidelines:                                    | N/A   |
| Date Available on Market:                                  | 2022-01-31  |
| Date Certified:  | 2021-05-03  |
| Markets:   | United States, Canada                                     |
| <b>ENERGY STAR Certified:</b>                              | Yes   |

**Captured On:** 04/30/2025