

Vertiv, Liebert - ITA-40k00AL3302P00 : ITA-40k00AL3302P00

Characteristic (ac): Modular UPS: No Number of Normal Modes: Multiple-normal-mode Default Normal Mode (ac): Voltage and Frequency Independent Test Input Voltage (V rms): 415 Test Input Frequency (Hz): 60 Test Output Voltage (V): 415 Test Output Frequency (Hz): 60 Total Input Power in W at 0% Load Min Config		
Brand Name: Vertiv, Liebert Model Name: ITA-40k00AL3302P00 Model Number: ITA-40k00AL3302P00 Power Conversion Mechanism: Static Minimum Configuration Tested Model number: ITA-40k00AL3302C00 Active Output Power Rating Minimum configuration (W): 40000 Apparent Output Power Rating Minimum configuration (W): 40000 Apparent Output Power Rating Minimum configuration (VA): 50000 Topology (ac): Multi-Mode Double Conversion ac - Other Application: Data Center, Consumer, Commercial acade Input Voltage (V rms): 380-415 Rated Input Voltage (V rms): 380-415 Rated Output Voltage (V): 380-415 Rated Output Frequency (Hz): 50-60 Rack Mountable: Yes Height (mm): 130 Width (mm): 430 Depth (mm): 560 Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Nommal Mode(s) Input Dependency Characteristic (ac): Woltage and Frequency Independent, Voltage and Frequency Dependent Characteristic (ac): Woltage and Frequency Independent Characteristic (ac): Woltage and Frequency Independent Characteristic (ac): Woltage and Frequency Independent Characteristic (ac): Voltage and Frequency Independent Characteristic Inductive Characteristic (ac): Voltage and Frequency Independent Characteristic Inductive Characteristic C	Specifications	
Model Name: ITA-40k00AL3302P00 Model Number: ITA-40k00AL3302P00 Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: ITA-40k00AL3302C00 Active Output Power Rating Minimum Configuration (W): 40000 Apparent Output Power Rating Minimum Configuration (VA): 40000 Topology (ac): Multi-Mode Double Conversion Topology and Product Type Combined: ac - Other Application: Data Center, Consumer, Commercial Rated Input Voltage (V rms): 380-415 Rated Input Frequency (Hz): 50-60 Rated Output Voltage (V): 380-415 Rated Output Frequency (Hz): 50-60 Rack Mountable: Yes Height (mm): 130 Width (mm): 430 Depth (mm): Voltage and Frequency Independent, Voltage and Frequency Dependent Characteristic (ac): Modular UPS: No Nounteer of Normal Mode (ac): Voltage and Frequency Independent Cest Input Voltage (V rms): 415 Test Input Voltage (V): 415 Test Input Voltage (V): 415 <	ENERGY STAR Unique ID:	2397062
Model Number: ITA-40k00AL3302P00 Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: ITA-40k00AL3302C00 Active Output Power Rating Minimum Configuration (W): 40000 Apparent Output Power Rating Minimum Configuration (VA): Multi-Mode Double Conversion Topology (ac): Multi-Mode Double Conversion Topology and Product Type Combined: ac - Other Application: Data Center,Consumer,Commercial Rated Input Voltage (V rms): 380-415 Rated Input Frequency (Hz): 50-60 Rated Output Voltage (V): 380-415 Rated Output Frequency (Hz): 50-60 Rack Mountable: Yes Height (mm): 430 Width (mm): 430 Depth (mm): 560 Normal Mode(s) Input Dependency Characteristic (ac): No Modular UPs: No Modular UPs: No Modular UPs: No Modular UPs: Voltage and Frequency Independent Modular UPs: Voltage and Frequency Independent Test Input Voltage (V rms):	Brand Name:	Vertiv, Liebert
Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: Active Output Power Rating Minimum configuration (W): Apparent Output Power Rating Minimum configuration (VA): Topology (ac): Multi-Mode Double Conversion Topology and Product Type Combined: ac - Other Application: Data Center, Consumer, Commercial Rated Input Voltage (V rms): 380-415 Rated Input Voltage (V): 380-415 Rated Output Voltage (V): 380-415 Rated Output Frequency (Hz): 50-60 Rated Output Frequency (Hz): 50-60 Rack Mountable: Yes Height (mm): 130 Width (mm): 430 Depth (mm): 430 Depth (mm): 560 Normal Mode(s) Input Dependency Characteristic (ac): No Nouthand IUPS: No Number of Normal Modes: Multiple-normal-mode Default Normal Mode (ac): Voltage and Frequency Independent Test Input Frequency (Hz): 60 Test Output Voltage (V): 415 Test Output Frequency (Hz): 60 Total Input Power in W at 0% Load Min Config 202.24	Model Name:	ITA-40k00AL3302P00
Minimum Configuration Tested Model Number: Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Topology and Product Type Combined: Application: Rated Input Voltage (V rms): Rated Input Voltage (V): Rated Output Voltage (V): Rated Output Voltage (V): Rated Output Frequency (Hz): So-60 Rack Mountable: Height (mm): 430 Depth (mm): So60 Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Multiple-normal-mode Default Normal Mode (ac): Voltage and Frequency Independent Test Input Frequency (Hz): 60 Test Untput Voltage (V): 415 Test Output Frequency (Hz): 60 Total Input Power in W at 0% Load Min Config	Model Number:	ITA-40k00AL3302P00
Number: 40000 Active Output Power Rating Minimum Configuration (W): 40000 Apparent Output Power Rating Minimum Configuration (VA): 40000 Topology (ac): Multi-Mode Double Conversion Topology and Product Type Combined: ac - Other Application: Data Center, Consumer, Commercial Rated Input Voltage (V rms): 380-415 Rated Input Frequency (Hz): 50-60 Rated Output Voltage (V): 380-415 Rated Output Voltage (V): 380-415 Rated Output Voltage (V): 380-415 Rated Muntable: Yes Height (mm): 130 Width (mm): 430 Depth (mm): 560 Normal Mode(s) Input Dependency Characteristic (ac): Voltage and Frequency Independent, Voltage and Frequency Dependent Characteristic (ac): Voltage and Frequency Independent Default Normal Mode (ac): Voltage and Frequency Independent Test Input Voltage (V): 415 Test Output Voltage (V): 415 Test Output Frequency (Hz): 60 Total Input Power in W at 0 % Load Min Config	Power Conversion Mechanism:	Static
Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Topology and Product Type Combined: Application: Application: Bate Input Voltage (V rms): Bate Output Voltage (V): Bate Output Vol	_	ITA-40K00AL3302C00
Configuration (VA): Topology (ac): Multi-Mode Double Conversion ac - Other Application: Rated Input Voltage (V rms): Rated Input Frequency (Hz): Rated Output Voltage (V): Rated Output Voltage (V): Rated Output Frequency (Hz): Rated Output Frequency (Hz): Rated Mountable: Yes Height (mm): Width (mm): Depth (mm): Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Multiple-normal-mode Default Normal Mode (ac): Voltage and Frequency Independent Test Input Voltage (V): A15 Test Input Voltage (V): 415 Test Output Power in W at 0% Load Min Config 202.24		40000
Topology and Product Type Combined: Application: Rated Input Voltage (V rms): 380-415 Rated Input Frequency (Hz): 380-415 Rated Output Voltage (V): 380-415 Rated Output Frequency (Hz): 50-60 Rack Mountable: Yes Height (mm): 130 Width (mm): 430 Depth (mm): 560 Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Default Normal Mode (ac): Voltage and Frequency Independent Test Input Voltage (V): 415 Test Output Voltage (V): 415 Test Output Power in W at 0% Load Min Config 202.24		40000
Application: Data Center,Consumer,Commercial Rated Input Voltage (V rms): 380-415 Rated Input Frequency (Hz): 50-60 Rated Output Voltage (V): 380-415 Rated Output Frequency (Hz): 50-60 Rack Mountable: Yes Height (mm): 130 Width (mm): 430 Depth (mm): 560 Normal Mode(s) Input Dependency Characteristic (ac): No Modular UPS: No Number of Normal Modes: Multiple-normal-mode Default Normal Mode (ac): Voltage and Frequency Independent Test Input Voltage (V rms): 415 Test Output Voltage (V): 415 Test Output Frequency (Hz): 60 Total Input Power in W at 0% Load Min Config	Topology (ac):	Multi-Mode Double Conversion
Rated Input Voltage (V rms): 380-415 Rated Input Frequency (Hz): 50-60 Rated Output Voltage (V): 380-415 Rated Output Frequency (Hz): 50-60 Rack Mountable: Yes Height (mm): 130 Width (mm): 430 Depth (mm): 560 Normal Mode(s) Input Dependency Characteristic (ac): No Mumber of Normal Modes: Multiple-normal-mode Default Normal Mode (ac): Voltage and Frequency Independent Test Input Voltage (V rms): 415 Test Input Frequency (Hz): 60 Total Input Power in W at 0% Load Min Config	Topology and Product Type Combined:	ac - Other
Rated Input Frequency (Hz): 50-60 Rated Output Voltage (V): 380-415 Rated Output Frequency (Hz): 50-60 Rack Mountable: Yes Height (mm): 130 Width (mm): 430 Depth (mm): 560 Normal Mode(s) Input Dependency Characteristic (ac): No Modular UPS: No Number of Normal Modes: Multiple-normal-mode Default Normal Mode (ac): Voltage and Frequency Independent Test Input Voltage (V rms): 415 Test Input Frequency (Hz): 60 Test Output Voltage (V): 415 Test Output Power in W at 0% Load Min Config 202.24	Application:	Data Center,Consumer,Commercial
Rated Output Voltage (V): Rated Output Frequency (Hz): So-60 Rack Mountable: Yes Height (mm): 130 Width (mm): 430 Depth (mm): 560 Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Default Normal Mode (ac): Voltage and Frequency Independent Voltage and Frequency Dependent Wultiple-normal-mode Default Normal Mode (ac): Voltage and Frequency Independent Test Input Voltage (V rms): 415 Test Output Voltage (V): 415 Test Output Frequency (Hz): 60 Total Input Power in W at 0% Load Min Config	Rated Input Voltage (V rms):	380-415
Rated Output Frequency (Hz): 50-60 Rack Mountable: Yes Height (mm): 130 Width (mm): 430 Depth (mm): 560 Normal Mode(s) Input Dependency Characteristic (ac): No No Number of Normal Modes: Multiple-normal-mode Default Normal Mode (ac): Voltage and Frequency Independent Test Input Voltage (V rms): 415 Test Output Voltage (V): 415 Test Output Frequency (Hz): 60 Total Input Power in W at 0% Load Min Config 202.24	Rated Input Frequency (Hz):	50-60
Rack Mountable: Height (mm): 130 Width (mm): 430 Depth (mm): 560 Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Multiple-normal-mode Default Normal Mode (ac): Test Input Voltage (V rms): Test Input Frequency (Hz): 60 Test Output Voltage (V): 415 Test Output Frequency (Hz): 60 Total Input Power in W at 0% Load Min Config	Rated Output Voltage (V):	380-415
Height (mm): Width (mm): 430 Depth (mm): 560 Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Default Normal Mode (ac): Test Input Voltage (V rms): Test Output Voltage (V): Test Output Voltage (V): Test Output Frequency (Hz): 60 Total Input Power in W at 0% Load Min Config 202.24	Rated Output Frequency (Hz):	50-60
Width (mm): Depth (mm): S60 Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Default Normal Mode (ac): Test Input Voltage (V rms): Test Output Voltage (V): Test Output Frequency (Hz): Total Input Power in W at 0% Load Min Config 202.24	Rack Mountable:	Yes
Depth (mm): Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Multiple-normal-mode Default Normal Mode (ac): Voltage and Frequency Independent, Voltage and Frequency Dependent Voltage and Frequency Independent Test Input Voltage (V rms): 415 Test Output Voltage (V): 415 Test Output Frequency (Hz): 60 Total Input Power in W at 0% Load Min Config	Height (mm):	130
Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Multiple-normal-mode Default Normal Mode (ac): Voltage and Frequency Independent Test Input Voltage (V rms): 415 Test Input Frequency (Hz): 60 Test Output Voltage (V): 415 Test Output Frequency (Hz): 60 Total Input Power in W at 0% Load Min Config	Width (mm):	430
Characteristic (ac): Modular UPS: No Number of Normal Modes: Multiple-normal-mode Default Normal Mode (ac): Voltage and Frequency Independent Test Input Voltage (V rms): 415 Test Input Frequency (Hz): 60 Test Output Voltage (V): 415 Test Output Frequency (Hz): 60 Total Input Power in W at 0% Load Min Config	Depth (mm):	560
Number of Normal Modes: Default Normal Mode (ac): Voltage and Frequency Independent Test Input Voltage (V rms): 415 Test Input Frequency (Hz): 60 Test Output Voltage (V): 415 Test Output Frequency (Hz): 60 Total Input Power in W at 0% Load Min Config 202.24		Voltage and Frequency Independent, Voltage and Frequency Dependent
Default Normal Mode (ac): Voltage and Frequency Independent Test Input Voltage (V rms): 415 Test Input Frequency (Hz): 60 Test Output Voltage (V): 415 Test Output Frequency (Hz): 60 Total Input Power in W at 0% Load Min Config 202.24	Modular UPS:	No
Test Input Voltage (V rms): 415 Test Input Frequency (Hz): 60 Test Output Voltage (V): 415 Test Output Frequency (Hz): 60 Total Input Power in W at 0% Load Min Config 202.24	Number of Normal Modes:	Multiple-normal-mode
Test Input Frequency (Hz): 60 Test Output Voltage (V): 415 Test Output Frequency (Hz): 60 Total Input Power in W at 0% Load Min Config 202.24	Default Normal Mode (ac):	Voltage and Frequency Independent
Test Output Voltage (V): 415 Test Output Frequency (Hz): 60 Total Input Power in W at 0% Load Min Config 202.24	Test Input Voltage (V rms):	415
Test Output Frequency (Hz): Total Input Power in W at 0% Load Min Config 202.24	Test Input Frequency (Hz):	60
Total Input Power in W at 0% Load Min Config 202.24	Test Output Voltage (V):	415
	Test Output Frequency (Hz):	60
	Total Input Power in W at 0% Load Min Config Lowest Dependency (ac):	202.24

Total Input Power in W at 0% Load Min Config Highest Dependency (ac):	164.27
Efficiency at 25% Load Min Config Lowest Dependency (ac):	95.8
Efficiency at 25% Load Min Config Highest Dependency (ac):	99.4
Efficiency at 50% Load Min Config Lowest Dependency (ac):	96.4
Efficiency at 50% Load Min Config Highest Dependency (ac):	99.5
Efficiency at 75% Load Min Config Lowest Dependency (ac):	96.3
Efficiency at 75% Load Min Config Highest Dependency (ac):	99.5
Efficiency at 100% Load Min Config Lowest Dependency (ac):	96.0
Efficiency at 100% Load Min Config Highest Dependency (ac):	99.5
Weighted Efficiency Calc Min Config Lowest Dependency:	96.2
Weighted Efficiency Calc Min Config Highest Dependency:	99.5
Efficiency (%):	96.2
Modular UPS Module Tested Model Number:	N/A
Energy Storage Mechanism:	Battery
Energy Storage System Technology:	Valve Regulated Lead-acid Battery
Energy Storage System Configuration:	Separate Enclosure
Energy Storage System Removable to Another Room:	No
Energy Storage System Runtime at 100% Load (min.):	30
Energy Storage System Runtime at 50% Load (min.):	60
Energy Storage System Warranty (yrs):	1
Energy Storage System Information URL:	http://www.enersys.com/ http://www.eastpennunigy.com/
Network Connections Available:	USB Port,Ethernet
Communication Protocols:	Other
Manufacturer Take Back Program:	No
Model Web Page URL:	https://www.vertivco.com/en-us/products-catalog/critical-power/ uninterruptible-power-supplies-ups/
Test Method Guidelines:	N/A
Date Available on Market:	2022-07-01
Date Certified:	2022-05-27
Markets:	United States, Taiwan, Japan, Canada
ENERGY STAR Certified:	Yes