

Eaton Brand UPS - SUINT1500LCD2U: SUINT1500LCD2U

2405637
Eaton Brand UPS
SUINT1500LCD2U
SUINT1500LCD2U
Static
SUINT1500LCD2U
1500
1500
Double Conversion
ac - Double Conversion (VFI)
Data Center,Consumer,Commercial
200-240
50-60
200-240
50-60
Yes
2
86
440
450
Voltage and Frequency Independent
No
Single-normal-mode
Voltage and Frequency Independent
230
60
230
60
50.65

Efficiency at 25% Load Min Config Lowest Dependency (ac):	88.2
Efficiency at 50% Load Min Config Lowest Dependency (ac):	90.7
Efficiency at 75% Load Min Config Lowest Dependency (ac):	92.5
Efficiency at 100% Load Min Config Lowest Dependency (ac):	92.3
Weighted Efficiency Calc Min Config Lowest Dependency:	92.0
Efficiency (%):	92
Modular UPS Module Tested Model Number:	N/A
Energy Storage Mechanism:	Battery
Energy Storage System Technology:	Other
Energy Storage System Configuration:	Integral
Energy Storage System Removable to Another Room:	Yes
Energy Storage System Runtime at 100% Load (min.):	4
Energy Storage System Runtime at 50% Load (min.):	9
Energy Storage System Warranty (yrs):	2
Energy Storage System Information URL:	https://www.eaton.com/us/en-us.html
Battery Recycling URL:	www.eaton.com/recycling
Network Connections Available:	Other
Communication Protocols:	Other
Communication Protocol Other:	Eaton Shut
Manufacturer Take Back Program:	No
Manufacturer Take Back Program URL:	www.eaton.com/recycling
Model Web Page URL:	www.eaton.com
Test Method Guidelines:	N/A
Date Available on Market:	2024-11-12
Date Certified:	2022-12-12
	2022-12-12 United States, Switzerland, Taiwan, Japan, Canada

Additional Model Information

SUINT1500LCD2UAM,SUINT1500LCD2UAM,

Captured On: 06/18/2025