

Liebert - GXT5LI-10KMVRT4XN-P: GXT5LI-10KMVRT4XN-P

| Specifications | |
|--|-----------------------------------|
| ENERGY STAR Unique ID: | 2545406 |
| Brand Name: | Liebert |
| Model Name: | GXT5LI-10KMVRT4XN-P |
| Model Number: | GXT5LI-10KMVRT4XN-P |
| Power Conversion Mechanism: | Static |
| Minimum Configuration Tested Model Number: | 1 |
| Active Output Power Rating Minimum Configuration (W): | 10000 |
| Apparent Output Power Rating Minimum Configuration (VA): | 10000 |
| Topology (ac): | Multi-Mode Double Conversion |
| Topology and Product Type Combined: | ac - Other |
| Application: | Data Center,Commercial |
| Rated Input Voltage (V rms): | 120-240 |
| Rated Input Frequency (Hz): | 50-60 |
| Rated Output Voltage (V): | 120-240 |
| Rated Output Frequency (Hz): | 50-60 |
| Rack Mountable: | Yes |
| Height (mm): | 3 |
| Width (mm): | 17 |
| Depth (mm): | 37 |
| Normal Mode(s) Input Dependency Characteristic (ac): | Voltage and Frequency Independent |
| Modular UPS: | No |
| Number of Normal Modes: | Single-normal-mode |
| Default Normal Mode (ac): | Voltage and Frequency Independent |
| Test Input Voltage (V rms): | 120 |
| Test Input Frequency (Hz): | 60 |
| Test Output Voltage (V): | 120 |
| Test Output Frequency (Hz): | 60 |
| Total Input Power in W at 0% Load Min Config Lowest Dependency (ac): | 53.78 |
| Efficiency at 25% Load Min Config Lowest Dependency (ac): | 94.2 |

| Efficiency at 50% Load Min Config Lowest | 94.2 |
|--|---|
| Dependency (ac): | |
| Efficiency at 75% Load Min Config Lowest Dependency (ac): | 93.6 |
| Efficiency at 100% Load Min Config Lowest Dependency (ac): | 92.7 |
| Weighted Efficiency Calc Min Config Lowest Dependency: | 93.5 |
| Efficiency (%): | 93.5 |
| Modular UPS Module Tested Model Number: | N/A |
| Energy Storage Mechanism: | Battery |
| Energy Storage System Technology: | Lithium-ion Battery |
| Energy Storage System Configuration: | Integral |
| Energy Storage System Removable to Another Room: | N/A |
| Energy Storage System Runtime at 100% Load (min.): | 10 |
| Energy Storage System Runtime at 50% Load (min.): | 21 |
| Energy Storage System Warranty (yrs): | 5 |
| Energy Storage System Information URL: | www.vertiv.com/en-us/products-catalog/critical-power/uninterruptible-power-supplies-ups/gxt5li-10kmvrt4uxln/#/downloads |
| Network Connections Available: | Serial Port,Ethernet,USB Port |
| Communication Protocols: | HTTPS,SNMP (v1, 2 or 3) |
| Manufacturer Take Back Program: | No |
| Model Web Page URL: | www.vertiv.com/en-us/products-catalog/critical-power/uninterruptible-power-supplies-ups/gxt5li-10kmvrt4uxln/#/downloads |
| Test Method Guidelines: | www.vertiv.com/en-us/products-catalog/critical-power/uninterruptible-power-supplies-ups/gxt5li-10kmvrt4uxln/#/downloads |
| Date Available on Market: | 2023-05-01 |
| Date Certified: | 2023-06-29 |
| Markets: | United States, Taiwan, Japan, Canada |
| ENERGY STAR Certified: | Yes |

Additional Model Information

GXT5LI-10KRT4XN-P,GXT5LI-10KRT4XN-P,

Captured On: 05/01/2025