

## Liebert - Liebert EXS F5 30k series: 53\*30J\* \* \* \* \* \* \*

| Specifications   |  |
|--|--|
| ENERGY STAR Unique ID:   | 2668086  |
| Brand Name:  | Liebert  |
| Model Name:  | Liebert EXS F5 30k series  |
| Model Number:  | 53*30J* * * * * * *  |
| Power Conversion Mechanism:  | Static   |
| Minimum Configuration Tested Model Number:                           | 1  |
| Active Output Power Rating Minimum Configuration (W):                | 30000  |
| Apparent Output Power Rating Minimum Configuration (VA):             | 30000  |
| Maximum Configuration Tested Model Number:                           | 2  |
| Topology (ac):   | Multi-Mode Double Conversion                                       |
| Topology and Product Type Combined:                                  | ac - Other   |
| Application:   | Data Center,Consumer,Commercial                                    |
| Rated Input Voltage (V rms):   | 208-220  |
| Rated Input Frequency (Hz):  | 50-60  |
| Rated Output Voltage (V):  | 208-220  |
| Rated Output Frequency (Hz):   | 50-60  |
| Rack Mountable:  | No   |
| Height (mm):   | 2000   |
| Width (mm):  | 600  |
| Depth (mm):  | 1000   |
| Normal Mode(s) Input Dependency Characteristic (ac):                 | Voltage and Frequency Independent, Voltage and Frequency Dependent |
| Modular UPS:   | Yes  |
| Number of Normal Modes:  | Multiple-normal-mode   |
| Default Normal Mode (ac):  | Voltage and Frequency Dependent                                    |
| Test Input Voltage (V rms):  | 208  |
| Test Input Frequency (Hz):   | 60   |
| Test Output Voltage (V):   | 208  |
| Test Output Frequency (Hz):  | 60   |
| Total Input Power in W at 0% Load Min Config Lowest Dependency (ac): | 313.8  |

| Total Input Power in W at 0% Load Min Config Highest Dependency (ac): | 129.66   |
|---|--|
| Efficiency at 25% Load Min Config Lowest Dependency (ac):             | 92.8   |
| Efficiency at 25% Load Min Config Highest Dependency (ac):            | 97.7   |
| Efficiency at 50% Load Min Config Lowest Dependency (ac):             | 94.5   |
| Efficiency at 50% Load Min Config Highest Dependency (ac):            | 98.5   |
| Efficiency at 75% Load Min Config Lowest Dependency (ac):             | 94.2   |
| Efficiency at 75% Load Min Config Highest Dependency (ac):            | 98.8   |
| Efficiency at 100% Load Min Config Lowest Dependency (ac):            | 93.8   |
| Efficiency at 100% Load Min Config Highest Dependency (ac):           | 98.9   |
| Weighted Efficiency Calc Min Config Lowest Dependency:                | 94.0   |
| Weighted Efficiency Calc Min Config Highest Dependency:               | 98.4   |
| Minimum Configuration Input Power Factor Highest-Input Dependency:    | 0.99   |
| Efficiency (%):   | 95.1   |
| Modular UPS Module Tested Model Number:                               | N/A  |
| Energy Storage Mechanism:   | Battery  |
| Energy Storage System Technology:                                     | Valve Regulated Lead-acid Battery  |
| Energy Storage System Configuration:                                  | Integral   |
| Energy Storage System Removable to Another Room:                      | No   |
| Energy Storage System Runtime at 100% Load (min.):                    | 20   |
| Energy Storage System Runtime at 50% Load (min.):                     | 10   |
| Energy Storage System Warranty (yrs):                                 | 1  |
| Energy Storage System Information URL:                                | http://www.enersys.com,http://www.eastpennunigy.com  |
| Network Connections Available:  | USB Port   |
| Communication Protocols:  | Other  |
| Manufacturer Take Back Program:                                       | No   |
| Model Web Page URL:   | https://www.vertivco.com/en-us/products-catalog/critical-power/uninterruptible-power-supplies-ups/ |
| Test Method Guidelines:   | N/A  |
| Date Available on Market:   | 2023-09-15   |
| Date Certified:   | 2023-09-22   |
| Markets:  | United States, Canada  |
| ENERGY STAR Certified:  | Yes  |
|   |  |

**Captured On:** 06/18/2025