

APC by Schneider Electric - Smart-UPS 2200VA SmartConnect TAA : SMT2200CUS

Specifications ENERGY STAR Unique ID: 2698706 Brand Name: APC by Schneider Electric Model Name: Smart-UPS 2200VA SmartConnect TAA Model Number: SMT2200CUS Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: SMT2200C Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Commercial Rated Input Voltage (V rms): 110-125	
Brand Name: Model Name: Smart-UPS 2200VA SmartConnect TAA Model Number: SMT2200CUS Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Commercial	
Model Name: Model Number: SMT2200CUS Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: Commercial SMT2200C 2200 2200 2200 Commercial	
Model Number: Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Commercial	
Power Conversion Mechanism: Minimum Configuration Tested Model Number: Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Commercial	
Minimum Configuration Tested Model Number: Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Commercial	
Number: Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Commercial	
Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Commercial	
Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Commercial	
Topology and Product Type Combined: ac Line Interactive (VI) Application: Commercial	
Application: Commercial	
Rated Input Voltage (V rms): 110-125	
Tito 120	
Rated Input Frequency (Hz): 50-60	
Rated Output Voltage (V): 110-125	
Rated Output Frequency (Hz): 50-60	
Rack Mountable: No	
Height (mm): 432	
Width (mm): 196	
Depth (mm): 544	
Total Number of Outlets: 10	
Number of Battery Backup and Surge 10 Protected Outlets:	
Number of Surge Protected Only Outlets: 0	
Normal Mode(s) Input Dependency Characteristic (ac): Voltage Independent	
Modular UPS: No	
Number of Normal Modes: Single-normal-mode	
Default Normal Mode (ac): Voltage Independent	
Test Input Voltage (V rms): 120	
Test Input Frequency (Hz): 60	
Test Output Voltage (V): 120	

Test Output Frequency (Hz):	60
Total Input Power in W at 0% Load Min Config Lowest Dependency (ac):	5.32
Efficiency at 25% Load Min Config Lowest Dependency (ac):	98.6
Efficiency at 50% Load Min Config Lowest Dependency (ac):	98.9
Efficiency at 75% Load Min Config Lowest Dependency (ac):	98.7
Efficiency at 100% Load Min Config Lowest Dependency (ac):	98.5
Weighted Efficiency Calc Min Config Lowest Dependency:	98.7
Efficiency (%):	98.7
Modular UPS Module Tested Model Number:	N/A
Energy Storage Mechanism:	Battery
Energy Storage System Technology:	Valve Regulated Lead-acid Battery
Energy Storage System Configuration:	Integral
Energy Storage System Removable to Another Room:	No
Energy Storage System Runtime at 100% Load (min.):	10
Energy Storage System Runtime at 50% Load (min.):	28
Energy Storage System Warranty (yrs):	2
Energy Storage System Information URL:	https://www.apc.com/shop/us/en/products/P-RBC55
Battery Recycling URL:	https://www.apc.com/us/en/who-we-are/sustainability/recycling-options.jsp
Network Connections Available:	Serial Port,Ethernet,USB Port
Communication Protocols:	Other,Modbus TCP,Modbus RTU
Communication Protocol Other:	USB Power Summary, Simple Signalling, SmartConnect
Manufacturer Take Back Program:	Yes
Manufacturer Take Back Program URL:	https://www.apc.com/us/en/who-we-are/sustainability/recycling-options.jsp
Model Web Page URL:	https://www.apc.com/us/en/product-category/88972-uninterruptible-power-supply-ups/
Test Method Guidelines:	https://www.apc.com/us/en/who-we-are/sustainability/
Date Available on Market:	2024-01-05
Date Certified:	2023-10-31
Markets:	United States
ENERGY STAR Certified:	Yes

Captured On: 06/17/2025