

## APC by Schneider Electric - Smart-UPS 2200VA RM SmartConnect TAA: SMT2200RM2UCUS

| Specifications   |                                      |
|--|--------------------------------------|
| ENERGY STAR Unique ID:                                   | 2698707                              |
| Brand Name:  | APC by Schneider Electric            |
| Model Name:  | Smart-UPS 2200VA RM SmartConnect TAA |
| Model Number:  | SMT2200RM2UCUS                       |
| Power Conversion Mechanism:                              | Static                               |
| Minimum Configuration Tested Model Number:               | SMT2200RM2UC                         |
| Active Output Power Rating Minimum Configuration (W):    | 1920                                 |
| Apparent Output Power Rating Minimum Configuration (VA): | 1920                                 |
| Topology (ac):   | Line Interactive                     |
| Topology and Product Type Combined:                      | ac Line Interactive (VI)             |
| Application:   | Commercial                           |
| Rated Input Voltage (V rms):                             | 110-125                              |
| Rated Input Frequency (Hz):                              | 50-60                                |
| Rated Output Voltage (V):                                | 110-125                              |
| Rated Output Frequency (Hz):                             | 50-60                                |
| Rack Mountable:  | Yes                                  |
| Rack Mount Height (U):                                   | 2                                    |
| Height (mm):   | 86                                   |
| Width (mm):  | 432                                  |
| Depth (mm):  | 683                                  |
| Total Number of Outlets:                                 | 8                                    |
| Number of Battery Backup and Surge Protected Outlets:    | 8                                    |
| Number of Surge Protected Only Outlets:                  | 0                                    |
| Normal Mode(s) Input Dependency Characteristic (ac):     | Voltage Independent                  |
| Modular UPS:   | No                                   |
| Number of Normal Modes:                                  | Single-normal-mode                   |
| Default Normal Mode (ac):                                | Voltage Independent                  |
| Test Input Voltage (V rms):                              | 120                                  |
| Test Input Frequency (Hz):                               | 60                                   |

| Test Output Voltage (V):   | 120  |
|--|--|
| Test Output Frequency (Hz):  | 60   |
| Total Input Power in W at 0% Load Min Config Lowest Dependency (ac): | 5.25   |
| Efficiency at 25% Load Min Config Lowest Dependency (ac):            | 98.7   |
| Efficiency at 50% Load Min Config Lowest Dependency (ac):            | 98.9   |
| Efficiency at 75% Load Min Config Lowest Dependency (ac):            | 98.8   |
| Efficiency at 100% Load Min Config Lowest Dependency (ac):           | 98.6   |
| Weighted Efficiency Calc Min Config Lowest Dependency:               | 98.8   |
| Efficiency (%):  | 98.8   |
| Modular UPS Module Tested Model Number:                              | N/A  |
| Energy Storage Mechanism:  | Battery  |
| Energy Storage System Technology:                                    | Valve Regulated Lead-acid Battery  |
| <b>Energy Storage System Configuration:</b>                          | Integral   |
| Energy Storage System Removable to Another Room:                     | No   |
| Energy Storage System Runtime at 100% Load (min.):                   | 3  |
| Energy Storage System Runtime at 50% Load (min.):                    | 10   |
| Energy Storage System Warranty (yrs):                                | 2  |
| Energy Storage System Information URL:                               | https://www.apc.com/shop/us/en/products/P-RBC43                                    |
| Battery Recycling URL:   | https://www.apc.com/us/en/who-we-are/sustainability/recycling-options.jsp          |
| Network Connections Available:                                       | Serial Port,Ethernet,USB Port  |
| Communication Protocols:   | HTTP,HTTPS,Other,Modbus TCP,SNMP (v1, 2 or 3),Modbus RTU                           |
| Communication Protocol Other:  | USB Power Summary, Simple Signalling, SmartConnect                                 |
| Manufacturer Take Back Program:                                      | Yes  |
| Manufacturer Take Back Program URL:                                  | https://www.apc.com/us/en/who-we-are/sustainability/recycling-options.jsp          |
| Model Web Page URL:  | https://www.apc.com/us/en/product-category/88972-uninterruptible-power-supply-ups/ |
| Test Method Guidelines:  | https://www.apc.com/us/en/who-we-are/sustainability/                               |
| Date Available on Market:  | 2024-01-05   |
| Date Certified:  | 2023-10-31   |
| Markets:   | United States  |
| ENERGY STAR Certified:   | Yes  |
|  |  |

**Captured On:** 06/17/2025