## APC by Schneider Electric - Smart-UPS 3000VA SmartConnect TAA : SMT3000CUS

## Specifications

| | |
|---|---|
| **ENERGY STAR Unique ID:** | 2698709 |
| **Brand Name:** | APC by Schneider Electric |
| **Model Name:** | Smart-UPS 3000VA SmartConnect TAA |
| **Model Number:** | SMT3000CUS |
| **Power Conversion Mechanism:** | Static |
| **Minimum Configuration Tested Model Number:** | SMT3000C |
| **Active Output Power Rating Minimum Configuration (W):** | 2700 |
| **Apparent Output Power Rating Minimum Configuration (VA):** | 3000 |
| **Topology (ac):** | Line Interactive |
| **Topology and Product Type Combined:** | ac Line Interactive (VI) |
| **Application:** | Commercial |
| **Rated Input Voltage (V rms):** | 110-125 |
| **Rated Input Frequency (Hz):** | 50-60 |
| **Rated Output Voltage (V):** | 110-125 |
| **Rated Output Frequency (Hz):** | 50-60 |
| **Rack Mountable:** | No |
| **Height (mm):** | 432 |
| **Width (mm):** | 196 |
| **Depth (mm):** | 544 |
| **Total Number of Outlets:** | 10 |
| **Number of Battery Backup and Surge Protected Outlets:** | 10 |
| **Number of Surge Protected Only Outlets:** | 0 |
| **Normal Mode(s) Input Dependency Characteristic (ac):** | Voltage Independent |
| **Modular UPS:** | No |
| **Number of Normal Modes:** | Single-normal-mode |
| **Default Normal Mode (ac):** | Voltage Independent |
| **Test Input Voltage (V rms):** | 120 |
| **Test Input Frequency (Hz):** | 60 |
| **Test Output Voltage (V):** | 120 |

| | |
|---|---|
| **Test Output Frequency (Hz):** | 60 |
| **Total Input Power in W at 0% Load Min Config Lowest Dependency (ac):** | 5.24 |
| **Efficiency at 25% Load Min Config Lowest Dependency (ac):** | 98.9 |
| **Efficiency at 50% Load Min Config Lowest Dependency (ac):** | 98.9 |
| **Efficiency at 75% Load Min Config Lowest Dependency (ac):** | 98.7 |
| **Efficiency at 100% Load Min Config Lowest Dependency (ac):** | 98.4 |
| **Weighted Efficiency Calc Min Config Lowest Dependency:** | 98.7 |
| **Efficiency (%):** | 98.7 |
| **Modular UPS Module Tested Model Number:** | N/A |
| **Energy Storage Mechanism:** | Battery |
| **Energy Storage System Technology:** | Valve Regulated Lead-acid Battery |
| **Energy Storage System Configuration:** | Integral |
| **Energy Storage System Removable to Another Room:** | No |
| **Energy Storage System Runtime at 100% Load (min.):** | 5 |
| **Energy Storage System Runtime at 50% Load (min.):** | 17 |
| **Energy Storage System Warranty (yrs):** | 2 |
| **Energy Storage System Information URL:** | https://www.apc.com/shop/us/en/products/P-RBC55 |
| **Battery Recycling URL:** | https://www.apc.com/us/en/who-we-are/sustainability/recycling-options.jsp |
| **Network Connections Available:** | Serial Port,Ethernet,USB Port |
| **Communication Protocols:** | Other,Modbus TCP,Modbus RTU |
| **Communication Protocol Other:** | USB Power Summary, Simple Signalling, SmartConnect |
| **Manufacturer Take Back Program:** | Yes |
| **Manufacturer Take Back Program URL:** | https://www.apc.com/us/en/who-we-are/sustainability/recycling-options.jsp |
| **Model Web Page URL:** | https://www.apc.com/us/en/product-category/88972-uninterruptible-power-supply-ups/ |
| **Test Method Guidelines:** | https://www.apc.com/us/en/who-we-are/sustainability/ |
| **Date Available on Market:** | 2024-01-05 |
| **Date Certified:** | 2023-10-31 |
| **Markets:** | United States |
| **ENERGY STAR Certified:** | Yes |