

APC by Schneider Electric - Smart-UPS Ultra 5KVA 208V RM 2U LI TAA : SRTL5KRM2UTUS

Specifications

•	
ENERGY STAR Unique ID:	2698713
Brand Name:	APC by Schneider Electric
Model Name:	Smart-UPS Ultra 5KVA 208V RM 2U LI TAA
Model Number:	SRTL5KRM2UTUS
Power Conversion Mechanism:	Static
Minimum Configuration Tested Model Number:	SRTL5KRM2UT
Active Output Power Rating Minimum Configuration (W):	5000
Apparent Output Power Rating Minimum Configuration (VA):	5000
Topology (ac):	Multi-Mode Double Conversion
Topology and Product Type Combined:	ac - Other
Application:	Commercial
Rated Input Voltage (V rms):	208-240
Rated Input Frequency (Hz):	50-60
Rated Output Voltage (V):	208-240
Rated Output Frequency (Hz):	50-60
Rack Mountable:	Yes
Rack Mount Height (U):	2
Height (mm):	89
Width (mm):	432
Depth (mm):	768
Total Number of Outlets:	4
Number of Battery Backup and Surge Protected Outlets:	4
Number of Surge Protected Only Outlets:	0
Normal Mode(s) Input Dependency Characteristic (ac):	Voltage and Frequency Independent, Voltage and Frequency Dependent
Modular UPS:	No
Number of Normal Modes:	Multiple-normal-mode
Default Normal Mode (ac):	Voltage and Frequency Independent
Test Input Voltage (V rms):	240
Test Input Frequency (Hz):	60

Test Output Voltage (V):	240
Test Output Frequency (Hz):	60
Total Input Power in W at 0% Load Min Config Lowest Dependency (ac):	55.22
Total Input Power in W at 0% Load Min Config Highest Dependency (ac):	52.02
Efficiency at 25% Load Min Config Lowest Dependency (ac):	94.1
Efficiency at 25% Load Min Config Highest Dependency (ac):	96.1
Efficiency at 50% Load Min Config Lowest Dependency (ac):	95.7
Efficiency at 50% Load Min Config Highest Dependency (ac):	98.7
Efficiency at 75% Load Min Config Lowest Dependency (ac):	96.0
Efficiency at 75% Load Min Config Highest Dependency (ac):	98.3
Efficiency at 100% Load Min Config Lowest Dependency (ac):	95.8
Efficiency at 100% Load Min Config Highest Dependency (ac):	98.5
Weighted Efficiency Calc Min Config Lowest Dependency:	95.9
Weighted Efficiency Calc Min Config Highest Dependency:	98.2
Minimum Configuration Input Power Factor Highest-Input Dependency:	1.0
Efficiency (%):	98.2
Modular UPS Module Tested Model Number:	N/A
Energy Storage Mechanism:	Battery
Energy Storage System Technology:	Lithium-ion Battery
Energy Storage System Configuration:	Integral
Energy Storage System Removable to Another Room:	Yes
Energy Storage System Runtime at 100% Load (min.):	5
Energy Storage System Runtime at 50% Load (min.):	12
Energy Storage System Warranty (yrs):	5
Energy Storage System Information URL:	http://www.apc.com/shop/us/en/products/P-SRYLBM
Battery Recycling URL:	https://www.apc.com/us/en/who-we-are/sustainability/recycling- options.jsp
Network Connections Available:	Ethernet
Communication Protocols:	HTTP,HTTPS,Modbus TCP,SNMP (v1, 2 or 3)
Manufacturer Take Back Program:	Yes
Manufacturer Take Back Program URL:	https://www.apc.com/us/en/who-we-are/sustainability/recycling- options.jsp

Model Web Page URL:	https://www.apc.com/us/en/product-category/88972-uninterruptible- power-supply-ups/
Test Method Guidelines:	https://www.apc.com/us/en/who-we-are/sustainability/
Date Available on Market:	2024-05-22
Date Certified:	2023-10-31
Markets:	United States
ENERGY STAR Certified:	Yes

Captured On: 06/18/2025