

APC by Schneider Electric - Smart-UPS 2200VA RM SC LI TAA: SMTL2200RM2UCUS

ENERGY STAR Unique ID: 2698714 Brand Name: APC by Schneider Electric Model Name: Smart-UPS 2200VA RM SC LI TAA Model Number: SMTL2200RM2UCUS Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: SMTL2200RM2UC Minimum Configuration Tested Model SMTL2200RM2UC Active Output Power Rating Minimum Configuration (W): Power Rating Minimum Configuration (W): SMTL2200RM2UC Apparent Output Power Rating Minimum Configuration (W): SMTL2200RM2UC Maximum Configuration Tested Model SMTL2200RM2UC Maximum Configuration Tested Model Number: Commercial Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Commercial Rated Input Voltage (V rms): 110-125 Rated Input Frequency (Hz): 50-60 Rated Output Voltage (V): 110-125 Rated Output Voltage (V): 110-125 Rated Output Frequency (Hz): 50-60 Rack Mountable: Yes Rack Mount Height (U): 2 Height (mm): 86 Width (mm): 432 Depth (mm): 683 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Outlets: Number of Surge Protected Only Outlets: 0	Specifications	
Brand Name: APC by Schneider Electric Model Name: Smart-UPS 2200VA RM SC LI TAA Model Number: SMTL2200RM2UCUS Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: SMTL2200RM2UC Active Output Power Rating Minimum Configuration (W): 1920 Apparent Output Power Rating Minimum Configuration (VA): SMTL2200RM2UC Maximum Configuration Tested Model Number: SMTL2200RM2UC Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Commercial Rated Input Voltage (V rms): 50-60 Rated Input Frequency (Hz): 50-60 Rated Output Voltage (V): 110-125 Rated Output Frequency (Hz): 50-60 Rack Mountable: Yes Rack Mount Height (U): 2 Height (mm): 86 Width (mm): 432 Depth (mm): 683 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: 8	Specifications	
Model Name: Smart-UPS 2200VA RM SC LI TAA Model Number: SMTL2200RM2UCUS Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: SMTL2200RM2UC Active Output Power Rating Minimum Configuration (W): 1920 Apparent Output Power Rating Minimum Configuration (VA): SMTL2200RM2UC Maximum Configuration Tested Model Number: SMTL2200RM2UC Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Commercial Rated Input Voltage (V rms): 110-125 Rated Input Frequency (Hz): 50-60 Rated Output Voltage (V): 110-125 Rated Output Frequency (Hz): 50-60 Rack Mountable: Yes Rack Mount Height (U): 2 Height (mm): 432 Depth (mm): 683 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: 8	ENERGY STAR Unique ID:	2698714
Model Number: SMTL2200RM2UCUS Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: SMTL2200RM2UC Active Output Power Rating Minimum Configuration (W): 1920 Apparent Output Power Rating Minimum Configuration (VA): SMTL2200RM2UC Maximum Configuration Tested Model Number: SMTL2200RM2UC Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Commercial Rated Input Voltage (V rms): 110-125 Rated Input Frequency (Hz): 50-60 Rated Output Voltage (V): 110-125 Rated Output Frequency (Hz): 50-60 Rack Mountable: Yes Rack Mount Height (U): 2 Height (mm): 432 Depth (mm): 683 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: 8	Brand Name:	APC by Schneider Electric
Power Conversion Mechanism:StaticMinimum Configuration Tested Model Number:SMTL2200RM2UCActive Output Power Rating Minimum Configuration (W):1920Apparent Output Power Rating Minimum Configuration (VA):1920Maximum Configuration Tested Model Number:SMTL2200RM2UCTopology (ac):Line InteractiveTopology and Product Type Combined:ac Line Interactive (VI)Application:CommercialRated Input Voltage (V rms):110-125Rated Output Frequency (Hz):50-60Rated Output Voltage (V):110-125Rated Output Frequency (Hz):50-60Rack Mountable:YesRack Mount Height (U):2Height (mm):432Depth (mm):432Depth (mm):683Total Number of Outlets:8Number of Battery Backup and Surge Protected Outlets:8	Model Name:	Smart-UPS 2200VA RM SC LI TAA
Minimum Configuration Tested Model Number: Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Maximum Configuration Tested Model Number: Topology (ac): Topology and Product Type Combined: Application: Rated Input Voltage (V rms): Rated Input Frequency (Hz): Rated Output Voltage (V): Rated Output Voltage (V): Rated Output Voltage (V): Rated Output Frequency (Hz): So-60 Rack Mountable: Rack Mountable: Rack Mount Height (U): 432 Depth (mm): 683 Total Number of Outlets: Number of Battery Backup and Surge Protected Outlets:	Model Number:	SMTL2200RM2UCUS
Number: Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Maximum Configuration Tested Model Number: Topology (ac): Line Interactive Topology and Product Type Combined: Actine Interactive (VI) Application: Commercial Rated Input Voltage (V rms): Rated Input Frequency (Hz): So-60 Rated Output Voltage (V): Rated Output Voltage (V): Rated Output Voltage (V): Rack Mountable: Rack Mount Height (U): Height (mm): Back Mount Height (U): Height (mm): Back Mountable: Rack Mount Height (V): Rated Output Frequency (Rack Mountable: Rack Mount Height (V): Rack Mount Height (V): Rack Mount Height (V): Rack Mountable: Rack Mount Height (V): Rack Mount Height (V): Rack Mount Height (V): Rack Mountable: Rack Mount Height (V): Rack Mountable: Rack Mount Height (V): Rack Mountable: Rack Mount Height (V): Rack Mount Height (V): Rack Mountable: Rack Mount Height (V): Rack Mount Height (V): Rack Mount Height (V): Rack Mountable: Rack Moun	Power Conversion Mechanism:	Static
Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Maximum Configuration Tested Model Number: Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Commercial Rated Input Voltage (V rms): Rated Input Frequency (Hz): So-60 Rated Output Voltage (V): Rated Output Voltage (V): Rated Output Frequency (Hz): So-60 Rack Mountable: Rack Mount Height (U): 2 Height (mm): 432 Depth (mm): 683 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: 8	——————————————————————————————————————	SMTL2200RM2UC
Configuration (VA):SMTL2200RM2UCMaximum Configuration Tested Model Number:SMTL2200RM2UCTopology (ac):Line InteractiveTopology and Product Type Combined:ac Line Interactive (VI)Application:CommercialRated Input Voltage (V rms):110-125Rated Input Frequency (Hz):50-60Rated Output Voltage (V):110-125Rated Output Frequency (Hz):50-60Rack Mountable:YesRack Mount Height (U):2Height (mm):86Width (mm):432Depth (mm):683Total Number of Outlets:8Number of Battery Backup and Surge Protected Outlets:8		1920
Number: Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Commercial Rated Input Voltage (V rms): Rated Input Frequency (Hz): So-60 Rated Output Voltage (V): Rated Output Frequency (Hz): So-60 Rack Mountable: Yes Rack Mount Height (U): 42 Height (mm): 86 Width (mm): 432 Depth (mm): 50-60 Rack Number of Outlets: 88 Number of Battery Backup and Surge Protected Outlets: 80 Line Interactive Ac Line Interactive Act Ac Line Interactive Act		1920
Topology and Product Type Combined: Application: Commercial Rated Input Voltage (V rms): Rated Input Frequency (Hz): S0-60 Rated Output Voltage (V): Rated Output Frequency (Hz): S0-60 Rated Output Frequency (Hz): S0-60 Rack Mountable: Yes Rack Mount Height (U): 42 Height (mm): 86 Width (mm): 432 Depth (mm): 683 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: 8		SMTL2200RM2UC
Application: Rated Input Voltage (V rms): Rated Input Frequency (Hz): Rated Output Voltage (V): Rated Output Frequency (Hz): Rated Output Frequency (Hz): Rack Mountable: Rack Mount Height (U): Peight (mm): Width (mm): 432 Depth (mm): 683 Total Number of Outlets: Number of Battery Backup and Surge Protected Outlets:	Topology (ac):	Line Interactive
Rated Input Voltage (V rms): 110-125 Rated Input Frequency (Hz): 50-60 Rated Output Voltage (V): 110-125 Rated Output Frequency (Hz): 50-60 Rack Mountable: Yes Rack Mount Height (U): 2 Height (mm): 86 Width (mm): 432 Depth (mm): 683 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: 8	Topology and Product Type Combined:	ac Line Interactive (VI)
Rated Input Frequency (Hz): 50-60 Rated Output Voltage (V): 110-125 Rated Output Frequency (Hz): 50-60 Rack Mountable: Yes Rack Mount Height (U): 2 Height (mm): 86 Width (mm): 432 Depth (mm): 683 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: 8	Application:	Commercial
Rated Output Voltage (V): 110-125 Rated Output Frequency (Hz): 50-60 Rack Mountable: Yes Rack Mount Height (U): 2 Height (mm): 86 Width (mm): 432 Depth (mm): 683 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: 8	Rated Input Voltage (V rms):	110-125
Rated Output Frequency (Hz): 50-60 Rack Mountable: Yes Rack Mount Height (U): 2 Height (mm): 86 Width (mm): 432 Depth (mm): 683 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: 8	Rated Input Frequency (Hz):	50-60
Rack Mount Height (U): Rack Mount Height (U): Height (mm): Width (mm): Depth (mm): 683 Total Number of Outlets: Number of Battery Backup and Surge Protected Outlets:	Rated Output Voltage (V):	110-125
Rack Mount Height (U): Height (mm): 86 Width (mm): 432 Depth (mm): 683 Total Number of Outlets: Number of Battery Backup and Surge Protected Outlets:	Rated Output Frequency (Hz):	50-60
Height (mm): 86 Width (mm): 432 Depth (mm): 683 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: 8	Rack Mountable:	Yes
Width (mm): 432 Depth (mm): 683 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: 8	Rack Mount Height (U):	2
Depth (mm): 683 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: 8	Height (mm):	86
Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: 8	Width (mm):	432
Number of Battery Backup and Surge Protected Outlets: 8	Depth (mm):	683
Protected Outlets:	Total Number of Outlets:	8
Number of Surge Protected Only Outlets: 0		8
	Number of Surge Protected Only Outlets:	0
Normal Mode(s) Input Dependency Characteristic (ac): Voltage Independent		Voltage Independent
Modular UPS: No	Modular UPS:	No
Number of Normal Modes: Single-normal-mode	Number of Normal Modes:	Single-normal-mode
Default Normal Mode (ac): Voltage Independent	Default Normal Mode (ac):	Voltage Independent

Test Input Voltage (V rms):	120
Test Input Frequency (Hz):	60
Test Output Voltage (V):	120
Test Output Frequency (Hz):	60
Total Input Power in W at 0% Load Min Config Lowest Dependency (ac):	5.29
Efficiency at 25% Load Min Config Lowest Dependency (ac):	98.6
Efficiency at 50% Load Min Config Lowest Dependency (ac):	98.8
Efficiency at 75% Load Min Config Lowest Dependency (ac):	98.7
Efficiency at 100% Load Min Config Lowest Dependency (ac):	98.4
Weighted Efficiency Calc Min Config Lowest Dependency:	98.6
Efficiency (%):	98.6
Modular UPS Module Tested Model Number:	N/A
Energy Storage Mechanism:	Battery
Energy Storage System Technology:	Lithium-ion Battery
Energy Storage System Configuration:	Integral
Energy Storage System Removable to Another Room:	No
Energy Storage System Runtime at 100% Load (min.):	6
Energy Storage System Runtime at 50% Load (min.):	12
Energy Storage System Warranty (yrs):	5
Energy Storage System Information URL:	https://www.apc.com/shop/us/en/products/P-APCRBC174-LI
Battery Recycling URL:	https://www.apc.com/us/en/who-we-are/sustainability/recycling-options.jsp
Network Connections Available:	Serial Port,Ethernet,USB Port
Communication Protocols:	HTTP,HTTPS,Other,Modbus TCP,SNMP (v1, 2 or 3),Modbus RTU
Communication Protocol Other:	USB Power Summary, Micro-Link, Simple Signaling, SmartConnect
Manufacturer Take Back Program:	Yes
Manufacturer Take Back Program URL:	http://www.apc.com/company/us/en/sustainability/recycling-options/
Model Web Page URL:	https://www.apc.com/us/en/product-category/88972-uninterruptible-power-supply-ups/
Test Method Guidelines:	http://www.apc.com/company/us/en/sustainability/energy-efficiency/
Date Available on Market:	2024-02-04
Date Certified:	2023-10-31
Markets:	United States
ENERGY STAR Certified:	Yes