

## APC by Schneider Electric - Smart-UPS Online SRT 6KVA 208 RM TAA : SRT6KRMXLTUS

| Specifications                                           |                                                                    |
|----------------------------------------------------------|--------------------------------------------------------------------|
| ENERGY STAR Unique ID:                                   | 2698718                                                            |
| Brand Name:                                              | APC by Schneider Electric                                          |
| Model Name:                                              | Smart-UPS Online SRT 6KVA 208 RM TAA                               |
| Model Number:                                            | SRT6KRMXLTUS                                                       |
| Power Conversion Mechanism:                              | Static                                                             |
| Minimum Configuration Tested Model Number:               | SRT6KXLT                                                           |
| Active Output Power Rating Minimum Configuration (W):    | 6000                                                               |
| Apparent Output Power Rating Minimum Configuration (VA): | 6000                                                               |
| Topology (ac):                                           | Multi-Mode Double Conversion                                       |
| Topology and Product Type Combined:                      | ac - Other                                                         |
| Application:                                             | Commercial                                                         |
| Rated Input Voltage (V rms):                             | 208-240                                                            |
| Rated Input Frequency (Hz):                              | 50-60                                                              |
| Rated Output Voltage (V):                                | 208-240                                                            |
| Rated Output Frequency (Hz):                             | 50-60                                                              |
| Rack Mountable:                                          | Yes                                                                |
| Rack Mount Height (U):                                   | 4                                                                  |
| Height (mm):                                             | 174                                                                |
| Width (mm):                                              | 432                                                                |
| Depth (mm):                                              | 719                                                                |
| Total Number of Outlets:                                 | 5                                                                  |
| Number of Battery Backup and Surge<br>Protected Outlets: | 5                                                                  |
| Number of Surge Protected Only Outlets:                  | 0                                                                  |
| Normal Mode(s) Input Dependency Characteristic (ac):     | Voltage and Frequency Independent, Voltage and Frequency Dependent |
| Modular UPS:                                             | No                                                                 |
| Number of Normal Modes:                                  | Multiple-normal-mode                                               |
| Default Normal Mode (ac):                                | Voltage and Frequency Independent                                  |
| Test Input Voltage (V rms):                              | 240                                                                |
| Test Input Frequency (Hz):                               | 60                                                                 |

| Test Output Voltage (V):                                              | 240                                                                           |
|-----------------------------------------------------------------------|-------------------------------------------------------------------------------|
| Test Output Frequency (Hz):                                           | 60                                                                            |
| Total Input Power in W at 0% Load Min Config Lowest Dependency (ac):  | 69.2                                                                          |
| Total Input Power in W at 0% Load Min Config Highest Dependency (ac): | 53.3                                                                          |
| Efficiency at 25% Load Min Config Lowest Dependency (ac):             | 93.0                                                                          |
| Efficiency at 25% Load Min Config Highest Dependency (ac):            | 96.4                                                                          |
| Efficiency at 50% Load Min Config Lowest Dependency (ac):             | 94.6                                                                          |
| Efficiency at 50% Load Min Config Highest Dependency (ac):            | 98.0                                                                          |
| Efficiency at 75% Load Min Config Lowest Dependency (ac):             | 94.6                                                                          |
| Efficiency at 75% Load Min Config Highest Dependency (ac):            | 98.5                                                                          |
| Efficiency at 100% Load Min Config Lowest Dependency (ac):            | 94.5                                                                          |
| Efficiency at 100% Load Min Config Highest Dependency (ac):           | 98.7                                                                          |
| Weighted Efficiency Calc Min Config Lowest Dependency:                | 94.6                                                                          |
| Weighted Efficiency Calc Min Config Highest Dependency:               | 98.4                                                                          |
| Minimum Configuration Input Power Factor Highest-Input Dependency:    | 1.0                                                                           |
| Efficiency (%):                                                       | 94.6                                                                          |
| Modular UPS Module Tested Model Number:                               | N/A                                                                           |
| Energy Storage Mechanism:                                             | Battery                                                                       |
| Energy Storage System Technology:                                     | Valve Regulated Lead-acid Battery                                             |
| Energy Storage System Configuration:                                  | Integral                                                                      |
| Energy Storage System Removable to Another Room:                      | No                                                                            |
| Energy Storage System Runtime at 100% Load (min.):                    | 2                                                                             |
| Energy Storage System Runtime at 50% Load (min.):                     | 8                                                                             |
| Energy Storage System Warranty (yrs):                                 | 2                                                                             |
| Energy Storage System Information URL:                                | http://www.apc.com/shop/us/en/products/P-APCRBC140                            |
| Battery Recycling URL:                                                | https://www.apc.com/us/en/who-we-are/sustainability/recycling-<br>options.jsp |
| Network Connections Available:                                        | Serial Port,Ethernet,USB Port                                                 |
| Communication Protocols:                                              | HTTP,HTTPS,Other,Modbus TCP,Modbus RTU                                        |
| Communication Protocol Other:                                         | USB Power Summary, Micro-Link, Simple Signaling                               |
| Manufacturer Take Back Program:                                       | Yes                                                                           |
|                                                                       |                                                                               |

| Manufacturer Take Back Program URL: | https://www.apc.com/us/en/who-we-are/sustainability/recycling-options.jsp          |
|-------------------------------------|------------------------------------------------------------------------------------|
| Model Web Page URL:                 | https://www.apc.com/us/en/product-category/88972-uninterruptible-power-supply-ups/ |
| Test Method Guidelines:             | https://www.apc.com/us/en/who-we-are/sustainability/                               |
| Date Available on Market:           | 2024-07-28                                                                         |
| Date Certified:                     | 2023-10-31                                                                         |
| Markets:                            | United States                                                                      |
| ENERGY STAR Certified:              | Yes                                                                                |

**Captured On:** 06/18/2025