



ENERGY STAR CERTIFIED

Uninterruptible Power Supplies

APC by Schneider Electric - Smart-UPS Ultra On-Line Lithium-ion 10kVA/10kW 4URack/Tower 208/240V : SRTL10KRM4UT

Specifications

| | |
|----------------------------------------------------------|----------------------------------------------------------------------|
| ENERGY STAR Unique ID: | 3354468 |
| Brand Name: | APC by Schneider Electric |
| Model Name: | Smart-UPS Ultra On-Line Lithium-ion 10kVA/10kW 4URack/Tower 208/240V |
| Model Number: | SRTL10KRM4UT |
| Power Conversion Mechanism: | Static |
| Minimum Configuration Tested Model Number: | SRTL10KRM4UT |
| Active Output Power Rating Minimum Configuration (W): | 10000 |
| Apparent Output Power Rating Minimum Configuration (VA): | 10000 |
| Topology (ac): | Multi-Mode Double Conversion |
| Topology and Product Type Combined: | ac - Other |
| Application: | Commercial |
| Rated Input Voltage (V rms): | 208-240 |
| Rated Input Frequency (Hz): | 50-60 |
| Rated Output Voltage (V): | 208-240 |
| Rated Output Frequency (Hz): | 50-60 |
| Rack Mountable: | Yes |
| Height (mm): | 175 |
| Width (mm): | 432 |
| Depth (mm): | 731 |
| Total Number of Outlets: | 4 |
| Number of Battery Backup and Surge Protected Outlets: | 4 |
| Number of Surge Protected Only Outlets: | 0 |
| Normal Mode(s) Input Dependency Characteristic (ac): | Voltage and Frequency Independent,Voltage and Frequency Dependent |
| Modular UPS: | No |
| Number of Normal Modes: | Multiple-normal-mode |
| Default Normal Mode (ac): | Voltage and Frequency Independent |
| Test Input Voltage (V rms): | 240 |

| | |
|------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Input Frequency (Hz): | 60 |
| Test Output Voltage (V): | 240 |
| Test Output Frequency (Hz): | 60 |
| Total Input Power in W at 0% Load Min Config Lowest Dependency (ac): | 100.99 |
| Total Input Power in W at 0% Load Min Config Highest Dependency (ac): | 81.17 |
| Efficiency at 25% Load Min Config Lowest Dependency (ac): | 94.4 |
| Efficiency at 25% Load Min Config Highest Dependency (ac): | 96.9 |
| Efficiency at 50% Load Min Config Lowest Dependency (ac): | 96.1 |
| Efficiency at 50% Load Min Config Highest Dependency (ac): | 98.2 |
| Efficiency at 75% Load Min Config Lowest Dependency (ac): | 96.5 |
| Efficiency at 75% Load Min Config Highest Dependency (ac): | 98.6 |
| Efficiency at 100% Load Min Config Lowest Dependency (ac): | 96.4 |
| Efficiency at 100% Load Min Config Highest Dependency (ac): | 98.7 |
| Weighted Efficiency Calc Min Config Lowest Dependency: | 96.3 |
| Weighted Efficiency Calc Min Config Highest Dependency: | 98.5 |
| Minimum Configuration Input Power Factor Highest-Input Dependency: | 1.0 |
| Efficiency (%): | 96.9 |
| Modular UPS Module Tested Model Number: | N/A |
| Energy Storage Mechanism: | Battery |
| Energy Storage System Technology: | Lithium-ion Battery |
| Energy Storage System Configuration: | Integral |
| Energy Storage System Removable to Another Room: | No |
| Energy Storage System Runtime at 100% Load (min.): | 5 |
| Energy Storage System Runtime at 50% Load (min.): | 12 |
| Energy Storage System Warranty (yrs): | 5 |
| Energy Storage System Information URL: | https://www.apc.com/us/en/product/SRYLBM |
| Battery Recycling URL: | https://www.apc.com/us/en/who-we-are/sustainability/recycling-options.jsp |
| Network Connections Available: | Ethernet |
| Communication Protocols: | HTTP,HTTPS,SNMP (v1, 2 or 3) |
| Manufacturer Take Back Program: | Yes |

| | |
|-------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Manufacturer Take Back Program URL: | https://www.apc.com/us/en/who-we-are/sustainability/recycling-options.jsp |
| Model Web Page URL: | https://www.apc.com/us/en/product/SRTL10KRM4UT |
| Test Method Guidelines: | https://www.apc.com/us/en/who-we-are/sustainability/ |
| Date Available on Market: | 2024-01-22 |
| Date Certified: | 2023-12-27 |
| Markets: | United States, Canada |
| ENERGY STAR Certified: | Yes |

Additional Model Information

Smart-UPS Ultra On-Line Lithium-ion 10kVA/10kW 4U Rack/Tower 208/240V Factory Serviced,SRTL10KRM4UTW;; Std Exch Smart-UPS Ultra On-Line Lithium-ion 10kVA/10kW 4U Rack/Tower 208/240V,SRTL10KRM4UTQ,

Captured On:
05/01/2025