

Minuteman - PRO1500RT2U: PRO1500RT2U

Brand Name: Minuteman Model Name: Model Number: PRO1500RT2U Model Number: PRO1500RT2U Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Data Center, Consumer, Commercial Rated Input Voltage (V rms): Rated Input Frequency (Hz): Rated Output Frequency (Hz): Rated Ou	Specifications	
Brand Name: Minuteman Model Name: PRO1500RT2U Model Number: PRO1500RT2U Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: PRO1500RT2U Number: Active Output Power Rating Minimum Configuration (W): Department of Configuration (W): Department of Configuration (W): Department of Configuration (W): Line Interactive Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Data Center, Consumer, Commercial Rated Input Voltage (V rms): 120-120 Rated Input Voltage (V): 120-120 Rated Input Frequency (Hz): 60-60 Rack Mountable: No Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 86 Width (mm): 481 Depth (mm): 510 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: No Nommal Mode(s) Input Dependency Voltage Independent Characteristic (ac): No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60-60 Test Output Voltage (V rms): 120 Test Input Frequency (Hz): 60-60 Test Output Voltage (V rms): 120	opeomounons	
Model Name: PR01500RT2U Model Number: PR01500RT2U Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: PR01500RT2U Active Output Power Rating Minimum Configuration (W): 1550 Apparent Output Power Rating Minimum Configuration (WA): 1500 Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Data Center, Consumer, Commercial Rated Input Voltage (V rms): 120-120 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rated Output Voltage (V): No Rack Mountable: No Height (mm): 86 Width (mm): 481 Depth (mm): 510 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Only Outlets: 0 Number of Surge Protected Only Outlets: 0 Normal Mode(s) Input Dependency Characteristic (ac): No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac):	·	3557057
Model Number: PRO1500RT2U Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: 1050 Active Output Power Rating Minimum Configuration (W): 1500 Apparent Output Power Rating Minimum Configuration (VA): 1500 Apparent Output Product Type Combined: ac Line Interactive (VI) Application: Data Center, Consumer, Commercial Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 86 Width (mm): 481 Depth (mm): 510 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: 8 Number of Battery Backup and Surge Protected Outlets: 0 Normal Mode(s) Input Dependency Characteristic (ac): No Normal Mode(s) Input Dependency Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120	Brand Name:	Minuteman
Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Data Center, Consumer, Commercial Rated Input Voltage (V rms): 120-120 Rated Input Voltage (V): 120-120 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rated Output Frequency (Hz): 86 Width (mm): 86 Width (mm): 86 Width (mm): 510 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: 0 Normal Mode(s) Input Dependency Characteristic (ac): No Normal Mode(s) Input Dependency Characteristic (ac): No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120	Model Name:	PRO1500RT2U
Minimum Configuration Tested Model Number: Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Data Center, Consumer, Commercial Rated Input Voltage (V rms): Rated Input Voltage (V): Rated Output Voltage (V): Rated Output Prequency (Hz): Rated Output Prequency (Hz): Rated Output Prequency (Hz): Rated Output Frequency (Hz): Rate Coutput Freque	Model Number:	PRO1500RT2U
Number: Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Data Center,Consumer,Commercial Rated Input Voltage (V rms): Rated Input Voltage (V): Rated Output Voltage (V): Rated Output Frequency (Hz): Rated Output Frequency (Hz): Rated Output Frequency (Hz): Rated Muntable: No Height (mm): B6 Width (mm): B6 Width (mm): Depth (mm): Total Number of Outlets: Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Default Normal Modes: Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): Test Input Voltage (V): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120	Power Conversion Mechanism:	Static
Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Data Center, Consumer, Commercial Rated Input Voltage (V rms): Rated Input Voltage (V rms): Rated Input Frequency (Hz): Rated Output Voltage (V): Rated Output Voltage (V): Rated Output Frequency (Hz): Rated Output Voltage (V): Rated Center, Consumer, Commercial Rate (VI) Rate Input Voltage (V): Rate Center (VI) Rate Input Voltage (V): Rate Center (VI) Rate Center	Minimum Configuration Tested Model Number:	PRO1500RT2U
Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Data Center,Consumer,Commercial Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 86 Width (mm): 481 Depth (mm): 510 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: Noumber of Surge Protected Only Outlets: 0 Normal Mode(s) Input Dependency Characteristic (ac): No Number of Normal Modes: Default Normal Mode (ac): Voltage Independent Test Input Voltage (V) rms): 120 Test Input Frequency (Hz): 60 Test Input Frequency (Hz): 60 Test Unput Voltage (V): 120	Active Output Power Rating Minimum Configuration (W):	1050
Topology and Product Type Combined: ac Line Interactive (VI) Application: Data Center,Consumer,Commercial Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 86 Width (mm): 481 Depth (mm): 510 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: 0 Normal Mode(s) Input Dependency Characteristic (ac): No Normal Models (S): No Number of Normal Modes: No Number of Normal Modes: No Number of Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Voltage (V): 120	Apparent Output Power Rating Minimum Configuration (VA):	1500
Application: Data Center,Consumer,Commercial Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 86 Width (mm): 481 Depth (mm): 510 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: 0 Normal Mode(s) Input Dependency Voltage Independent Normal Mode(s) Input Dependency Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120	Topology (ac):	Line Interactive
Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 86 Width (mm): 481 Depth (mm): 510 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: 0 Normal Mode(s) Input Dependency Characteristic (ac): Voltage Independent Number of Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Untput Voltage (V): 120	Topology and Product Type Combined:	ac Line Interactive (VI)
Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 86 Width (mm): 481 Depth (mm): 510 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Only Outlets: 0 Normal Mode(s) Input Dependency Characteristic (ac): No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Voltage (V): 120	Application:	Data Center,Consumer,Commercial
Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 86 Width (mm): 481 Depth (mm): 510 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: 0 Normal Mode(s) Input Dependency Characteristic (ac): No Nounber of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Voltage (V): 120	Rated Input Voltage (V rms):	120-120
Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 86 Width (mm): 481 Depth (mm): 510 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: 0 Normal Modes Input Dependency Characteristic (ac): No Nomber of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Voltage (V): 120	Rated Input Frequency (Hz):	60-60
Rack Mountable: Height (mm): 86 Width (mm): 481 Depth (mm): 510 Total Number of Outlets: Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: Number of Surge Protected Only Outlets: Voltage Independent Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120	Rated Output Voltage (V):	120-120
Height (mm): 86 Width (mm): 481 Depth (mm): 510 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: 0 Number of Surge Protected Only Outlets: 0 Normal Mode(s) Input Dependency Characteristic (ac): No Noundlar UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Voltage (V): 120	Rated Output Frequency (Hz):	60-60
Width (mm): Depth (mm): 510 Total Number of Outlets: Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: Number of Surge Protected Only Outlets: Voltage Independent Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Test Input Voltage (V rms): Test Input Frequency (Hz): Test Output Voltage (V): 120	Rack Mountable:	No
Depth (mm): Total Number of Outlets: Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Test Input Voltage (V rms): Test Input Frequency (Hz): 60 Test Output Voltage (V):	Height (mm):	86
Total Number of Outlets: Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: O Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Test Input Voltage (V rms): Test Input Frequency (Hz): Test Output Voltage (V): 8 O Voltage Independent 120 120	Width (mm):	481
Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Output Voltage (V): 120	Depth (mm):	510
Protected Outlets: Number of Surge Protected Only Outlets: Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Output Voltage (V): 120	Total Number of Outlets:	8
Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120	Number of Battery Backup and Surge Protected Outlets:	8
Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120	Number of Surge Protected Only Outlets:	0
Number of Normal Modes: Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120	Normal Mode(s) Input Dependency Characteristic (ac):	Voltage Independent
Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120	Modular UPS:	No
Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120	Number of Normal Modes:	Single-normal-mode
Test Input Frequency (Hz): 60 Test Output Voltage (V): 120	Default Normal Mode (ac):	Voltage Independent
Test Output Voltage (V): 120	Test Input Voltage (V rms):	120
, ,	Test Input Frequency (Hz):	60
Test Output Frequency (Hz): 60	Test Output Voltage (V):	120
	Test Output Frequency (Hz):	60

Efficiency at 25% Load Min Config Lowest Dependency (ac):	98.1
Efficiency at 50% Load Min Config Lowest Dependency (ac):	98.7
Efficiency at 75% Load Min Config Lowest Dependency (ac):	98.7
Efficiency at 100% Load Min Config Lowest Dependency (ac):	98.5
Weighted Efficiency Calc Min Config Lowest Dependency:	98.6
Efficiency (%):	98.6
Modular UPS Module Tested Model Number:	N/A
Energy Storage Mechanism:	Battery
Energy Storage System Technology:	Valve Regulated Lead-acid Battery
Energy Storage System Configuration:	Integral
Energy Storage System Removable to Another Room:	N/A
Energy Storage System Runtime at 100% Load (min.):	4
Energy Storage System Runtime at 50% Load (min.):	14
Energy Storage System Warranty (yrs):	3
Energy Storage System Information URL:	https://minutemanups.com/uninterruptible-power-supply/
Battery Recycling URL:	https://minutemanups.com/contact/
Network Connections Available:	Ethernet,USB Port
Communication Protocols:	HTTP,HTTPS,SNMP (v1, 2 or 3)
Manufacturer Take Back Program:	Yes
Manufacturer Take Back Program URL:	https://minutemanups.com/contact/
Model Web Page URL:	https://minutemanups.com/uninterruptible-power-supply/pro-rt2u-line-interactive-uninterruptible-power-supply/
Test Method Guidelines:	N/A
Date Available on Market:	2025-01-01
Date Certified:	2024-08-02
Markets:	United States, Canada
ENERGY STAR Certified:	Yes

Captured On: 05/01/2025