

CyberPower - OL1KRTHD : OL1KRTHD

Final Name:3892592Brand Name:CyberPowerWodel Name:OL1KRTHDWodel Number:OL1KRTHDPower Conversion Mechanism:StaticWinimum Configuration Tested ModelOL750RMNumber:600Configuration (W):750Apparent Output Power Rating Minimum750Configuration (VA):Number:Active Output Power Rating Minimum000Configuration (VA):000Maximum Configuration Tested Model0L1KRTHDSonfiguration (VA):000Maximum Configuration Tested Model0L1KRTHDSonfiguration (VA):000Maximum Configuration (VA):000Maximum Configuration (VA):000Sonfiguration (VY):Double ConversionFopology (ac):Double Conversion (VFI)Application:ac - Double Conversion (VFI)Application:Data Center,Consumer,CommercialRated Input Voltage (Vrms):50-60Rated Output Frequency (Hz):50-60Rated Output Voltage (V):100-125Rated Output Frequency (Hz):50-60Rated Output Frequency (Hz):50-60Rated Mountable:YesRack Mount Height (U):2400433Sopola433SopolaSopolaSofial Number of Outlets:88SopolaNicth (mm):6Sopola50-60Sopola50-60Sopola50-60Sopola50-60Sopo		
Arand Name:CyberPowerWodel Name:OL1KRTHDWodel Number:OL1KRTHDPower Conversion Mechanism:StaticPower Conversion Mechanism:StaticNumber:OL750RMStative Output Power Rating Minimum600Configuration (W):Active Output Power Rating MinimumConfiguration (W):750Apparent Output Power Rating Minimum0L1KRTHDConfiguration (W):OL1KRTHDConfiguration (W):0L1KRTHDConfiguration (W):Double ConversionConfiguration (W):Double ConversionConfiguration (W):Double ConversionConfiguration (W):Data Center,Consumer,CommercialApplication:Data Center,Consumer,CommercialRated Input Voltage (V rms):50-60Rated Output Frequency (Hz):50-60Rated Output Frequency (Hz):50-60Rated Output Frequency (Hz):2Stated Output Frequency (Hz):50-60Rated Munt Height (U):2Stated Numt Height (U):3Stated Numt Height (U):8Stated Numt Heig	Specifications	
Note in the interventionOut it RTHDWodel Name:OLT KRTHDPower Conversion Mechanism:StaticWinnum Configuration Tested ModelOL750RMNumber:600Configuration (W):600Configuration (W):750Configuration (W):0L1KRTHDConfiguration (W):0L1KRTHDConfiguration (W):0L1KRTHDConfiguration (W):0L1KRTHDConfiguration (W):000Configuration (W):000Configuration (W):0uble ConversionConfiguration (W):0uble Conversion (VFI)Active Output Power Rating Maximum Configuration (W):0uble Conversion (VFI)Application:0uble Conversion (VFI)Application:0uo125Rated Input Voltage (V rms):100-125Rated Input Voltage (V):0uo125Rated Unput Frequency (Hz):0uo125Rated Output Voltage (V):0uo125Rated Output Frequency (Hz):0uo125Rated Noutbel:9uo1200 <trr>Rated Nout</trr>	ENERGY STAR Unique ID:	3892592
Active Output Power Rating Minimum Configuration Tested ModelOLTKRTHDActive Output Power Rating Minimum Configuration (W):600Active Output Power Rating Minimum Configuration (W):750Apparent Output Power Rating Minimum Configuration (W):0L1KRTHDApparent Output Power Rating Minimum Configuration (W):000Attive Output Power Rating Maximum Configuration (W):000Active Output Power Rating Maximum Configuration (W):000Application:000Application:000Rated Input Voltage (V rms):100-125Rated Output Voltage (V):00-125Rated Output Victage (V):00-60Rated Output Frequency (Hz):50-60Raked Mountable:YesRaked Mountable:433Active (M):300Application:60Application:60Application:60Application:60Application:60Application:60App	Brand Name:	CyberPower
Power Conversion Mechanism:StaticWinimum Configuration Tested Model Number:0.750RMActive Output Power Rating Minimum Configuration (W):600Apparent Output Power Rating Minimum Configuration (VA):750Maximum Configuration Tested Model Wumber:0.11KRTHDActive Output Power Rating Maximum Configuration (WA):0.100Active Output Power Rating Maximum Configuration (W):0.000Active Output Power Rating Maximum Configuration (W):0.000Active Output Power Rating Maximum Configuration (W):0.000Active Output Power Rating Maximum Configuration (W):0.000Appleation:0.000Application:0.000Acted Input Voltage (Vrms):0.0125Rated Input Voltage (VI):0.000Rated Output Prequency (Hz):0.000Rated Output Frequency (Hz):0.000Rated Nountable:VesRated Mountable:0.000With (mm):0.000Active Output Frequency (Hz):0.000Active Output Frequency (Hz):0.000Active Output Frequency (Hz):0.000Active Output Frequency (Hz):0.000Rated Mountable:1.0000Configuration:0.000Configuration:0.0000Configuration:0.00000000000000000000000000000000000	Model Name:	OL1KRTHD
Winnum Configuration Tested Model Number:0.1750RMActive Output Power Rating Minimum Configuration (W):600Apparent Output Power Rating Minimum Configuration (VA):750Apparent Output Power Rating Minimum Configuration (VA):0.11KRTHDAutimum Configuration Tested Model Number:0.000Active Output Power Rating Maximum Configuration (W):0.000Active Output Power Rating Maximum Configuration (W):0.000Active Output Power Rating Maximum Configuration (W):0.000Application:0.000Application:0.000Application:0.000Application:0.000Rated Input Voltage (Vrms):0.0125Rated Output Frequency (Hz):50-60Rated Output Voltage (V):100-125Rated Output Frequency (Hz):50-60Rated Nountable:YesRated Nountable:433Active Mumber of Outlets:8Active Mumber of Outlets:8Mumber of Battery Backup and Surge8	Model Number:	OL1KRTHD
Number:Image: Configuration (W):Active Output Power Rating Minimum Configuration (W):600Apparent Output Power Rating Minimum Configuration (VA):750Maximum Configuration Tested Model womber:0.1KRTHDActive Output Power Rating Maximum Configuration (W):0.00Active Output Product Type Combined:0.00Acted Input Voltage (Vrms):0.00Rated Input Voltage (Vrms):0.00Rated Output Prequency (Hz):0.00Rated Output Prequency (Hz):0.00Rated Output Frequency (Hz):0.00Rated Nountable:0.00Rated Nountable:0.00Active Context0.00Active Context0.00Active Context0.00Active Context0.00Active Context0.00Active Context0.00Active Context0.00Active Context0.00Active Context	Power Conversion Mechanism:	Static
Configuration (W):Image: Configuration (W):Apparent Output Power Rating Minimum Configuration (VA):750Maximum Configuration Tested Model Number:0L1KRTHDActive Output Power Rating Maximum Configuration (W):1000Configuration (W):0ouble ConversionFopology (ac):Double Conversion (VFI)Application:Data Center,Consumer,CommercialRated Input Voltage (V rms):100-125Rated Input Frequency (Hz):50-60Rated Output Frequency (Hz):50-60Rated Mountable:YesRack Mountable:2Height (mm):86Vidth (mm):290Kotter of Outlets:8Number of Battery Backup and Surge8Number of Battery Backup and Surge8	Minimum Configuration Tested Model Number:	OL750RM
Configuration (VA):Configuration Tested ModelOL1KRTHDNumber:1000Active Output Power Rating Maximum1000Configuration (W):Double ConversionFopology (ac):Double Conversion (VFI)Fopology and Product Type Combined:ac - Double Conversion (VFI)Application:Data Center,Consumer,CommercialRated Input Voltage (V rms):100-125Rated Input Frequency (Hz):50-60Rated Output Frequency (Hz):50-60Rated Output Frequency (Hz):50-60Rated Mount Height (U):2Rated Mount Height (U):2Rated Mount Height (U):36Rated Mount Height (U):433Control (Control):390Ratel Number of Outlets:8Rater Mount Policies:8Rater Mumber of Battery Backup and Surge8	Active Output Power Rating Minimum Configuration (W):	600
Number:Image: Constraint of the second s	Apparent Output Power Rating Minimum Configuration (VA):	750
Configuration (W):Double ConversionFopology (ac):Double Conversion (VFI)Fopology and Product Type Combined:ac - Double Conversion (VFI)Application:Data Center,Consumer,CommercialRated Input Voltage (V rms):100-125Rated Input Frequency (Hz):50-60Rated Output Voltage (V):100-125Rated Output Voltage (V):50-60Rated Output Frequency (Hz):50-60Rated Mountable:YesRack Mountable:2Rack Mount Height (U):8Application:300Poepth (mm):290South Constant South Sou	Maximum Configuration Tested Model Number:	OL1KRTHD
Fopology and Product Type Combined:ac - Double Conversion (VFI)Application:Data Center,Consumer,CommercialAted Input Voltage (V rms):100-125Ated Input Frequency (Hz):50-60Ated Output Voltage (V):100-125Ated Output Frequency (Hz):50-60Ated Mountable:YesAck Mount Height (U):2Ack Mount Height (U):36Ack Mount Height (U):290Ated Number of Outlets:8Actage Number of Battery Backup and Surge8	Active Output Power Rating Maximum Configuration (W):	1000
Application:Data Center,Consumer,CommercialRated Input Voltage (V rms):100-125Rated Input Frequency (Hz):50-60Rated Output Voltage (V):100-125Rated Output Frequency (Hz):50-60Rated Output Frequency (Hz):50-60Rated Mountable:YesRack Mount Height (U):2Height (mm):86Vidth (mm):290Opth (mm):8Number of Outlets:8Number of Battery Backup and Surge8	Topology (ac):	Double Conversion
Rated Input Voltage (V rms):100-125Rated Input Frequency (Hz):50-60Rated Output Voltage (V):100-125Rated Output Frequency (Hz):50-60Rack Mountable:YesRack Mount Height (U):2Height (mm):86Nidth (mm):290Opeth (mm):290Fotal Number of Outlets:8Number of Battery Backup and Surge8	Topology and Product Type Combined:	ac - Double Conversion (VFI)
Rated Input Frequency (Hz):50-60Rated Output Voltage (V):100-125Rated Output Frequency (Hz):50-60Rack Mountable:YesRack Mount Height (U):2Height (mm):86Vidth (mm):290Depth (mm):90Total Number of Outlets:8Number of Battery Backup and Surge8	Application:	Data Center,Consumer,Commercial
Rated Output Voltage (V):100-125Rated Output Frequency (Hz):50-60Rack Mountable:YesRack Mount Height (U):2Height (mm):86Vidth (mm):433Oepth (mm):290Fotal Number of Outlets:8Number of Battery Backup and Surge8	Rated Input Voltage (V rms):	100-125
Rated Output Frequency (Hz):50-60Rack Mountable:YesRack Mount Height (U):2Height (mm):86Nidth (mm):433Opth (mm):290Total Number of Outlets:8Number of Battery Backup and Surge8	Rated Input Frequency (Hz):	50-60
Rack Mountable:YesRack Mount Height (U):2Height (mm):86Width (mm):433Depth (mm):290Total Number of Outlets:8Number of Battery Backup and Surge8	Rated Output Voltage (V):	100-125
Rack Mount Height (U):2Height (mm):86Width (mm):433Depth (mm):290Total Number of Outlets:8Number of Battery Backup and Surge8	Rated Output Frequency (Hz):	50-60
Height (mm):86Width (mm):433Depth (mm):290Total Number of Outlets:8Number of Battery Backup and Surge8	Rack Mountable:	Yes
Width (mm): 433 Depth (mm): 290 Total Number of Outlets: 8 Number of Battery Backup and Surge 8	Rack Mount Height (U):	2
Depth (mm): 290 Total Number of Outlets: 8 Number of Battery Backup and Surge 8	Height (mm):	86
Fotal Number of Outlets: 8 Number of Battery Backup and Surge 8	Width (mm):	433
Number of Battery Backup and Surge 8	Depth (mm):	290
	Total Number of Outlets:	8
	Number of Battery Backup and Surge Protected Outlets:	8
Number of Surge Protected Only Outlets: 0	Number of Surge Protected Only Outlets:	0
	Normal Mode(s) Input Dependency Characteristic (ac):	Voltage and Frequency Independent, Voltage and Frequency Dependent
No	Modular UPS:	No
Number of Normal Modes: Multiple-normal-mode	Number of Normal Modes:	Multiple-normal-mode
Default Normal Mode (ac): Voltage and Frequency Independent	Default Normal Mode (ac):	Voltage and Frequency Independent

Test Input Voltage (V rms):	125
Test Input Frequency (Hz):	60
Test Output Voltage (V):	125
Test Output Frequency (Hz):	60
Total Input Power in W at 0% Load Min Config Lowest Dependency (ac):	21.62
Total Input Power in W at 0% Load Min Config Highest Dependency (ac):	21.37
Efficiency at 25% Load Min Config Lowest Dependency (ac):	84.4
Efficiency at 25% Load Min Config Highest Dependency (ac):	87.6
Efficiency at 50% Load Min Config Lowest Dependency (ac):	90.0
Efficiency at 50% Load Min Config Highest Dependency (ac):	93.5
Efficiency at 75% Load Min Config Lowest Dependency (ac):	91.7
Efficiency at 75% Load Min Config Highest Dependency (ac):	95.5
Efficiency at 100% Load Min Config Lowest Dependency (ac):	92.2
Efficiency at 100% Load Min Config Highest Dependency (ac):	96.5
Weighted Efficiency Calc Min Config Lowest Dependency:	91.3
Weighted Efficiency Calc Min Config Highest Dependency:	93.8
Minimum Configuration Input Power Factor Highest-Input Dependency:	0.99
Total Input Power in W at 0% Load Max Config Lowest Dependency (ac):	24.62
Total Input Power in W at 0% Load Max Config Highest Dependency (ac):	22.9
Efficiency at 25% Load Max Config Lowest Dependency (ac):	87.5
Efficiency at 25% Load Max Config Highest Dependency (ac):	91.4
Efficiency at 50% Load Max Config Lowest Dependency (ac):	90.7
Efficiency at 50% Load Max Config Highest Dependency (ac):	95.3
Efficiency at 75% Load Max Config Lowest Dependency (ac):	91.7
Efficiency at 75% Load Max Config Highest Dependency (ac):	96.5
Efficiency at 100% Load Max Config Lowest Dependency (ac):	91.8
Efficiency at 100% Load Max Config Highest Dependency (ac):	97.0

Weighted Efficiency Calc Max Config Lowest Dependency:	91.4
Weighted Efficiency Calc Max Config Highest Dependency:	95.3
Maximum Configuration Input Power Factor Lowest-Input Dependency:	0.99
Maximum Configuration Input Power Factor Highest-Input Dependency:	0.99
Efficiency (%):	91.4
Modular UPS Module Tested Model Number:	N/A
Energy Storage Mechanism:	Battery
Energy Storage System Technology:	Valve Regulated Lead-acid Battery
Energy Storage System Configuration:	Integral
Energy Storage System Removable to Another Room:	No
Energy Storage System Runtime at 100% Load (min.):	3
Energy Storage System Runtime at 50% Load (min.):	12
Energy Storage System Warranty (yrs):	3
Energy Storage System Information URL:	http://www.cyberpowersystems.com/
Network Connections Available:	Serial Port,Ethernet,USB Port
Communication Protocols:	HTTP,HTTPS,SNMP (v1, 2 or 3)
Manufacturer Take Back Program:	Yes
Manufacturer Take Back Program URL:	https://www.cyberpowersystems.com/faqs/how-do-i-dispose-of-my- ups/
Model Web Page URL:	http://www.cyberpowersystems.com/
Test Method Guidelines:	http://www.cyberpowersystems.com/
Date Available on Market:	2025-02-15
Date Certified:	2025-01-03
Markets:	United States
ENERGY STAR Certified:	Yes

Additional Model Information

OL1KRM, OL1KRTHDN, OL1KRMN, OL1KRTHDTAA, OL1KRTHDTAAN, OL1KRTHDLI, OL1KRTHDLIN,OL1KRM, OL1KRT HDN, OL1KRMN, OL1KRTHDTAA, OL1KRTHDTAAN, OL1KRTHDLI, OL1KRTHDLIN,

UPC Codes 649532937264

Captured On: 06/18/2025