

MINUTEMAN Power Technologies - EC1000RTXL2U: 90000780

| Specifications | |
|--|-----------------------------------|
| ENERGY STAR Unique ID: | 3892643 |
| Brand Name: | MINUTEMAN Power Technologies |
| Model Name: | EC1000RTXL2U |
| Model Number: | 90000780 |
| Power Conversion Mechanism: | Static |
| Minimum Configuration Tested Model Number: | EC1000RTXL2U |
| Active Output Power Rating Minimum Configuration (W): | 900 |
| Apparent Output Power Rating Minimum Configuration (VA): | 1000 |
| Maximum Configuration Tested Model Number: | N/A |
| Topology (ac): | Double Conversion |
| Topology and Product Type Combined: | ac - Double Conversion (VFI) |
| Application: | Commercial |
| Rated Input Voltage (V rms): | 120-120 |
| Rated Input Frequency (Hz): | 50-60 |
| Rated Output Voltage (V): | 120-120 |
| Rated Output Frequency (Hz): | 50-60 |
| Rack Mountable: | Yes |
| Rack Mount Height (U): | 2 |
| Height (mm): | 88 |
| Width (mm): | 479 |
| Depth (mm): | 407 |
| Total Number of Outlets: | 6 |
| Number of Battery Backup and Surge Protected Outlets: | 6 |
| Number of Surge Protected Only Outlets: | 0 |
| Normal Mode(s) Input Dependency Characteristic (ac): | Voltage and Frequency Independent |
| Modular UPS: | Yes |
| Number of Normal Modes: | Single-normal-mode |
| Default Normal Mode (ac): | Voltage and Frequency Independent |

| Test Input Voltage (V rms): | 120 |
|--|---|
| Test Input Frequency (Hz): | 60 |
| Test Output Voltage (V): | 120 |
| Test Output Frequency (Hz): | 60 |
| Total Input Power in W at 0% Load Min Config Lowest Dependency (ac): | 30.8 |
| Efficiency at 25% Load Min Config Lowest Dependency (ac): | 85.3 |
| Efficiency at 50% Load Min Config Lowest Dependency (ac): | 90.0 |
| Efficiency at 75% Load Min Config Lowest Dependency (ac): | 91.2 |
| Efficiency at 100% Load Min Config Lowest Dependency (ac): | 91.5 |
| Weighted Efficiency Calc Min Config Lowest Dependency: | 90.9 |
| Efficiency (%): | 90.9 |
| Modular UPS Module Tested Model Number: | N/A |
| Energy Storage Mechanism: | Battery |
| Energy Storage System Technology: | Valve Regulated Lead-acid Battery |
| Energy Storage System Configuration: | Integral |
| Energy Storage System Removable to Another Room: | No |
| Energy Storage System Runtime at 100% Load (min.): | 2 |
| Energy Storage System Runtime at 50% Load (min.): | 10 |
| Energy Storage System Warranty (yrs): | 3 |
| Energy Storage System Information URL: | N/A |
| Network Connections Available: | Serial Port,Other,Ethernet,USB Port |
| Communication Protocols: | None |
| Manufacturer Take Back Program: | Yes |
| Model Web Page URL: | https://minutemanups.com/ |
| Test Method Guidelines: | N/A |
| Date Available on Market: | 2025-01-01 |
| Date Certified: | 2024-12-12 |
| Markets: | United States, Switzerland, Taiwan, Japan, Canada |
| ENERGY STAR Certified: | Yes |

Captured On: 06/19/2025